

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

1 Identification

- **Product identifier**

- **Trade name:** Sure Fil™ J52 - Part A

- **Article number:** 87-307679A

- **Application of the substance / the mixture**

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Dayton® Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 2 H401 Toxic to aquatic life.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

epoxy resin

- **Hazard statements**

Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life.

- **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 1

Reactivity = 0

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part A

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)

| | | |
|-----------------|---|----------------|
| HEALTH | 1 | Health = 1 |
| FIRE | 1 | Fire = 1 |
| PHYSICAL HAZARD | 0 | Reactivity = 0 |

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

| | | |
|------------|---|--------|
| 25085-99-8 | Diglycidyl ether of bisphenol A homopolymer | 50-75% |
| 84852-15-3 | 4-nonylphenol, branched | ≤ 10% |
| 14807-96-6 | Talc (Mg ₃ H ₂ (SiO ₃) ₄) | ≤ 5% |
| 13463-67-7 | titanium dioxide | ≤ 5% |
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | ≤ 5% |
| 471-34-1 | calcium carbonate | ≤ 2.5% |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms receive medical treatment.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Seek medical treatment.

· Information for doctor:

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part A

(Contd. of page 2)

- **Advice for firefighters**

- **Protective equipment:**

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- **Information about protection against explosions and fires:** No special measures required.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:** cool and dry

- **Requirements to be met by storerooms and receptacles:** Store in a cool dry location.

- **Information about storage in one common storage facility:**

Store away from incompatible materials.

Store away from foodstuffs.

- **Further information about storage conditions:** Keep receptacle tightly sealed.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

471-34-1 calcium carbonate

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV TLV withdrawn

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part A

(Contd. of page 3)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Color: Grey

· **Odor:** Mild

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

· **Flash point:** >94 °C (>201 °F)

· **Flammability (solid, gaseous):** Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

· **Vapor pressure:** Not determined.

· **Density at 20 °C (68 °F):** 1.19 g/cm³ (9.931 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part A

(Contd. of page 4)

- | | |
|---|-----------------|
| · Partition coefficient (n-octanol/water): Not determined. | |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 0.0 % |
| · Solids content: 100.0 % | |
| · Other information No further relevant information available. | |
| · Volatile Organic Compounds: Not determined | |

10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

25085-99-8 Diglycidyl ether of bisphenol A homopolymer

| | | |
|--------|------|----------------------|
| Oral | LD50 | 5000 mg/kg (rat) |
| Dermal | LD50 | 20000 mg/kg (rabbit) |

64742-48-9 Naphtha (petroleum), hydrotreated heavy

| | | |
|--------|------|-------------------|
| Oral | LD50 | >5000 mg/kg (rat) |
| Dermal | LD50 | >3000 mg/kg (rab) |

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:**
Strong irritant with the danger of severe eye injury.
Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

| | | |
|------------|---|----|
| 14807-96-6 | Talc (Mg ₃ H ₂ (SiO ₃) ₄) | 2B |
| 13463-67-7 | titanium dioxide | 2B |
| 14808-60-7 | Quartz (SiO ₂) | 1 |

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part A

(Contd. of page 5)

| | |
|--|----------------------------|
| · NTP (National Toxicology Program) | |
| 14808-60-7 | Quartz (SiO ₂) |
| · OSHA-Ca (Occupational Safety & Health Administration) | |
| None of the ingredients is listed. | |

K

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (Self-assessment): slightly hazardous for water
 Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of as normal garbage. Do not allow product to reach sewage system.
 It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, ADN, IATA · IMDG | <p>Not Regulated UN3082</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT, ADR, ADN, IATA · IMDG | <p>Not Regulated ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin), MARINE POLLUTANT</p> |

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016


Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part A

(Contd. of page 6)

· **Transport hazard class(es)**· **DOT, ADR, ADN, IATA**· **Class**

Not Regulated

· **IMDG**· **Class**

9 Miscellaneous dangerous substances and articles

· **Label**

9

· **Packing group**· **DOT, ADR, IMDG, IATA**

III

· **Environmental hazards:**· **Marine pollutant:**

Yes

Symbol (fish and tree)

· **Special precautions for user**· **EMS Number:**

F-A,S-F

· **Stowage Category**

A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **DOT**· **Remarks:**

Add "Marine Pollutant" to end of proper shipping name if shipping in a bulk container (>119 gallons).

· **ADR**· **U.S. Domestic Ground Shipments:**

Same as listed for Standard Shipments above.

· **U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:**

Same as listed for Standard Shipments above.

· **Emergency Response Guide (ERG) Number:**

Not determine

· **IMDG**· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

Not Regulated

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part A

(Contd. of page 7)

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

| | | |
|------------|-------------------------|------|
| 84852-15-3 | 4-nonylphenol, branched | ≤10% |
|------------|-------------------------|------|

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

| | |
|------------|------------------|
| 13463-67-7 | titanium dioxide |
|------------|------------------|

| | |
|------------|----------------------------|
| 14808-60-7 | Quartz (SiO ₂) |
|------------|----------------------------|

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

| | | |
|------------|---|----|
| 14807-96-6 | Talc (Mg ₃ H ₂ (SiO ₃) ₄) | A4 |
|------------|---|----|

| | | |
|------------|------------------|----|
| 13463-67-7 | titanium dioxide | A4 |
|------------|------------------|----|

| | | |
|------------|----------------------------|----|
| 14808-60-7 | Quartz (SiO ₂) | A2 |
|------------|----------------------------|----|

· **MAK (German Maximum Workplace Concentration)**

| | | |
|------------|---|----|
| 14807-96-6 | Talc (Mg ₃ H ₂ (SiO ₃) ₄) | 3B |
|------------|---|----|

| | | |
|------------|------------------|----|
| 13463-67-7 | titanium dioxide | 3A |
|------------|------------------|----|

| | | |
|------------|----------------------------|---|
| 14808-60-7 | Quartz (SiO ₂) | 1 |
|------------|----------------------------|---|

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

| | |
|------------|------------------|
| 13463-67-7 | titanium dioxide |
|------------|------------------|

| | |
|------------|----------------------------|
| 14808-60-7 | Quartz (SiO ₂) |
|------------|----------------------------|

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07

· **Signal word** Warning

· **Hazard-determining components of labeling:**

epoxy resin

· **Hazard statements**

Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part A

(Contd. of page 8)

· **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

· **Date of preparation / last revision** 03/17/2016 / 87

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - AcuteHazard, Category 2

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

1 Identification

- **Product identifier**
- **Trade name:** Sure Fil™ J52 - Part B
- **Article number:** 87-307679B
- **Application of the substance / the mixture**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Dayton® Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**
Acute Tox. 4 H302 Harmful if swallowed.
Skin Corr. 1C H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Aquatic Acute 3 H402 Harmful to aquatic life.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05 GHS07

- **Signal word** Danger
- **Hazard-determining components of labeling:**
4-nonylphenol, branched
2-piperazin-1-ylethylamine
cyclohex-1,2-ylenediamine
Benzyl alcohol
- **Hazard statements**
Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
Do not breathe dusts or mists.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER/doctor.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part B

(Contd. of page 1)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 3

Fire = 1

Reactivity = 2

· **HMIS-ratings (scale 0 - 4)**

| | |
|-----------------|---|
| HEALTH | 3 |
| FIRE | 1 |
| PHYSICAL HAZARD | 2 |

Health = 3

Fire = 1

Reactivity = 2

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

| | | |
|------------|----------------------------|---------|
| 84852-15-3 | 4-nonylphenol, branched | 75-100% |
| 140-31-8 | 2-piperazin-1-ylethylamine | 10-25% |
| 100-51-6 | Benzyl alcohol | ≤ 10% |
| 694-83-7 | cyclohex-1,2-ylenediamine | ≤ 2.5% |
| 124-09-4 | hexamethylenediamine | ≤ 2.5% |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**· **General information:**

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms receive medical treatment.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.· **After swallowing:**

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part B

(Contd. of page 2)

Seek medical treatment.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:**

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

· **Information about protection against explosions and fires:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool dry location.

· **Information about storage in one common storage facility:** Store away from incompatible materials.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part B

(Contd. of page 3)

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

| | |
|--------------------------------------|--|
| 100-51-6 Benzyl alcohol | |
| WEEL | Long-term value: 10 ppm |
| 124-09-4 hexamethylenediamine | |
| TLV | Long-term value: 2.3 mg/m ³ , 0.5 ppm |
| WEEL | Long-term value: 1 ppm |

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Color: Amber

- **Odor:** Ammonia-like

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

- **Flash point:** >94 °C (>201 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 315 °C (599 °F)

- **Decomposition temperature:** Not determined.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part B

(Contd. of page 4)

| | |
|---|---|
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product does not present an explosion hazard. |
| · Explosion limits: | |
| Lower: | 2.1 Vol % |
| Upper: | 10.5 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 0.1 hPa |
| · Density at 20 °C (68 °F): | 0.97 g/cm ³ (8.095 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 6.0 % |
| Solids content: | 100.0 % |
| · Other information | No further relevant information available. |
| · Volatile Organic Compounds: | Not determined |

10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

140-31-8 2-piperazin-1-ylethylamine

| | | |
|--------|------|--------------------|
| Oral | LD50 | 2140 mg/kg (rat) |
| Dermal | LD50 | 880 mg/kg (rabbit) |

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:** Strong caustic effect.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part B

(Contd. of page 5)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

| | | |
|----------|------------------|---|
| 105-60-2 | 1,6-hexanolactam | 4 |
| 71-43-2 | benzene | 1 |

· **NTP (National Toxicology Program)**

| | | |
|---------|---------|---|
| 71-43-2 | benzene | K |
|---------|---------|---|

· **OSHA-Ca (Occupational Safety & Health Administration)**

| | | |
|---------|---------|--|
| 71-43-2 | benzene | |
|---------|---------|--|

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS





Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part B

(Contd. of page 6)

14 Transport information

| | |
|--|---|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA | <p style="text-align: right;">UN1760</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT, IATA · ADR · IMDG | <p style="text-align: right;">Corrosive liquids, n.o.s. (nonylphenol) 1760 Corrosive liquids, n.o.s. (nonylphenol) CORROSIVE LIQUID, N.O.S. (nonylphenol), MARINE POLLUTANT</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: right;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="text-align: right;">8 Corrosive substances 8</p> |
| <ul style="list-style-type: none"> · ADR, IATA | <div style="text-align: right;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="text-align: right;">8 Corrosive substances 8</p> |
| <ul style="list-style-type: none"> · IMDG | <div style="text-align: right;">   </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="text-align: right;">8 Corrosive substances 8</p> |
| <ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG · IATA | <p style="text-align: right;">III II</p> |
| <ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: | <p style="text-align: right;">Product contains environmentally hazardous substances: 4-nonylphenol, branched No Symbol (fish and tree)</p> |
| <ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category · Stowage Code | <p style="text-align: right;">Warning: Corrosive substances 80 F-A,S-B B SW2 Clear of living quarters.</p> |
| <ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | <p style="text-align: right;">Not applicable.</p> |

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part B

(Contd. of page 7)

· **Transport/Additional information:**

· **ADR**

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Same as listed for Standard Shipments above.

· **U.S. Domestic Ground Shipments:**

· **U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:**

Same as listed for Standard Shipments above.

· **Emergency Response Guide (ERG) Number:**

153

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1760 CORROSIVE LIQUIDS, N.O.S., 8, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

| | |
|-----------|--------------------|
| 7664-41-7 | ammonia, anhydrous |
|-----------|--------------------|

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

| | | |
|------------|-------------------------|---------|
| 84852-15-3 | 4-nonylphenol, branched | 75-100% |
| 7664-41-7 | ammonia, anhydrous | ≤0.1% |
| 71-43-2 | benzene | ≤0.01% |

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

| | |
|---------|---------|
| 71-43-2 | benzene |
|---------|---------|

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

| | |
|---------|---------|
| 71-43-2 | benzene |
|---------|---------|

· **Chemicals known to cause developmental toxicity:**

| | |
|---------|---------|
| 71-43-2 | benzene |
|---------|---------|

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

| | | |
|---------|---------|--------|
| 71-43-2 | benzene | A, K/L |
|---------|---------|--------|

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part B

(Contd. of page 8)

| · TLV (Threshold Limit Value established by ACGIH) | | |
|--|------------------|----|
| 105-60-2 | 1,6-hexanolactam | A5 |
| 71-43-2 | benzene | A1 |
| · MAK (German Maximum Workplace Concentration) | | |
| 71-43-2 | benzene | 1 |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) | | |
| 71-43-2 | benzene | |

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

4-nonylphenol, branched
2-piperazin-1-ylethylamine
cyclohex-1,2-ylenediamine
Benzyl alcohol

· **Hazard statements**

Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

Do not breathe dusts or mists.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER/doctor.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

· **Date of preparation / last revision** 03/17/2016 / 77

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/17/2016

Reviewed on 03/17/2016

Trade name: Sure Fil™ J52 - Part B

(Contd. of page 9)

ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Corr. 1C: Skin corrosion/irritation, Hazard Category 1C
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Aquatic Acute 3: Hazardous to the aquatic environment - AcuteHazard, Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

US