

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2016

Reviewed on 01/22/2016

## 1 Identification

- **Product identifier**

- **Trade name:** Pro-Poxy™ 300 - Part A

- **Article number:** 87-140144A

- **Application of the substance / the mixture**

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Unitex®

3101 Gardner

Kansas city, MO 64120

Tel: (800) 821-5846

Fax: (816) 483-3149

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

## 2 Hazard(s) identification

- **Classification of the substance or mixture**

Eye Irrit. 2A H319 Causes serious eye irritation.

Carc. 2 H351 Suspected of causing cancer.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Warning

- **Hazard-determining components of labeling:**

Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)

titanium dioxide

- **Hazard statements**

Causes serious eye irritation.

Suspected of causing cancer.

- **Precautionary statements**

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 1

Reactivity = 0

(Contd. on page 2)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2016

Reviewed on 01/22/2016

Trade name: Pro-Poxy™ 300 - Part A

(Contd. of page 1)

### · HMIS-ratings (scale 0 - 4)

HEALTH	1	Health = 1
FIRE	1	Fire = 1
PHYSICAL HAZARD	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

### · Dangerous components:

471-34-1	calcium carbonate	≤ 5%
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	≤ 5%
13463-67-7	titanium dioxide	≤ 2.5%
2210-79-9	2,3-epoxypropyl o-tolyl ether	≤ 1%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

## 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
In the event of persistent symptoms receive medical treatment.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Seek medical treatment.
- **Information for doctor:**  
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.  
· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2016

Reviewed on 01/22/2016

Trade name: Pro-Poxy™ 300 - Part A

(Contd. of page 2)

· **Advice for firefighters**· **Protective equipment:**

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

## 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:** Do not allow product to reach sewage system or any water course.· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

· **Handling:**· **Precautions for safe handling**

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

· **Information about protection against explosions and fires:** No special measures required.· **Conditions for safe storage, including any incompatibilities**· **Storage:** cool and dry· **Requirements to be met by storerooms and receptacles:** No special requirements.· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:** Keep receptacle tightly sealed.· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:****471-34-1 calcium carbonate**

PEL Long-term value: 15\* 5\*\* mg/m<sup>3</sup>  
\*total dust \*\*respirable fraction

REL Long-term value: 10\* 5\*\* mg/m<sup>3</sup>  
\*total dust \*\*respirable fraction

TLV TLV withdrawn

· **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 4)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2016

Reviewed on 01/22/2016

Trade name: Pro-Poxy™ 300 - Part A

(Contd. of page 3)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
 Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Avoid contact with the eyes.  
 Avoid contact with the eyes and skin.
- **Breathing equipment:**  
 Use suitable respiratory protective device when high concentrations are present.  
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**  
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Wear appropriate eye protection to prevent eye contact.

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquid
Color:	Clear
Odor:	Mild
Odor threshold:	Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	260 °C (500 °F)
- **Flash point:** 249 °C (480 °F)
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:**
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not selfigniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**

Lower:	Not determined.
--------	-----------------

(Contd. on page 5)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2016

Reviewed on 01/22/2016

Trade name: Pro-Poxy™ 300 - Part A

(Contd. of page 4)

<b>Upper:</b>	Not determined.
· <b>Vapor pressure:</b>	Not determined.
· <b>Density at 20 °C (68 °F):</b>	1.202 g/cm <sup>3</sup> (10.031 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	0.0 %
<b>Solids content:</b>	100.0 %
· <b>Other information</b>	No further relevant information available.
· <b>Volatile Organic Compounds:</b>	Not determined

## 10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**25085-99-8 Diglycidyl ether of bisphenol A homopolymer**

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:**  
Strong irritant with the danger of severe eye injury.  
Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant

(Contd. on page 6)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2016

Reviewed on 01/22/2016

Trade name: Pro-Poxy™ 300 - Part A

(Contd. of page 5)

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	2B
13463-67-7	titanium dioxide	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

· **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Water hazard class 1 (Self-assessment): slightly hazardous for water
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.  
It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

## 14 Transport information

· **UN-Number**

· **DOT, ADR, ADN, IATA**

· **IMDG**

Not Regulated

UN3082

· **UN proper shipping name**

· **DOT, ADR, ADN, IATA**

· **IMDG**

Not Regulated

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S. (epoxy resin), MARINE POLLUTANT

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2016

Reviewed on 01/22/2016

Trade name: Pro-Poxy™ 300 - Part A


(Contd. of page 6)

· **Transport hazard class(es)**

· DOT, ADR, ADN, IATA

· Class

Not Regulated

· **IMDG**

· Class

9 Miscellaneous dangerous substances and articles

· Label

9

· **Packing group**

· DOT, ADR, IMDG, IATA

III

· **Environmental hazards:**

· Marine pollutant:

No

Symbol (fish and tree)

· **Special precautions for user**

· EMS Number:

F-A,S-F

· Stowage Category

A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **ADR**

· U.S. Domestic Ground Shipments:

Same as listed for Standard Shipments above.

· U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:

Same as listed for Standard Shipments above.

· **Emergency Response Guide (ERG) Number:**

Not determine

· **IMDG**

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

Not Regulated

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

None of the ingredients is listed.

(Contd. on page 8)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/22/2016

Reviewed on 01/22/2016

Trade name: Pro-Poxy™ 300 - Part A

(Contd. of page 7)

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

13463-67-7 titanium dioxide

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6 Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)

A4

13463-67-7 titanium dioxide

A4

· **MAK (German Maximum Workplace Concentration)**

14807-96-6 Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)

3B

13463-67-7 titanium dioxide

3A

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 titanium dioxide

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)

titanium dioxide

· **Hazard statements**

Causes serious eye irritation.

Suspected of causing cancer.

· **Precautionary statements**

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 9)



# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/22/2016

Reviewed on 01/22/2016

**Trade name: Pro-Poxy™ 300 - Part A**

(Contd. of page 8)

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing SDS:** Environmental, Health & Safety Department
- **Contact:** Environmental, Health & Safety Manager
- **Date of preparation / last revision** 01/22/2016 / 210
- **Abbreviations and acronyms:**

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*NIOSH: National Institute for Occupational Safety*

*OSHA: Occupational Safety & Health*

*TLV: Threshold Limit Value*

*PEL: Permissible Exposure Limit*

*REL: Recommended Exposure Limit*

*Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A*

*Carc. 2: Carcinogenicity, Hazard Category 2*

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2017

Reviewed on 02/01/2017

## 1 Identification

- **Product identifier**

- **Trade name:** Pro-Poxy™ 300 - Part B

- **Article number:** 87-140144B

- **Application of the substance / the mixture**

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Unitex®

3101 Gardner

Kansas city, MO 64120

Tel: (800) 821-5846

Fax: (816) 483-3149

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

## 2 Hazard(s) identification

- **Classification of the substance or mixture**

Acute Tox. 4 H332 Harmful if inhaled.

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

*m*-phenylenebis(methylamine)

cyclohex-1,2-ylenediamine

hexamethylenediamine

4-nonylphenol, branched

- **Hazard statements**

Harmful if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2017

Reviewed on 02/01/2017

**Trade name: Pro-Poxy™ 300 - Part B**

(Contd. of page 1)

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

*Immediately call a POISON CENTER/doctor.*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 1

Reactivity = 2

· **HMIS-ratings (scale 0 - 4)**

HEALTH	3
FIRE	1
PHYSICAL HAZARD	2

Health = 3

Fire = 1

Reactivity = 2

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

471-34-1	calcium carbonate	50-75%
1477-55-0	m-phenylenebis(methylamine)	10-25%
14808-60-7	Quartz (SiO <sub>2</sub> )	≤ 5%
694-83-7	cyclohex-1,2-ylenediamine	≤ 1%
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic	≤ 1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

· **Description of first aid measures**

· **General information:**

*Immediately remove any clothing soiled by the product.*

*In the event of persistent symptoms receive medical treatment.*

· **After inhalation:** *In case of unconsciousness place patient stably in side position for transportation.*

· **After skin contact:**

*Immediately wash with water and soap and rinse thoroughly.*

*Immediately rinse with water.*

*If skin irritation continues, consult a doctor.*

· **After eye contact:** *Rinse opened eye for several minutes under running water. Then consult a doctor.*

· **After swallowing:**

*Drink copious amounts of water and provide fresh air. Immediately call a doctor.*

*Seek medical treatment.*

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** *No further relevant information available.*

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2017

Reviewed on 02/01/2017

Trade name: Pro-Poxy™ 300 - Part B

(Contd. of page 2)

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

## 5 Fire-fighting measures

· **Extinguishing media**· **Suitable extinguishing agents:**CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.· **Special hazards arising from the substance or mixture** No further relevant information available.· **Advice for firefighters**· **Protective equipment:**

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

## 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**· **PAC-1:**

471-34-1	calcium carbonate	45 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
546-93-0	Magnesite	45 mg/m <sup>3</sup>
694-83-7	cyclohex-1,2-ylenediamine	2.1 mg/m <sup>3</sup>
156-87-6	3-aminopropan-1-ol	8.3 mg/m <sup>3</sup>
63148-62-9	Siloxanes and Silicones, di-Me	65 mg/m <sup>3</sup>

· **PAC-2:**

471-34-1	calcium carbonate	210 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>
546-93-0	Magnesite	260 mg/m <sup>3</sup>
694-83-7	cyclohex-1,2-ylenediamine	23 mg/m <sup>3</sup>
156-87-6	3-aminopropan-1-ol	91 mg/m <sup>3</sup>
63148-62-9	Siloxanes and Silicones, di-Me	720 mg/m <sup>3</sup>

· **PAC-3:**

471-34-1	calcium carbonate	1,300 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2017

Reviewed on 02/01/2017

Trade name: Pro-Poxy™ 300 - Part B

(Contd. of page 3)

546-93-0	Magnesite	1,600 mg/m <sup>3</sup>
694-83-7	cyclohex-1,2-ylenediamine	140 mg/m <sup>3</sup>
156-87-6	3-aminopropan-1-ol	550 mg/m <sup>3</sup>
63148-62-9	Siloxanes and Silicones, di-Me	4,300 mg/m <sup>3</sup>

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool dry location.
- **Information about storage in one common storage facility:** Store away from incompatible materials.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

### 471-34-1 calcium carbonate

PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	TLV withdrawn

### 1477-55-0 m-phenylenebis(methylamine)

REL	Ceiling limit value: 0.1 mg/m <sup>3</sup> Skin
TLV	Ceiling limit value: 0.1 mg/m <sup>3</sup> Skin

### 14808-60-7 Quartz (SiO<sub>2</sub>)

PEL	see Quartz listing
REL	Long-term value: 0.05* mg/m <sup>3</sup> *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m <sup>3</sup> *as respirable fraction

(Contd. on page 5)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2017

Reviewed on 02/01/2017

Trade name: Pro-Poxy™ 300 - Part B

(Contd. of page 4)

**546-93-0 Magnesite**

PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	TLV withdrawn

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Use suitable respiratory protective device when high concentrations are present.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Liquid

**Color:** Grey

· **Odor:** Distinctive

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** Undetermined.

· **Flash point:** >94 °C (>201 °F)

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2017

Reviewed on 02/01/2017

Trade name: Pro-Poxy™ 300 - Part B

(Contd. of page 5)

· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	370 °C (698 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.0 Vol %
<b>Upper:</b>	10.5 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	0.1 hPa
· <b>Density at 20 °C (68 °F):</b>	1.776 g/cm <sup>3</sup> (14.821 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	0.0 %
<b>Solids content:</b>	100.0 %
· <b>Other information</b>	No further relevant information available.
· <b>Volatile Organic Compounds:</b>	Not determined

## 10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1477-55-0 m-phenylenebis(methylamine)

Oral LD50 1040 mg/kg (rat)

Inhalative LC50/4 h 2.4 mg/l (rat)

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2017

Reviewed on 02/01/2017

Trade name: Pro-Poxy™ 300 - Part B

(Contd. of page 6)

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:** Strong caustic effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

<b>· IARC (International Agency for Research on Cancer)</b>	
14808-60-7 Quartz (SiO <sub>2</sub> )	1

<b>· NTP (National Toxicology Program)</b>	
14808-60-7 Quartz (SiO <sub>2</sub> )	K

<b>· OSHA-Ca (Occupational Safety &amp; Health Administration)</b>	
None of the ingredients is listed.	

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
- Water hazard class 1 (Self-assessment): slightly hazardous for water
- Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
- Must not be disposed of as normal garbage. Do not allow product to reach sewage system.
- It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

(Contd. on page 8)



# Safety Data Sheet

acc. to OSHA HCS




Printing date 02/01/2017

Reviewed on 02/01/2017

Trade name: Pro-Poxy™ 300 - Part B

(Contd. of page 7)

## 14 Transport information

<ul style="list-style-type: none"> <li>· UN-Number</li> <li>· DOT, ADR, IMDG, IATA</li> </ul>	<p style="margin: 0;">UN1760</p>	
<ul style="list-style-type: none"> <li>· UN proper shipping name</li> <li>· DOT</li> <li>· ADR</li> <li>· IMDG</li> <li>· IATA</li> </ul>	<p style="margin: 0;">Corrosive liquids, n.o.s. (nonylphenol) 1760 Corrosive liquids, n.o.s. (nonylphenol), ENVIRONMENTALLY HAZARDOUS CORROSIVE LIQUID, N.O.S. (nonylphenol), MARINE POLLUTANT CORROSIVE LIQUID, N.O.S. (nonylphenol)</p>	
<ul style="list-style-type: none"> <li>· Transport hazard class(es)</li> <li>· DOT</li> </ul>	<div style="text-align: center; margin-bottom: 10px;">  </div> <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	<p style="margin: 0;">8 Corrosive substances 8</p>
<ul style="list-style-type: none"> <li>· ADR, IATA</li> </ul>	<div style="text-align: center; margin-bottom: 10px;">  </div> <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	<p style="margin: 0;">8 Corrosive substances 8</p>
<ul style="list-style-type: none"> <li>· IMDG</li> </ul>	<div style="text-align: center; margin-bottom: 10px;">  </div> <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>	<p style="margin: 0;">8 Corrosive substances 8</p>
<ul style="list-style-type: none"> <li>· Packing group</li> <li>· DOT, ADR, IMDG, IATA</li> </ul>	<p style="margin: 0;">III</p>	
<ul style="list-style-type: none"> <li>· Environmental hazards:</li> <li>· Marine pollutant:</li> </ul>	<p style="margin: 0;">No Symbol (fish and tree)</p>	
<ul style="list-style-type: none"> <li>· Special precautions for user</li> <li>· Danger code (Kemler):</li> <li>· EMS Number:</li> <li>· Segregation groups</li> <li>· Stowage Category</li> <li>· Stowage Code</li> </ul>	<p style="margin: 0;">Warning: Corrosive substances 80 F-A,S-B Alkalis A SW2 Clear of living quarters.</p>	
<ul style="list-style-type: none"> <li>· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</li> </ul>	<p style="margin: 0;">Not applicable.</p>	

(Contd. on page 9)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2017

Reviewed on 02/01/2017

Trade name: Pro-Poxy™ 300 - Part B

(Contd. of page 8)

· **Transport/Additional information:**

· **ADR**

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Same as listed for Standard Shipments above.

· **U.S. Domestic Ground Shipments:**

· **U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:**

Same as listed for Standard Shipments above.

· **Emergency Response Guide (ERG) Number:**

153

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1760 CORROSIVE LIQUIDS, N.O.S. (NONYLPHENOL), 8, III, ENVIRONMENTALLY HAZARDOUS

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

104-40-5 nonylphenol

10-25%

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

14808-60-7 Quartz (SiO<sub>2</sub>)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

14808-60-7 Quartz (SiO<sub>2</sub>)

A2

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2017

Reviewed on 02/01/2017

Trade name: Pro-Poxy™ 300 - Part B

(Contd. of page 9)

· <b>MAK (German Maximum Workplace Concentration)</b>	
14808-60-7	Quartz (SiO <sub>2</sub> )
	1

· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>	
14808-60-7	Quartz (SiO <sub>2</sub> )

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05

GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

*m*-phenylenebis(methylamine)

cyclohex-1,2-ylenediamine

hexamethylenediamine

4-nonylphenol, branched

· **Hazard statements**

Harmful if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Water hazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

· **Date of preparation / last revision** 02/01/2017 / 250

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 11)