

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

1 Identification

- **Product identifier**
- **Trade name:** Pro-Poxy™ Type III DOT - Part A
- **Article number:** 87-140333A
- **Application of the substance / the mixture**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Unitex®
3101 Gardner
Kansas city, MO 64120

Tel: (800) 821-5846
Fax: (816) 483-3149

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Aquatic Acute 3 H402 Harmful to aquatic life.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**
epoxy resin
nonylphenol
- **Hazard statements**
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves / eye protection / face protection.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part A

(Contd. of page 1)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	1	Fire = 1
PHYSICAL HAZARD	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
25085-99-8 Diglycidyl ether of bisphenol A homopolymer
- **Identification number(s)**
- **NLP Number:** 500-033-5
- **Index number:** 603-074-00-8
- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

25085-99-8	Diglycidyl ether of bisphenol A homopolymer	75-100%
2210-79-9	2,3-epoxypropyl o-tolyl ether	≤ 10%
84852-15-3	4-nonylphenol, branched	≤ 5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
In the event of persistent symptoms receive medical treatment.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Seek medical treatment.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part A

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

84852-15-3	4-nonylphenol, branched	3.9 mg/m ³
------------	-------------------------	-----------------------

- **PAC-2:**

84852-15-3	4-nonylphenol, branched	43 mg/m ³
------------	-------------------------	----------------------

- **PAC-3:**

84852-15-3	4-nonylphenol, branched	260 mg/m ³
------------	-------------------------	-----------------------

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** cool and dry
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:**
Store away from incompatible materials.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part A

(Contd. of page 3)

Store away from foodstuffs.

- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Color: Clear

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 261 °C (502 °F)

- **Flash point:** 155 °C (311 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 370 °C (698 °F)

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part A

(Contd. of page 4)

· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.122 g/cm ³ (9.363 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	0 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
· Other information	No further relevant information available.
· Volatile Organic Compounds:	Not determined

10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Reacts with acids, alkalis and oxidizing agents.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Nitrogen oxides

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

25085-99-8 Diglycidyl ether of bisphenol A homopolymer

Oral LD50 5000 mg/kg (rat)

Dermal LD50 20000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part A

(Contd. of page 5)

- **on the eye:**
Strong irritant with the danger of severe eye injury.
Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of as normal garbage. Do not allow product to reach sewage system.
It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017



Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part A

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, ADR, ADN, IATA · IMDG 	<p style="text-align: right;"><i>Not Regulated</i></p> <p style="text-align: right;">UN3082</p>
<ul style="list-style-type: none"> · UN proper shipping name · DOT, ADR, ADN, IATA · IMDG 	<p style="text-align: right;"><i>Not Regulated</i></p> <p style="text-align: right;"><i>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin), MARINE POLLUTANT</i></p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT, ADR, IATA <div style="text-align: center; margin: 10px 0;">  </div> <ul style="list-style-type: none"> · Class · Label · ADN/R Class: 	<p style="text-align: right;"><i>Not Regulated</i></p> <p style="text-align: right;">9</p> <p style="text-align: right;"><i>Not Regulated</i></p>
<ul style="list-style-type: none"> · IMDG <div style="text-align: center; margin: 10px 0;">  </div> <ul style="list-style-type: none"> · Class · Label 	<p style="text-align: right;"><i>9 Miscellaneous dangerous substances and articles</i></p> <p style="text-align: right;">9</p>
<ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG, IATA 	<p style="text-align: right;"><i>III</i></p>
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	<p style="text-align: right;"><i>Product contains environmentally hazardous substances: 4-nonylphenol, branched</i></p> <p style="text-align: right;"><i>Yes</i></p> <p style="text-align: right;"><i>Symbol (fish and tree)</i></p>
<ul style="list-style-type: none"> · Special precautions for user · EMS Number: · Stowage Category 	<p style="text-align: right;"><i>F-A,S-F</i></p> <p style="text-align: right;"><i>A</i></p>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	<p style="text-align: right;"><i>Not applicable.</i></p>
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · U.S. Domestic Ground Shipments: · U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments: · Emergency Response Guide (ERG) Number: 	<p style="text-align: right;"><i>Same as listed for Standard Shipments above.</i></p> <p style="text-align: right;"><i>Same as listed for Standard Shipments above.</i></p> <p style="text-align: right;"><i>Not determine</i></p>

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part A

(Contd. of page 7)

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	Not Regulated

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

84852-15-3	4-nonylphenol, branched	≤5%
------------	-------------------------	-----

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogeny categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **MAK (German Maximum Workplace Concentration)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part A

(Contd. of page 8)

- **Signal word** Warning
- **Hazard-determining components of labeling:**
epoxy resin
nonylphenol
- **Hazard statements**
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves / eye protection / face protection.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **National regulations:**
- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environmental, Health & Safety Department
- **Contact:** Environmental, Health & Safety Manager
- **Date of preparation / last revision** 04/04/2017 / 197
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

1 Identification

- **Product identifier**

- **Trade name:** Pro-Poxy™ Type III DOT - Part B

- **Article number:** 87-140333B

- **Application of the substance / the mixture**

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Unitex®

3101 Gardner

Kansas city, MO 64120

Tel: (800) 821-5846

Fax: (816) 483-3149

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Acute Tox. 4 H302 Harmful if swallowed.

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05

GHS07

GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

nonylphenol

3,6-diazaoctanethylenediamin

2,4,6-tris(dimethylaminomethyl)phenol

cyclohex-1,2-ylenediamine

- **Hazard statements**

Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

- **Precautionary statements**

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part B

(Contd. of page 1)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	3	Health = 3
FIRE	1	Fire = 1
PHYSICAL HAZARD	2	Reactivity = 2

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

25154-52-3	nonylphenol	50-75%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	≤ 10%
112-24-3	3,6-diazaoctanethylenediamin	≤ 10%
694-83-7	cyclohex-1,2-ylenediamine	≤ 2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
In the event of persistent symptoms receive medical treatment.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Immediately call a doctor.
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part B

(Contd. of page 2)

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**· **Suitable extinguishing agents:**CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.· **Special hazards arising from the substance or mixture** No further relevant information available.· **Advice for firefighters**· **Protective equipment:**

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**· **PAC-1:**

25154-52-3	nonylphenol	4.9 mg/m ³
9046-10-0	Polyoxypropylenediamine	4.8 mg/m ³
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	6.5 mg/m ³
112-24-3	3,6-diazaoctanethylenediamin	3 ppm
694-83-7	cyclohex-1,2-ylenediamine	2.1 mg/m ³
105-60-2	1,6-hexanolactam	3 mg/m ³
7664-41-7	ammonia, anhydrous	30 ppm
111-49-9	perhydroazepine	5.7 mg/m ³
71-43-2	benzene	52 ppm

· **PAC-2:**

25154-52-3	nonylphenol	53 mg/m ³
9046-10-0	Polyoxypropylenediamine	53 mg/m ³
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	72 mg/m ³
112-24-3	3,6-diazaoctanethylenediamin	14 ppm
694-83-7	cyclohex-1,2-ylenediamine	23 mg/m ³
105-60-2	1,6-hexanolactam	40 mg/m ³

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part B

(Contd. of page 3)

7664-41-7	ammonia, anhydrous	160 ppm
111-49-9	perhydroazepine	63 mg/m ³
71-43-2	benzene	800 ppm
· PAC-3:		
25154-52-3	nonylphenol	320 mg/m ³
9046-10-0	Polyoxypropylenediamine	320 mg/m ³
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	430 mg/m ³
112-24-3	3,6-diazaoctanethylenediamin	83 ppm
694-83-7	cyclohex-1,2-ylenediamine	140 mg/m ³
105-60-2	1,6-hexanolactam	240 mg/m ³
7664-41-7	ammonia, anhydrous	1,100 ppm
111-49-9	perhydroazepine	380 mg/m ³
71-43-2	benzene	4000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from incompatible materials.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

112-24-3 3,6-diazaoctanethylenediamin

WEEL	Long-term value: 6 mg/m ³ , 1 ppm
	Skin

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part B

(Contd. of page 4)

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Amber

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

· **Flash point:** >94 °C (>201 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 335 °C (635 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower: 1.0 Vol %

Upper: 0.0 Vol %

· **Vapor pressure:** Not determined.

· **Density at 20 °C (68 °F):** 0.97 g/cm³ (8.095 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic at 20 °C (68 °F): 0 mPas

Kinematic: Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part B

(Contd. of page 5)

· Solvent content:	
Organic solvents:	0.0 %
· Solids content: 100.0 %	
· Other information No further relevant information available.	
· Volatile Organic Compounds:	Not determined

10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

25154-52-3 nonylphenol

Oral	LD50	1620 mg/kg (rat)
------	------	------------------

112-24-3 3,6-diazaoctanethylenediamin

Oral	LD50	2500 mg/kg (rat)
------	------	------------------

Dermal	LD50	805 mg/kg (rabbit)
--------	------	--------------------

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:** Strong caustic effect.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

105-60-2	1,6-hexanolactam	4
----------	------------------	---

71-43-2	benzene	1
---------	---------	---

- **NTP (National Toxicology Program)**

71-43-2	benzene	K
---------	---------	---

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part B

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

71-43-2 benzene

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**
 Water hazard class 3 (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Water hazard class 1 (Self-assessment): slightly hazardous for water
 Must not reach bodies of water or drainage ditch undiluted or unneutralized.
 Also poisonous for fish and plankton in water bodies.
 Very toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of as normal garbage. Do not allow product to reach sewage system.
 It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

- | | |
|----------------------------------|--|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1760 |
| · UN proper shipping name | |
| · DOT | Corrosive liquids, n.o.s. (nonylphenol) |
| · ADR | 1760 Corrosive liquids, n.o.s. (nonylphenol) |
| · IMDG | CORROSIVE LIQUID, N.O.S. (nonylphenol), MARINE POLLUTANT |
| · IATA | CORROSIVE LIQUID, N.O.S. (nonylphenol) |

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part B

(Contd. of page 7)

· **Transport hazard class(es)**· **DOT**

· **Class** 8 Corrosive substances
 · **Label** 8

· **ADR, IMDG**

· **Class** 8 Corrosive substances
 · **Label** 8

· **IATA**

· **Class** 8 Corrosive substances
 · **Label** 8

· **Packing group**

· **DOT, ADR, IMDG, IATA** III

· **Environmental hazards:** Product contains environmentally hazardous substances: 4-nonylphenol, branched

· **Marine pollutant:** Yes

Symbol (fish and tree)

· **Special marking (ADR):** Symbol (fish and tree)

· **Special precautions for user** Warning: Corrosive substances

· **Danger code (Kemler):** 80

· **EMS Number:** F-A,S-B

· **Segregation groups** Alkalis

· **Stowage Category** A

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**· **DOT**

· **Remarks:** Add "Marine Pollutant" to end of proper shipping name if shipping in a bulk container (>119 gallons).

· **ADR**

· **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· **U.S. Domestic Ground Shipments:** Same as listed for Standard Shipments above.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part B

(Contd. of page 8)

· U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:	Same as listed for Standard Shipments above.
· Emergency Response Guide (ERG) Number:	Not determine
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1760 CORROSIVE LIQUIDS, N.O.S. (NONYLPHENOL), 8, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

7664-41-7	ammonia, anhydrous
-----------	--------------------

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

25154-52-3	nonylphenol	50-75%
7664-41-7	ammonia, anhydrous	≤0.1%
71-43-2	benzene	≤0.01%

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:

71-43-2	benzene
---------	---------

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

71-43-2	benzene
---------	---------

· Chemicals known to cause developmental toxicity:

71-43-2	benzene
---------	---------

· Cancerogenity categories

· EPA (Environmental Protection Agency)

71-43-2	benzene	A, K/L
---------	---------	--------

· TLV (Threshold Limit Value established by ACGIH)

105-60-2	1,6-hexanolactam	A5
----------	------------------	----

71-43-2	benzene	A1
---------	---------	----

· MAK (German Maximum Workplace Concentration)

71-43-2	benzene	I
---------	---------	---

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part B

(Contd. of page 9)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

71-43-2 benzene

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

nonylphenol

3,6-diazaoctanethylenediamin

2,4,6-tris(dimethylaminomethyl)phenol

cyclohex-1,2-ylenediamine

· **Hazard statements**

Harmful if swallowed.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

· **Precautionary statements**

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Water hazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

· **Date of preparation / last revision** 04/04/2017 / 199

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/04/2017

Reviewed on 04/04/2017

Trade name: Pro-Poxy™ Type III DOT - Part B

(Contd. of page 10)

vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2

US