

## Taper-Lock® #12 Coupler Availability

The Dayton Superior Taper-Lock® System, taper threaded mechanical rebar couplers, provide a simple, quick, cost effective, method for splicing rebar in tension and/or compression applications. Taper-lock couplers may be used with plain or deformed bars in sizes #4 through #18. Taper-Lock couplers utilize a proprietary, tapered thread on the rebar and mating couplers to mechanically splice the system. This tapered thread is designed to make installation easier, faster, and safer than conventional methods while providing in excess, specified strengths of most building codes. Taper-Lock is a Type 2, 160% specified yield, and 100% specified ultimate system.

Taper-Lock couplers are now available for splicing #12[40mm] rebar. This allows customers in Mexico and Latin America a full portfolio of engineered solutions to meet their splicing needs.

Ordering Information:

Product Code	Sales Cat	Coupler Type	Finish	Country of Origin
<b>145103</b>	D310	STANDARD COUPLER	BLACK	IMPORT
<b>145106</b>	D340	FLANGE COUPLER	BLACK	IMPORT
<b>145109</b>	D330	POSITIONAL COUPLER	BLACK	IMPORT
<b>145112</b>	D351	STANDARD END ANCHOR	BLACK	IMPORT

Please contact Customer Service for availability and pricing at 1.877.977.9600.