

TECHNICAL DATA SHEET

DESCRIPTION

The B17 - Double Flared Coil Loop Insert is made with two looped wire struts welded to a helix coil used for heavy form anchorage in mass concrete construction.

PRODUCT SPECIFICATION

- Standard length is 12" for 1", 1-1/4" and 1-1/2" diameter units.
- Standard 6" nominal flares are supplied unless other sizes requested.



FEATURES

- Made with two looped wire struts welded to a helix coil
- Ability to use the B17 insert to straddle the steel for reinforcement.

TECHNICAL DATA

Bolt Diameter x Insert Length	Flare width	Wire Strut Diameter	Safe Working Load Tension (lbs.)	Minimum Concrete Strength (psi)	Minimum Edge Distance
1" x 12" Std.	5-3/4"	0.375"	18,000	2,000	15"
1" x 12" Hvy.	5-3/4"	0.442"	27,000	2,000	15"
1-1/4" x 12" Std.	6"	0.375"	18,000	2,000	15"
1-1/4" x 12" Hvy.	6"	0.442"	27,000	2,000	15"
1-1/2" x 12" Std.	6-1/4"	0.375"	18,000	2,000	15"
1-1/2" x 12" Hvy.	6-1/4"	0.442"	27,000	2,000	15"

SWL provides a factor of safety of approximately 2 to 1.

SWL may vary with concrete weight and strength, as well as with insert setback and edge distance.

Contact the Dayton Superior Technical Service Department for variables.

RELATED PRODUCTS

- B12 - Coil Rod
- B14 - Coil Bolt
- F48 - Eye Nut
- F49 and F49A - Eye Bolt(s)

ORDERING INFORMATION

COIL LOOP INSERT DOUBLE FLARED - PLAIN

Product Code	Description	Weight
44800	1" X 12" PLAIN W/ 0.375 WIRE DIA.	2.37 LB
44820	1-1/4" X 12" PLAIN W/ 0.375 WIRE DIA.	2.45 LB
44810	1" X 12" PLAIN W/ 0.44 WIRE DIA.	2.85 LB
44830	1-1/4" X 12" PLAIN W/ 0.44 WIRE DIA.	2.94 LB
44850	1-1/2" X 12" PLAIN W/ 0.44 WIRE DIA.	3.40 LB

COIL LOOP INSERT DOUBLE FLARED - ELECTRO

GALVANIZED

Product Code	Description	Weight
44801	1" X 12" EGALV W/ 0.44 WIRE DIA.	2.87 LB

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.