


TECHNICAL DATA SHEET

DESCRIPTION

The PSBB bar support consists of a 30" section of rebar support made for composite material with interlocking ends for joining two or more sections together to create a continuous length of beam bolster.

APPLICATION

PSBB is used to support and provide proper cover for rebar in Elevated Slab, Tilt-Wall, Precast, Post-Tension, Parking Garage Decks and as a side form spacer.



FEATURES

- Cover heights from 3/4" to 3"
- High Load strength and impact resistance
- Qualifies for use as a Beam Bolster with 2-1/2" leg spacing
- Can be used individually or locked together to create any length
- Manufactured in 30" lengths and packaged in standardized boxes
- Special packaging available in 5' or 10' sections, bundled and palletized.
- Meets all requirements to qualify as a CRSI Class 1 Bar Support
- Qualifies for LEED credits

INSTALLATION

1. Per CRSI recommended guidelines for spacing

RELATED PRODUCTS

- Aztec PSB E-Z Lok Slab Bolster
- Aztec PSBU StrongBack Slab Bolster Upper
- Aztec PSC Straddle Chair
- Aztec PTC Tower Chair
- Aztec Hy-Chair

ORDERING INFORMATION

AZTEC® STRONGBACK BEAM BOLSTER

Product Code	Description	Weight
123570	3/4" X 2-1/2'	0.10 LB
220147	3/4" X 5'	0.10 LB
220148	3/4" X 10'	0.09 LB
123571	1" X 2-1/2'	0.11 LB
220149	1" X 5'	0.10 LB
220150	1" X 10'	0.11 LB
123572	1-1/4" X 2-1/2'	0.12 LB
220151	1-1/4" X 5'	0.11 LB
220152	1-1/4" X 10'	0.11 LB
123573	1-1/2" X 2-1/2'	0.12 LB
220153	1-1/2" X 5'	0.12 LB
220154	1-1/2" X 10'	0.12 LB
123574	1-3/4" X 2-1/2'	0.16 LB
220155	1-3/4" X 5'	0.12 LB
220156	1-3/4" X 10'	0.12 LB
123575	2" X 2-1/2'	0.14 LB
220157	2" X 5'	0.13 LB
220158	2" X 10'	0.13 LB
123576	2-1/4" X 2-1/2'	0.15 LB
220160	2-1/4" X 5'	0.14 LB
123577	2-1/2" X 2-1/2'	0.17 LB
220161	2-1/2" X 5'	0.15 LB
220490	2-1/2" X 10'	0.10 LB
123578	2-3/4" X 2-1/2'	0.18 LB
220491	2-3/4" X 5'	0.18 LB
123579	3" X 2-1/2'	0.18 LB
220163	3" X 5'	0.18 LB
220164	3" X 10'	0.18 LB

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com

TECHNICAL DATA SHEET**WARRANTY (ACCESSORIES)**

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.