

TECHNICAL DATA SHEET
DESCRIPTION

Clean Strip J1EF is a water-based, economical, V.O.C. compliant, concrete form release agent. Clean Strip J1EF works to ensure clean, positive release on plywood, fiberglass, aluminum, steel, urethane and other concrete forming materials and form liners. This product acts as a barrier to the adhesion of concrete while minimizing surface dusting. Properly applied, Clean Strip J1EF will not stain concrete or interfere with the adhesion of coatings.

USE

Clean Strip J1EF works to ensure clean, positive release on plywood, fiberglass, aluminum, steel, urethane and other concrete forming materials and form liners.

FEATURES

- Economical
- V.O.C. compliant
- Clean, positive release
- Minimizes surface dusting
- Reduced surface defects
- Non-staining
- Water clean up
- Biodegradable
- Certified to conform to NSF/ANSI Standard 61 by WQA
- May contribute to LEED credits
- Excellent sprayability


VOC

Contains 0 g/L.

Estimating Guide

FORM FACE MATERIAL	ESTIMATED COVERAGE
Hard/dense/smooth forms (plastic, fiberglass, steel, HDO, aluminum)	1000 – 1500 sq. ft./gal. (24.6 - 36.9 sq m/L)
Medium density overlaid plywood	1000 – 1250 sq. ft./gal. (24.6 - 30.7 sq m/L)
Dimensional or rough lumber, striated plywood	500 – 1000 sq. ft./gal. (12.3 - 24.6 sq m/L)

Packaging

PRODUCT CODE	PACKAGE	SIZE
		Liters
309374AU	Pail	18.9L
309373AU	Drum	208.20

STORAGE

Keep from freezing. Store in original containers, keeping container lids, spouts and/or bungs tightly sealed. Shelf life of 12 months in properly stored sealed containers.

Surface Preparation:

Surfaces to be treated should be clean and free of all water, dust and dirt or residues, which might transfer to the final concrete surface.

Mixing:

Stir well prior to use

Placement:

Apply during dry weather with low-pressure spray, roller or brush. Apply uniformly to assure proper coverage. Use of a fine fan tip, 0.1-0.2 gpm allows for more even coverage and avoidance of excess material. For improved application consistency and reduction in labor utilize the Dayton Spray-Pro (Item # 309233 or 309232) power spray system. Wipe excess material from forms prior to form construction and concrete placement. **FOR BEST RESULTS APPLY TO FORMS BEFORE EACH USE.**

CLEAN UP

Use clean water for clean up.

LIMITATIONS
FOR PROFESSIONAL USE ONLY

Tested against and certified to NSF/ANSI 61. This product is certified to conform to NSF/ANSI Standard 61 at a maximum surface area to volume ratio of 1.1 sq. cm./L. Forms and equipment must be clean and dry prior to use. Excessive rain after application prior to concrete placement may require re-application. When properly treated forms should have a uniform thin film, with a slight waxy feel. After use, a white residue may be visible on forms. This is normal for water based form release agents and should not be confused with concrete build up.

TECHNICAL DATA SHEET**PRECAUTIONS****READ SDS PRIOR TO USING PRODUCT**

- Use with adequate ventilation
- Wear protective clothing, gloves and eye protection (goggles, safety glasses and/or face shield)
- Keep out of the reach of children
- Do not take internally
- In case of ingestion, seek medical help immediately
- May cause skin irritation upon contact, especially prolonged or repeated. If skin contact occurs, wash immediately with soap and water and seek medical help as needed.
- If eye contact occurs, flush immediately with clean water and seek medical help as needed
- Dispose of waste material in accordance with federal, state and local requirements

MANUFACTURER

Dayton Superior Corporation (Australia) PTY LTD
31 Metrolink Circuit
Campbellfield, VIC 3061
Australia
Australia Phone: +61 1300 DAYTON (329866)
Website: www.daytonsuperior.com.au

WARRANTY

Dayton Superior Corporation ("Dayton") warrants for 12 months from the date of manufacture or for the duration of the published product shelf life, whichever is less, that at the time of shipment by Dayton, the product is free of manufacturing defects and conforms to Dayton's product properties in force on the date of acceptance by Dayton of the order. Dayton shall only be liable under this warranty if the product has been applied, used, and stored in accordance with Dayton's instructions, especially surface preparation and installation, in force on the date of acceptance by Dayton of the order. The purchaser must examine the product when received and promptly notify Dayton in writing of any non-conformity before the product is used and no later than 30 days after such non-conformity is first discovered. If Dayton, in its sole discretion, determines that the product breached the above warranty, it will, in its sole discretion, replace the non-conforming product, refund the purchase price or issue a credit in the amount of the purchase price. This is the sole and exclusive remedy for breach of this warranty. Only a Dayton officer is authorized to modify this warranty. The information in this data sheet supersedes all other sales information received by the customer during the sales process. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM, TRADE OR OTHERWISE.

Dayton shall not be liable in contract or in tort (including, without limitation, negligence, strict liability or otherwise) for loss of sales, revenues or profits; cost of capital or funds; business interruption or cost of downtime, loss of use, damage to or loss of use of other property (real or personal); failure to realize expected savings; frustration of economic or business expectations; claims by third parties (other than for bodily injury), or economic losses of any kind; or for any special, incidental, indirect, consequential, punitive or exemplary damages arising in any way out of the performance of, or failure to perform, its obligations under any contract for sale of product, even if Dayton could foresee or has been advised of the possibility of such damages. The Parties expressly agree that these limitations on damages are allocations of risk constituting, in part, the consideration for this contract, and also that such limitations shall survive the determination of any court of competent jurisdiction that any remedy provided in these terms or available at law fails of its essential purpose.