

## TECHNICAL DATA SHEET

### DESCRIPTION

Coated in zinc to help prevent rusting, the CR 200 Wedge Anchor can be used as a post-installed anchor wherever fixtures need safely secured into concrete. The slight winged expansion wedges into the concrete base, creating a solid anchor for any fixture.



### FEATURES

- 1/2" x 5-1/2" Wedge Anchor
- Corrosion Resistant
- Washer and nut included
- 1/2" bit used to pre-drill hole for 1/2" anchor

### ORDERING INFORMATION

#### CR200 WEDGE ANCHOR

| Product Code | Description                | Weight (lbs.) |
|--------------|----------------------------|---------------|
| 101636       | 5-1/2" x 1/2" DIA.<br>ZINC | 0.3           |

### INSTALLATION

1. Drill a 1/2" diameter hole perpendicular to the surface. The hole depth should take the fixture thickness into account and ensure 2-1/4" of minimum engagement.
2. Thoroughly clean the drilled hole with compressed air.
3. Position fixture in-line with the hole. Removing the nut and washer if necessary.
4. Tighten the nut of the anchor using a torque wrench until the wedge engages in the hole. Typical installation can vary between 40-60 ft-lbs.

### MANUFACTURER

Dayton Superior Corporation  
 1125 Byers Road  
 Miamisburg, OH 45342  
 Customer Service: 888-977-9600  
 Technical Services: 877-266-7732  
 Website: [www.daytonsuperior.com](http://www.daytonsuperior.com)

### WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.