### **Rebar Threading Solutions**



# D310 Taper-Lock® Standard Coupler

#### DESCRIPTION

The D310 Taper-Lock Standard Coupler is a Type 2, rebar coupler used to connect rebar. It consists of a coupler containing internal tapered female threads.

## FEATURES & BENEFITS


The D310 Taper-Lock Standard Coupler is used to connect two pieces of rebar where at least one of the bars is free to rotate.

- Available made from USA melted and rolled steel
- Easier to use and up to 25% faster installation
- Versatility to meet project needs
- Complies with most jobsite specifications

#### PRODUCT DATA

- Available in plain, epoxy coated, or galvanized finish
- Available in carbon, weldable, chromium, or stainless steel

Size	A (IN)	B (IN)
#4 [13mm]	2.36	1.02
#5 [16mm]	2.76	1.22
#6 [19mm]	2.87	1.28
#7 [22mm]	3.19	1.40
#8 [25mm]	3.62	1.62
#9 [29mm]	4.02	1.81
#10 [32mm]	4.49	2.05
#11 [36mm]	4.92	2.25
#12 [40mm]	5.47	2.54
#14 [43mm]	5.87	2.72
#18 [57mm]	7.64	3.63





Building Strength™

DAYTONSUPERIOR.COM | 800-745-3700 ©2020 Dayton Superior Corporation