

D630 Compression Only Coupler

DESCRIPTION

The Dayton Superior D630 Compression Coupler is an easy-to-install rebar coupler, perfect for applications requiring a compression-only connection.



- Available in rebar sizes #4 [13mm, 10M] through #18 [57mm, 55M]
- Develop the full ACI Type 2 requirement in compression
- Can be installed on first bar prior to second bar
- Uses readily available ratchets for assembly
- Wide inspection holes at bar end location
- Removeable and reusable
- Small profile for tight applications
- Can be used at hoop and stirrup locations

PRODUCT DATA

- ACI 318, Type 2 (Compression Only)
- ICC AC133, Type 2 (Compression Only)
- AASHTO & State Departments of Transportation (Compression Only)
- International Building Codes (IBC), Type 2 (Compression Only)

PRODUCT CODE	DESCRIPTION	WEIGHT
144842	#4 - 13MM	0.58 LB
144843	#5- 16MM	0.66 LB
144844	#6 - 19MM	0.79 LB
144845	#7 - 22MM	0.87 LB
144846	#8 - 25MM	1.35 LB
144847	#9 - 29MM	1.68 LB
144848	#10 - 32MM	1.93 LB
144849	#11 - 36MM	1.99 LB
144850	#14 - 43MM	3.03 LB
144851	#18 - 57MM	3.86 LB

