

ProAnchor WeatherMax

DESCRIPTION

ProAnchor WeatherMax is a two component high strength, styrene-free, vinyl ester anchoring adhesive used for anchoring threaded rod and reinforcing bar in cracked and uncracked concrete in accordance with ACI 355.4 and ICC-ES ESR-4554.

FEATURES & BENEFITS

- Non-sag gel consistency for horizontal and vertical installations
- Meets requirements of ACI 355.4 and ICC-ES ESR-4554
- Full cure in 45 minutes at 70 °F (21 °C)
- Ideal for cold weather installations
- Meets ASTM C881 / AASHTO M235 Type I, II, IV, & V Grade 3 Class A, B & C
- High structural strength adhesive
- Resists sustained loads up to 161 °F (72°C) temperatures
- Styrene free

PRODUCT DATA

ProAnchor WeatherMax is for use in cracked and uncracked normal weight and lightweight concrete anchoring dowels, bolts, threaded rod, pins and reinforcement steel in concrete. Install anchors in a vertical down, horizontal, upwardly inclined and overhead installations.

Resists static, wind and earthquake loading in tension and shear (IBC Seismic Design Categories A through F). ProAnchor WeatherMax can also be used in cooler and freezer applications or anywhere low temperature installations are required.



**Anchor
DesignPro
Software**

Free download - get started at:
www.DaytonSuperior.com/designPro