Tel.: (866) 329-8724

Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2023 Reviewed on 04/21/2023

1 Identification

- · Product identifier
- · Trade name: AggreGlossTM J25LVOC
- · Article number: 101155
- · Application of the substance / the mixture
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dayton® Superior

4226 Kansas Avenue

Kansas City, KS 66106

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapor.

Acute Tox. 3 H331 Toxic if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

Repr. 1B H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Aquatic Acute 2 H401 Toxic to aquatic life.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS06

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

xylene

dibutyl phthalate

ethylbenzene

n-butyl methacrylate

methyl methacrylate

· Hazard statements

Flammable liquid and vapor.

Toxic if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 04/21/2023 Reviewed on 04/21/2023

Trade name: AggreGlossTM J25LVOC

(Contd. of page 1)

Suspected of causing cancer.

May damage fertility or the unborn child.

May cause damage to the hearing organs through prolonged or repeated exposure.

Toxic to aquatic life.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
540-88-5	tert-butyl acetate	≥25-≤40%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	>20-<40%
1330-20-7		≥10-<12%
	dibutyl phthalate	≥2.5-≤5%
	ethylbenzene	≥1.1-<3.5%
108-88-3		≥0.1-<0.2%
	n-butyl methacrylate	≥0.1-<0.2%
80-62-6	methyl methacrylate	≥0.1-<0.2%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms recieve medical treatment.

(Contd. on page 3)

Printing date 04/21/2023 Reviewed on 04/21/2023

Trade name: AggreGlossTM J25LVOC

(Contd. of page 2)

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Seek medical treatment.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, sand, extinguishing powder. Do not use water.

Foam

- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- US

Printing date 04/21/2023 Reviewed on 04/21/2023

Trade name: AggreGlossTM J25LVOC

(Contd. of page 3)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · **Storage:** cool and dry
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At th	is time, the other constituents have no known exposure limits.
540-	88-5 tert-butyl acetate
PEL	Long-term value: 950 mg/m³, 200 ppm
REL	Long-term value: 950 mg/m³, 200 ppm
TLV	Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm
1330	1-20-7 xylene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI
84-7	4-2 dibutyl phthalate
PEL	Long-term value: 5 mg/m³
REL	Long-term value: 5 mg/m³
TLV	Long-term value: 5 mg/m³
100-	41-4 ethylbenzene

(Contd. on page 5)

Printing date 04/21/2023 Reviewed on 04/21/2023

Trade name: AggreGlossTM J25LVOC

(Contd. of page 4) TLV Long-term value: 87 mg/m³, 20 ppm 108-88-3 toluene PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift REL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm TLV Long-term value: 75 mg/m³, 20 ppm 80-62-6 methyl methacrylate PEL Long-term value: 410 mg/m³, 100 ppm REL Long-term value: 410 mg/m³, 100 ppm TLV Short-term value: 410 mg/m³, 100 ppm Long-term value: 205 mg/m³, 50 ppm **DSEN** Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids 100-41-4 ethylbenzene BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative) 108-88-3 toluene BEI 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene 0.03 mg/LMedium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 6)

Printing date 04/21/2023 Reviewed on 04/21/2023

Trade name: AggreGlossTM J25LVOC

(Contd. of page 5)

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

9 Physical and chemical properties

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Density at 20 °C (68 °F):

· Relative density

· Vapor density

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Eye protection: Wear appropriate eye protection to prevent eye contact.

Information on basic physical and of	chemical properties
General Information Appearance:	
Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	8.9 °C (48 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	500 °C (932 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures an possible.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	41 hPa (30.8 mm Hg)

1.07317 g/cm³ (8.9556 lbs/gal)

Not determined.

Not determined.

(Contd. on page 7)

Printing date 04/21/2023 Reviewed on 04/21/2023

Trade name: AggreGlossTM J25LVOC

		(Contd. of page
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	30.1-<55.1 %	
Solids content:	25.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No decomposition if stored and applied as directed.
- · Chemical stability No decomposition if stored and applied as directed
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Keep away from heat and sources of ignition.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC5	0 value	es that are relevant for classification:	
	1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
84-74-2	84-74-2 dibutyl phthalate		
Oral	LD50	8,000 mg/kg (rat)	
Dermal	LD50	20,000 mg/kg (rabbit)	

- Primary irritant effect:
- · on the skin: May cause skin irritation.
- on the eye:

Strong irritant with the danger of severe eye injury.

Irritating effect.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

(Contd. on page 8)

Printing date 04/21/2023 Reviewed on 04/21/2023

Trade name: AggreGlossTM J25LVOC

		(Contd. of page 7)
· Carcinoger	nic categories	
· IARC (Inte	ernational Agency for Research on Cancer)	
1330-20-7	xylene	3
100-41-4	ethylbenzene	28
108-88-3	toluene	3
80-62-6	methyl methacrylate	3
· NTP (Natio	onal Toxicology Program)	
None of the	e ingredients is listed.	
· OSHA-Ca	(Occupational Safety & Health Administration)	
None of the	e ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to Federal, State, and Local regulations.

14 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN1992
· UN proper shipping name · DOT	Flammable liquids, toxic, n.o.s. (Butyl methacrylate, methacrylic acid polymer, dibutyl phthalate)

(Contd. on page 9)

Printing date 04/21/2023 Reviewed on 04/21/2023

 $\textit{Trade name: AggreGloss}^{\text{TM}} \textit{ J25LVOC}$

	(Contd. of page
· ADR · IMDG, IATA	1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (Buty methacrylate, methacrylic acid polymer, dibutyl phthalate, ENVIRONMENTALLY HAZARDOUS FLAMMABLE LIQUID, TOXIC, N.O.S. (Butyl methacrylate)
InDO, IATA	methacrylic acid polymer, dibutyl phthalate)
· Transport hazard class(es)	
· DOT	
TONC 6	
· Class · Label	3 Flammable liquids 3, 6.1
· ADR	
· Class · Label	3 Flammable liquids 3+6.1
· IMDG	
· Class · Label	3 Flammable liquids 3/6.1
· IATA	5/0.1
· Class · Label	3 Flammable liquids 3 (6.1)
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	336
· EMS Number: · Stowage Category	F-E,S-D B
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	

Printing date 04/21/2023 Reviewed on 04/21/2023

Trade name: AggreGloss™ J25LVOC

	(Contd. of page
· Transport/Additional information:	
· ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· U.S. Domestic Ground Shipments:	Same as listed for Standard Shipments above.
· U.S. Domestic Ground Non-Bulk (119 gal or less per	
container) Shipments:	Same as listed for Standard Shipments above.
Emergency Response Guide (ERG) Number:	Not determine
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (BUTY
· ·	METHACRYLATE, METHACRYLIC ACID POLYMEN
	DIBUTYL PHTHALATE), 3 (6.1), III, ENVIRONMENTALL
	HAZARDOUS

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

1330-20-7 :	rylene	≥10-<12%
84-74-2	dibutyl phthalate	≥2.5-≤5%
100-41-4	ethylbenzene	≥1.1-<3.5
108-88-3	toluene	≥0.1-<0.2
80-62-6	methyl methacrylate	≥0.1-<0.2
TSCA (Toxi	ic Substances Control Act):	
540-88-5	tert-butyl acetate	ACTIV
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIV
28262-63-7	Butyl methacrylate, methacrylic acid polymer	ACTIV
1330-20-7	xylene	ACTIV
84-74-2	dibutyl phthalate	ACTIV
100-41-4	ethylbenzene	ACTIV
108-88-3	toluene	ACTIV
97-88-1	n-butyl methacrylate	ACTIV
80-62-6	methyl methacrylate	ACTIV
108-83-8	2,6-dimethylheptan-4-one	ACTIV

(Contd. on page 11

Printing date 04/21/2023 Reviewed on 04/21/2023

Trade name: AggreGlossTM J25LVOC

(Contd. of page 10) · Hazardous Air Pollutants 1330-20-7 xylene 84-74-2 dibutyl phthalate 100-41-4 ethylbenzene 108-88-3 toluene 80-62-6 methyl methacrylate Proposition 65 · Chemicals known to the State of California (Prop. 65) to cause cancer: 100-41-4 ethylbenzene · Chemicals known to cause reproductive toxicity for females: 84-74-2 dibutyl phthalate · Chemicals known to cause reproductive toxicity for males: 84-74-2 dibutyl phthalate · Chemicals known to cause developmental toxicity: 84-74-2 dibutyl phthalate 108-88-3 toluene · Cancerogenity categories · EPA (Environmental Protection Agency) 1330-20-7 xylene D 84-74-2 dibutyl phthalate D 100-41-4 ethylbenzene 108-88-3 toluene II 80-62-6 methyl methacrylate E, NL TLV (Threshold Limit Value established by ACGIH) 1330-20-7 xylene A4100-41-4 ethylbenzene A3108-88-3 toluene A480-62-6 methyl methacrylate A4· MAK (German Maximum Workplace Concentration) 100-41-4 ethylbenzene 3A· NIOSH-Ca (National Institute for Occupational Safety and Health)

- None of the ingredients is listed.
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms









GHS02 GHS06

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling: xylene

dibutyl phthalate ethylbenzene

Printing date 04/21/2023 Reviewed on 04/21/2023

Trade name: AggreGlossTM J25LVOC

(Contd. of page 11)

n-butyl methacrylate

methyl methacrylate

· Hazard statements

Flammable liquid and vapor.

Toxic if inhaled.

Causes skin irritation.

Causes serious eve irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

May damage fertility or the unborn child.

May cause damage to the hearing organs through prolonged or repeated exposure.

Toxic to aquatic life.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Water hazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · **Department issuing SDS:** Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- Date of preparation / last revision 04/21/2023 / 4
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

(Contd. on page 13)

Printing date 04/21/2023 Reviewed on 04/21/2023

Trade name: AggreGlossTM J25LVOC

(Contd. of page 12)

Repr. 1B: Reproductive toxicity – Category 1B STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2