

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

1 Identification

- **Product identifier**
- **Trade name:** TOP-CAST® EX 200 Wash-Off Extender
- **Article number:** 101003
- **Application of the substance / the mixture**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Dayton® Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flam. Liq. 4	H227	Combustible liquid.
Eye Irrit. 2B	H320	Causes eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Aquatic Acute 2	H401	Toxic to aquatic life.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07 GHS09

- **Signal word** Warning
- **Hazard-determining components of labeling:**
Distilled Tall Oil Fatty Acids
- **Hazard statements**
 Combustible liquid.
 Causes eye irritation.
 May cause an allergic skin reaction.
 Toxic to aquatic life.
 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
 Keep away from flames and hot surfaces. – No smoking.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wear protective gloves/protective clothing/eye protection/face protection.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: **TOP-CAST® EX 200 Wash-Off Extender**

(Contd. of page 1)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	2	Fire = 2
PHYSICAL HAZARD	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

68131-87-3	Petroleum Hydrocarbon Resin	≥2.5-<13%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	<3.75%
61790-12-3	Distilled Tall Oil Fatty Acids	≥1-<1.6%
1330-20-7	xylene	<1.2%
100-41-4	ethylbenzene	≥0.1-<0.4%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
In the event of persistent symptoms receive medical treatment.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: TOP-CAST® EX 200 Wash-Off Extender

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow product to reach sewage system or any water course.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** cool and dry
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
-----	--

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: **TOP-CAST® EX 200 Wash-Off Extender**

(Contd. of page 3)

REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Long-term value: 87 mg/m³, 20 ppm
BEI

· Ingredients with biological limit values:**1330-20-7 xylene**

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine
Medium: urine
Time: end of shift at end of workweek
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· Exposure controls**· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: TOP-CAST® EX 200 Wash-Off Extender

(Contd. of page 4)

9 Physical and chemical properties

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	68 °C (154.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	1.016 g/cm ³ (8.47852 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Fully miscible.
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	2.2 %
Water:	77.0 %
Solids content:	17.0 %
· Other information	No further relevant information available.
· Volatile Organic Compounds:	Contains less than 100 g/L.

10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: **TOP-CAST® EX 200 Wash-Off Extender**

(Contd. of page 5)

- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
128-37-0	Butylated hydroxytoluene	3
108-88-3	toluene	3
111-42-2	2,2'-iminodiethanol	2B
91-20-3	naphthalene	2B

- **NTP (National Toxicology Program)**

91-20-3	naphthalene	R
---------	-------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Water hazard class 1 (Self-assessment): slightly hazardous for water
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: TOP-CAST® EX 200 Wash-Off Extender

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**

- **DOT** NA1993

- **ADR, IMDG, IATA** UN1993

- **UN proper shipping name**

- **DOT** COMBUSTIBLE LIQUID, N.O.S

- **ADR** 1993 FLAMMABLE LIQUID, N.O.S., ENVIRONMENTALLY HAZARDOUS

- **IMDG, IATA** FLAMMABLE LIQUID, N.O.S.

- **Transport hazard class(es)**

- **DOT**



- **Class** 3 Combustible liquids

- **Label** 3

- **ADR, IMDG, IATA**



- **Class** 3 Flammable liquids

- **Label** 3

- **Packing group**

- **DOT, ADR, IMDG, IATA** III

- **Environmental hazards:**

- **Marine pollutant:** No

- **Special precautions for user**

Warning: Flammable liquids

- **Danger code (Kemler):** 30

- **EMS Number:** F-E,S-E

- **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: **TOP-CAST® EX 200 Wash-Off Extender**

(Contd. of page 7)

· **Transport/Additional information:**

· **ADR**

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Same as listed for Standard Shipments above.

· **U.S. Domestic Ground Shipments:**

· **U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:**

DOT: Not regulated (Reclassified as per 49CFR 173.150).

· **Emergency Response Guide (ERG) Number:**

Not determine

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III,
ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

1330-20-7	xylene	<1.2%
100-41-4	ethylbenzene	≥0.1-<0.4%
108-88-3	toluene	<0.1%
111-42-2	2,2'-iminodiethanol	<0.1%
91-20-3	naphthalene	<0.025%

· **TSCA (Toxic Substances Control Act):**

68131-87-3	Petroleum Hydrocarbon Resin	ACTIVE
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVE
61790-12-3	Distilled Tall Oil Fatty Acids	ACTIVE
1330-20-7	xylene	ACTIVE
141-43-5	monoethanolamine	ACTIVE
100-41-4	ethylbenzene	ACTIVE
11138-66-2	Xanthan Gum	ACTIVE
128-37-0	Butylated hydroxytoluene	ACTIVE
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	ACTIVE
108-88-3	toluene	ACTIVE
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic	ACTIVE
64741-89-5	Distillates (petroleum), solvent-refined light paraffinic	ACTIVE

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: **TOP-CAST® EX 200 Wash-Off Extender**

(Contd. of page 8)

111-42-2	2,2'-iminodiethanol	ACTIVE
91-20-3	naphthalene	ACTIVE
107-22-2	glyoxal	ACTIVE
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE

· **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
108-88-3	toluene
111-42-2	2,2'-iminodiethanol
91-20-3	naphthalene

· **Proposition 65**· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

100-41-4	ethylbenzene
111-42-2	2,2'-iminodiethanol
91-20-3	naphthalene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

· **Carcinogenity categories**· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D
108-88-3	toluene	II
91-20-3	naphthalene	C, CBD

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
128-37-0	Butylated hydroxytoluene	A4
108-88-3	toluene	A4
111-42-2	2,2'-iminodiethanol	A3
91-20-3	naphthalene	A4
107-22-2	glyoxal	A4

· **MAK (German Maximum Workplace Concentration)**

100-41-4	ethylbenzene	3A
128-37-0	Butylated hydroxytoluene	4
111-42-2	2,2'-iminodiethanol	3B
91-20-3	naphthalene	2
107-22-2	glyoxal	3B

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: TOP-CAST® EX 200 Wash-Off Extender

(Contd. of page 9)

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS09

· **Signal word** Warning

· **Hazard-determining components of labeling:**

Distilled Tall Oil Fatty Acids

· **Hazard statements**

Combustible liquid.

Causes eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

Keep away from flames and hot surfaces. – No smoking.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

· **Date of preparation / last revision** 04/21/2023 / 45

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 4: Flammable liquids – Category 4

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2