

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

## 1 Identification

- **Product identifier**

- **Trade name:** Tuf Seal J35LVOC

- **Article number:** 101092

- **Application of the substance / the mixture**

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Dayton® Superior  
4226 Kansas Avenue  
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

## 2 Hazard(s) identification

- **Classification of the substance or mixture**

Flam. Liq. 3      H226 Flammable liquid and vapor.

Acute Tox. 3      H331 Toxic if inhaled.

Skin Irrit. 2      H315 Causes skin irritation.

Eye Irrit. 2A      H319 Causes serious eye irritation.

Skin Sens. 1      H317 May cause an allergic skin reaction.

Carc. 2      H351 Suspected of causing cancer.

Repr. 1B      H360 May damage fertility or the unborn child.

STOT RE 2      H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Aquatic Acute 2      H401 Toxic to aquatic life.

Aquatic Chronic 2      H411 Toxic to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02    GHS06    GHS07    GHS08    GHS09

- **Signal word** Danger

- **Hazard-determining components of labeling:**

xylene

dibutyl phthalate

ethylbenzene

- **Hazard statements**

Flammable liquid and vapor.

Toxic if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Tuf Seal J35LVOC

(Contd. of page 1)

May damage fertility or the unborn child.

May cause damage to the hearing organs through prolonged or repeated exposure.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2
FIRE	3
PHYSICAL HAZARD	0

Health = \*2

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

540-88-5	tert-butyl acetate	≥30-≤45%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	>25-<45%
1330-20-7	xylene	≥10-<12%
84-74-2	dibutyl phthalate	≥2.5-≤5%
100-41-4	ethylbenzene	≥1.1-<3.5%
108-88-3	toluene	≥0.1-<0.2%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms receive medical treatment.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Tuf Seal J35LVOC

(Contd. of page 2)

- **After inhalation:**  
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.  
In case of unconsciousness place patient stably in side position for transportation.  
Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
Immediately rinse with water.  
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, sand, extinguishing powder. Do not use water.  
Foam
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**  
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.  
Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

US

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Tuf Seal J35LVOC

(Contd. of page 3)

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** cool and dry
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

### 540-88-5 tert-butyl acetate

PEL	Long-term value: 950 mg/m <sup>3</sup> , 200 ppm
REL	Long-term value: 950 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

### 1330-20-7 xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

### 84-74-2 dibutyl phthalate

PEL	Long-term value: 5 mg/m <sup>3</sup>
REL	Long-term value: 5 mg/m <sup>3</sup>
TLV	Long-term value: 5 mg/m <sup>3</sup>

### 100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: **Tuf Seal J35LVOC**

(Contd. of page 4)

TLV Long-term value: 87 mg/m<sup>3</sup>, 20 ppm  
BEI

**108-88-3 toluene**

PEL Long-term value: 200 ppm  
Ceiling limit value: 300; 500\* ppm  
\*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 375 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 75 mg/m<sup>3</sup>, 20 ppm  
BEI

**· Ingredients with biological limit values:****1330-20-7 xylene**

BEI 1.5 g/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: Methylhippuric acids

**100-41-4 ethylbenzene**

BEI 0.7 g/g creatinine  
Medium: urine  
Time: end of shift at end of workweek  
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-  
Medium: end-exhaled air  
Time: not critical  
Parameter: Ethyl benzene (semi-quantitative)

**108-88-3 toluene**

BEI 0.02 mg/L  
Medium: blood  
Time: prior to last shift of workweek  
Parameter: Toluene

0.03 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Toluene

0.3 mg/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Tuf Seal J35LVOC

(Contd. of page 5)

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Liquid  
**Color:** According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** Undetermined.

· **Flash point:** 10.6 °C (51.1 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 500 °C (932 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

**Lower:** Not determined.

**Upper:** Not determined.

· **Vapor pressure at 20 °C (68 °F):** 41 hPa (30.8 mm Hg)

· **Density at 20 °C (68 °F):** 1.07305 g/cm<sup>3</sup> (8.9546 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

**Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

**Dynamic:** Not determined.

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Tuf Seal J35LVOC

(Contd. of page 6)

<b>Kinematic:</b>	Not determined.
<b>Solvent content:</b>	
<b>Organic solvents:</b>	35.1-<60.1 %
<b>Solids content:</b>	15.0 %
<b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

### 84-74-2 dibutyl phthalate

Oral	LD50	8,000 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:**  
Strong irritant with the danger of severe eye injury.  
Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
108-88-3	toluene	3
80-62-6	methyl methacrylate	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Tuf Seal J35LVOC

(Contd. of page 7)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.


## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Water hazard class 1 (Self-assessment): slightly hazardous for water
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

## 14 Transport information

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>   | UN1992   |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG, IATA</b></li> </ul> | Flammable liquids, toxic, n.o.s. (Butyl acetates, Chlorobenzotrifluorides)<br>1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (BUTYL ACETATES, CHLOROBENZOTRIFLUORIDES), ENVIRONMENTALLY HAZARDOUS<br>FLAMMABLE LIQUID, TOXIC, N.O.S. (BUTYL ACETATES, CHLOROBENZOTRIFLUORIDES) |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>   |   |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> </ul>  | 3 Flammable liquids  |

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Tuf Seal J35LVOC

(Contd. of page 8)

· **Label** 3, 6.1

· **ADR**



· **Class** 3 Flammable liquids  
 · **Label** 3+6.1

· **IMDG**



· **Class** 3 Flammable liquids  
 · **Label** 3/6.1

· **IATA**



· **Class** 3 Flammable liquids  
 · **Label** 3 (6.1)

· **Packing group**  
 · **DOT, ADR, IMDG, IATA** III

· **Environmental hazards:**  
 · **Special marking (ADR):** Symbol (fish and tree)

· **Special precautions for user** Warning: Flammable liquids  
 · **Danger code (Kemler):** 336  
 · **EMS Number:** F-E,S-D  
 · **Stowage Category** B

· **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**  
 · **Excepted quantities (EQ)** Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml  
 Same as listed for Standard Shipments above.

· **U.S. Domestic Ground Shipments:**  
 · **U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:** Same as listed for Standard Shipments above.

· **Emergency Response Guide (ERG) Number:** Not determine

· **IMDG**  
 · **Limited quantities (LQ)** 5L

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Tuf Seal J35LVOC

(Contd. of page 9)

## · Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

## · UN "Model Regulation":

UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (BUTYL ACETATES, CHLOROBENZOTRIFLUORIDES), 3 (6.1), III, ENVIRONMENTALLY HAZARDOUS

## 15 Regulatory information

## · Safety, health and environmental regulations/legislation specific for the substance or mixture

## · Sara

## · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

## · Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

1330-20-7	xylene	≥10-<12%
84-74-2	dibutyl phthalate	≥2.5-≤5%
100-41-4	ethylbenzene	≥1.1-<3.5%
108-88-3	toluene	≥0.1-<0.2%
80-62-6	methyl methacrylate	>0-<0.1%

## · TSCA (Toxic Substances Control Act):

540-88-5	tert-butyl acetate	ACTIVE
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVE
28262-63-7	Butyl methacrylate, methacrylic acid polymer	ACTIVE
1330-20-7	xylene	ACTIVE
84-74-2	dibutyl phthalate	ACTIVE
100-41-4	ethylbenzene	ACTIVE
108-88-3	toluene	ACTIVE
97-88-1	n-butyl methacrylate	ACTIVE
80-62-6	methyl methacrylate	ACTIVE
108-83-8	2,6-dimethylheptan-4-one	ACTIVE

## · Hazardous Air Pollutants

1330-20-7	xylene
84-74-2	dibutyl phthalate
100-41-4	ethylbenzene
108-88-3	toluene
80-62-6	methyl methacrylate

## · Proposition 65

## · Chemicals known to the State of California (Prop. 65) to cause cancer:

100-41-4 ethylbenzene

## · Chemicals known to cause reproductive toxicity for females:

84-74-2 dibutyl phthalate

(Contd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Tuf Seal J35LVOC

(Contd. of page 10)

· **Chemicals known to cause reproductive toxicity for males:**

84-74-2 dibutyl phthalate

· **Chemicals known to cause developmental toxicity:**

84-74-2 dibutyl phthalate

108-88-3 toluene

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
84-74-2	dibutyl phthalate	D
100-41-4	ethylbenzene	D
108-88-3	toluene	II
80-62-6	methyl methacrylate	E, NL

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
108-88-3	toluene	A4
80-62-6	methyl methacrylate	A4

· **MAK (German Maximum Workplace Concentration)**

100-41-4	ethylbenzene	3A
----------	--------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02   GHS06   GHS07   GHS08   GHS09

· **Signal word** Danger

· **Hazard-determining components of labeling:**

xylene  
dibutyl phthalate  
ethylbenzene

· **Hazard statements**

Flammable liquid and vapor.  
Toxic if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
Suspected of causing cancer.  
May damage fertility or the unborn child.  
May cause damage to the hearing organs through prolonged or repeated exposure.  
Toxic to aquatic life.  
Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 12)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

**Trade name: Tuf Seal J35LVOC**

(Contd. of page 11)

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **National regulations:**

· **Water hazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

· **Date of preparation / last revision** 04/21/2023 / 2

· **Abbreviations and acronyms:**

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*NIOSH: National Institute for Occupational Safety*

*OSHA: Occupational Safety & Health*

*TLV: Threshold Limit Value*

*PEL: Permissible Exposure Limit*

*REL: Recommended Exposure Limit*

*BEI: Biological Exposure Limit*

*Flam. Liq. 3: Flammable liquids – Category 3*

*Acute Tox. 3: Acute toxicity – Category 3*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A*

*Skin Sens. 1: Skin sensitisation – Category 1*

*Carc. 2: Carcinogenicity – Category 2*

*Repr. 1B: Reproductive toxicity – Category 1B*

*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

*Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2*

*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*