

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/21/2024

Reviewed on 05/21/2024

1 Identification

- **Product identifier**
- **Trade name:** D490 High Strength Splicing Grout
- **Article number:** 114287
- **Application of the substance / the mixture**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Dayton® Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**
Skin Corr. 1C H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.
Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 1A H350 May cause cancer.
Repr. 1A H360 May damage fertility or the unborn child.
STOT SE 3 H335 May cause respiratory irritation.
STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05 GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Cement, portland, chemicals
Quartz (SiO₂)
- **Hazard statements**
Causes severe skin burns and eye damage.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
May damage fertility or the unborn child.
May cause respiratory irritation.
Causes damage to organs through prolonged or repeated exposure.
- **Precautionary statements**
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/21/2024

Reviewed on 05/21/2024

Trade name: D490 High Strength Splicing Grout

(Contd. of page 1)

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 0

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1
FIRE	0
PHYSICAL HAZARD	0

Health = 1

Fire = 0

Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

65997-15-1	Cement, portland, chemicals	≥35-<70%
14808-60-7	Quartz (SiO ₂)	≥35-<70%
554-13-2	lithium carbonate	≥0-≤1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**· **After inhalation:** Supply fresh air; consult doctor in case of complaints.· **After skin contact:** If skin irritation continues, consult a doctor.· **After eye contact:** Rinse opened eye for several minutes under running water.· **After swallowing:** Seek medical treatment.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.· **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/21/2024

Reviewed on 05/21/2024

Trade name: D490 High Strength Splicing Grout

(Contd. of page 2)

- **Advice for firefighters**

- **Protective equipment:**

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

No special measures required.

- **Methods and material for containment and cleaning up:** Pick up mechanically.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- **Information about protection against explosions and fires:** No special measures required.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** None.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

65997-15-1 Cement, portland, chemicals

PEL Long-term value: 50 mppcf or 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV Long-term value: 1* mg/m³
E; *as respirable fraction

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/21/2024

Reviewed on 05/21/2024

Trade name: D490 High Strength Splicing Grout

(Contd. of page 3)

14808-60-7 Quartz (SiO₂)

PEL	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Powder

Color: Gray

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not applicable.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not determined.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

· **Vapor pressure:** Not applicable.

· **Density at 20 °C (68 °F):** 2.68411 g/cm³ (22.3989 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not applicable.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/21/2024

Reviewed on 05/21/2024

Trade name: D490 High Strength Splicing Grout

(Contd. of page 4)

· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Insoluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Solids content:	100.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:** No irritating effect known.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

14808-60-7 Quartz (SiO₂)

I

· NTP (National Toxicology Program)

14808-60-7 Quartz (SiO₂)

K

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/21/2024

Reviewed on 05/21/2024

Trade name: D490 High Strength Splicing Grout

(Contd. of page 5)

- **Additional ecological information:**
- **General notes:** Water hazard class 1 (Self-assessment): slightly hazardous for water
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

- | | |
|---|--|
| · UN-Number
· DOT, ADR, ADN, IMDG, IATA | Not Regulated |
| · UN proper shipping name
· DOT, ADR, ADN, IMDG, IATA | Not Regulated |
| · Transport hazard class(es)
· DOT, ADR, ADN, IMDG, IATA
· Class | Not Regulated |
| · Packing group
· DOT, ADR, IMDG, IATA | Not Regulated |
| · Environmental hazards: | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · U.S. Domestic Ground Shipments: | Same as listed for Standard Shipments above. |
| · U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments: | Same as listed for Standard Shipments above. |
| · Emergency Response Guide (ERG) Number: | Not determine |
| · UN "Model Regulation": | Not Regulated |

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/21/2024

Reviewed on 05/21/2024

Trade name: D490 High Strength Splicing Grout

(Contd. of page 6)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

554-13-2	lithium carbonate	≥0-≤1%
----------	-------------------	--------

· TSCA (Toxic Substances Control Act):

65997-15-1	Cement, portland, chemicals	ACTIVE
------------	-----------------------------	--------

14808-60-7	Quartz (SiO ₂)	ACTIVE
------------	----------------------------	--------

554-13-2	lithium carbonate	ACTIVE
----------	-------------------	--------

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

554-13-2	lithium carbonate
----------	-------------------

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

14808-60-7	Quartz (SiO ₂)	A2
------------	----------------------------	----

· MAK (German Maximum Workplace Concentration)

14808-60-7	Quartz (SiO ₂)	1
------------	----------------------------	---

· NIOSH-Ca (National Institute for Occupational Safety and Health)

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS05 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Cement, portland, chemicals

Quartz (SiO₂)

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/21/2024

Reviewed on 05/21/2024

Trade name: D490 High Strength Splicing Grout

(Contd. of page 7)

Hazard statements

Causes severe skin burns and eye damage.
 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 May cause an allergic skin reaction.
 May cause cancer.
 May damage fertility or the unborn child.
 May cause respiratory irritation.
 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Immediately call a poison center/doctor.
 Specific treatment (see on this label).
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

- **Water hazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

· **Date of preparation / last revision** 05/21/2024 / -

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Skin Corr. 1C: Skin corrosion/irritation – Category 1C
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Resp. Sens. 1: Respiratory sensitisation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Carc. 1A: Carcinogenicity – Category 1A
 Repr. 1A: Reproductive toxicity – Category 1A
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1