

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 05/24/2021

Reviewed on 05/24/2021

### 1 Identification

· **Product identifier**

· **Trade name:** Anchoring Cement

· **Article number:** 307974

· **Application of the substance / the mixture**

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Dayton® Superior  
4226 Kansas Avenue  
Kansas City, KS 66106

Tel.: (866) 329-8724

*Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.*

· **Information department:** Environmental, Health, and Safety department.

### 2 Hazard(s) identification

· **Classification of the substance or mixture**

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 1A H350 May cause cancer.

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05    GHS07    GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Quartz (SiO<sub>2</sub>)

Cement, portland, chemicals

· **Hazard statements**

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause cancer.

· **Precautionary statements**

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

*Immediately call a poison center/doctor.*

*Specific treatment (see on this label).*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/24/2021

Reviewed on 05/24/2021

Trade name: **Anchoring Cement**

(Contd. of page 1)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	3	Health = 3
FIRE	0	Fire = 0
PHYSICAL HAZARD	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

14808-60-7	Quartz (SiO <sub>2</sub> )	≥10- <60%
1317-65-3	Limestone	<14.0%
65997-15-1	Cement, portland, chemicals	≥5- <6%
26499-65-0	Calcium sulfate	<2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
In the event of persistent symptoms receive medical treatment.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.  
Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**  
Drink copious amounts of water and provide fresh air. Immediately call a doctor.  
Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

US

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 05/24/2021

Reviewed on 05/24/2021

Trade name: Anchoring Cement

(Contd. of page 2)

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**  
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
No special measures required.
- **Methods and material for containment and cleaning up:**  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** cool and dry
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

(Contd. on page 4)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/24/2021

Reviewed on 05/24/2021

Trade name: **Anchoring Cement**

(Contd. of page 3)

**14808-60-7 Quartz (SiO<sub>2</sub>)**

PEL	Long-term value: 0.05* mg/m <sup>3</sup> *resp. dust; 30mg/m <sup>3</sup> /%SiO <sub>2</sub> +2
REL	Long-term value: 0.05* mg/m <sup>3</sup> *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m <sup>3</sup> *as respirable fraction

**65997-15-1 Cement, portland, chemicals**

PEL	Long-term value: 50 mppcf or 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	Long-term value: 1* mg/m <sup>3</sup> E; *as respirable fraction

**26499-65-0 Calcium sulfate**

PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction

**69012-64-2 Silica-Amorphous Silica fume**

TLV	TLV withdrawn
-----	---------------

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Suitable respiratory protective device recommended.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

US

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/24/2021

Reviewed on 05/24/2021

Trade name: Anchoring Cement

(Contd. of page 4)

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

**Form:** Solid  
**Color:** According to product specification

· **Odor:** Characteristic  
 · **Odor threshold:** Not determined.

· **pH-value:** Not applicable.

#### · Change in condition

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** >999 °C (>1,830.2 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not determined.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

#### · Explosion limits:

**Lower:** Not determined.  
**Upper:** Not determined.

· **Vapor pressure:** Not applicable.

· **Density at 20 °C (68 °F):** 2.74819 g/cm<sup>3</sup> (22.93365 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not applicable.

· **Evaporation rate** Not applicable.

#### · Solubility in / Miscibility with

**Water:** Soluble.

· **Partition coefficient (n-octanol/water):** Not determined.

#### · Viscosity:

**Dynamic:** Not applicable.  
**Kinematic:** Not applicable.

#### · Solvent content:

**Organic solvents:** 0.0 %  
**Water:** 0.0 %

**Solids content:** 100.0 %

· **Other information** No further relevant information available.

## 10 Stability and reactivity

· **Reactivity** No decomposition if stored and applied as directed.

· **Chemical stability** No decomposition if stored and applied as directed

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid** Keep away from heat and sources of ignition.

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/24/2021

Reviewed on 05/24/2021

Trade name: Anchoring Cement

(Contd. of page 5)

- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 1317-65-3 Limestone

Oral	LD50	6,450 mg/kg (rat)
Dermal	LD50	500 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** May cause skin irritation.

- **on the eye:**

Strong caustic effect.

Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

Carcinogenic.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

14808-60-7	Quartz (SiO <sub>2</sub> )	1
69012-64-2	Silica-Amorphous Silica fume	3
50-00-0	formaldehyde	1

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO <sub>2</sub> )	K
50-00-0	formaldehyde	K

- **OSHA-Ca (Occupational Safety & Health Administration)**

50-00-0	formaldehyde
---------	--------------

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

(Contd. on page 7)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/24/2021

Reviewed on 05/24/2021

Trade name: Anchoring Cement

(Contd. of page 6)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of as normal garbage. Do not allow product to reach sewage system.  
It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

### 14 Transport information

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, ADR, ADN, IMDG, IATA</b></li> </ul>  | Not Regulated                                |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT, ADR, ADN, IMDG, IATA</b></li> </ul>                            | Not Regulated                                |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT, ADR, ADN, IMDG, IATA</b></li> <li>· <b>Class</b></li> </ul> | Not Regulated                                |
| <ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>   | Not Regulated                                |
| <ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>                                     | No   |
| <ul style="list-style-type: none"> <li>· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b></li> </ul>                        | Not applicable.                              |
| <ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> </ul>  |  |
| <ul style="list-style-type: none"> <li>· <b>ADR</b></li> </ul>  |  |
| <ul style="list-style-type: none"> <li>· <b>U.S. Domestic Ground Shipments:</b></li> </ul>  | Same as listed for Standard Shipments above. |
| <ul style="list-style-type: none"> <li>· <b>U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:</b></li> </ul>                       | Same as listed for Standard Shipments above. |
| <ul style="list-style-type: none"> <li>· <b>Emergency Response Guide (ERG) Number:</b></li> </ul>   | Not determine                                |
| <ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>   | Not Regulated                                |

US

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/24/2021

Reviewed on 05/24/2021

Trade name: Anchoring Cement

(Contd. of page 7)

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

50-00-0	formaldehyde
---------	--------------

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

554-13-2	lithium carbonate	<0.1%
50-00-0	formaldehyde	<0.1%

· TSCA (Toxic Substances Control Act):

14808-60-7	Quartz (SiO <sub>2</sub> )	ACTIVE
65997-16-2	Cement, alumina, chemicals	ACTIVE
1317-65-3	Limestone	ACTIVE
65997-15-1	Cement, portland, chemicals	ACTIVE
69012-64-2	Silica-Amorphous Silica fume	ACTIVE
9084-06-4	Naphthalenesulfonic acid, polymer with formaldehyde, sodium salt	ACTIVE
77-92-9	citric acid	ACTIVE
7757-82-6	sodium sulphate	ACTIVE
554-13-2	lithium carbonate	ACTIVE
497-19-8	sodium carbonate	ACTIVE
50-00-0	formaldehyde	ACTIVE
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE

· Hazardous Air Pollutants

50-00-0	formaldehyde
---------	--------------

· Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:

14808-60-7	Quartz (SiO <sub>2</sub> )
------------	----------------------------

50-00-0	formaldehyde
---------	--------------

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

554-13-2	lithium carbonate
----------	-------------------

· Cancerogenity categories

· EPA (Environmental Protection Agency)

50-00-0	formaldehyde	B1
---------	--------------	----

· TLV (Threshold Limit Value established by ACGIH)

14808-60-7	Quartz (SiO <sub>2</sub> )	A2
------------	----------------------------	----

50-00-0	formaldehyde	A2
---------	--------------	----

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/24/2021

Reviewed on 05/24/2021

Trade name: **Anchoring Cement**

(Contd. of page 8)

· <b>MAK (German Maximum Workplace Concentration)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	1
50-00-0	formaldehyde	4
· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	
50-00-0	formaldehyde	

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05   GHS07   GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Quartz (SiO<sub>2</sub>)

Cement, portland, chemicals

· **Hazard statements**

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause cancer.

· **Precautionary statements**

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

· **Date of preparation / last revision** 05/24/2021 / 78

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

(Contd. on page 10)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 05/24/2021

Reviewed on 05/24/2021

**Trade name: Anchoring Cement**

(Contd. of page 9)

*ACGIH: American Conference of Governmental Industrial Hygienists*  
*EINECS: European Inventory of Existing Commercial Chemical Substances*  
*ELINCS: European List of Notified Chemical Substances*  
*CAS: Chemical Abstracts Service (division of the American Chemical Society)*  
*NFPA: National Fire Protection Association (USA)*  
*HMIS: Hazardous Materials Identification System (USA)*  
*LC50: Lethal concentration, 50 percent*  
*LD50: Lethal dose, 50 percent*  
*PBT: Persistent, Bioaccumulative and Toxic*  
*vPvB: very Persistent and very Bioaccumulative*  
*NIOSH: National Institute for Occupational Safety*  
*OSHA: Occupational Safety & Health*  
*TLV: Threshold Limit Value*  
*PEL: Permissible Exposure Limit*  
*REL: Recommended Exposure Limit*  
*Skin Corr. 1C: Skin corrosion/irritation – Category 1C*  
*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*  
*Skin Sens. 1: Skin sensitisation – Category 1*  
*Carc. 1A: Carcinogenicity – Category 1A*

US