Printing date 04/20/2023

Reviewed on 04/20/2023

1 Identification

- · Product identifier
- · Trade name: Architectural FinishTM
- · Article number: 308236
- Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Dayton® Superior 4226 Kansas Avenue Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Hazard(s) identification

· Classification of the substance or mixture

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 1A H350 May cause cancer.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

- *Hazard-determining components of labeling:* Cement, portland, chemicals Quartz (SiO2)
- · Hazard statements

Causes severe skin burns and eye damage.

- May cause an allergic skin reaction.
- May cause cancer.

May cause respiratory irritation.

Precautionary statements

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/20/2023


Reviewed on 04/20/2023

Trade name: Architectural FinishTM

· Classifica	tion	syst	em:	•

· NFPA ratings (scale 0 - 4)

0Health = 1 Fire = 0 Reactivity = 0



HEALTH1Health = 1FIRE0Fire = 0PHYSICAL HAZARD0Reactivity = 0

• Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
65997-15-1	Cement, portland, chemicals	≥20-<60%	
14808-60-7	Quartz (SiO2)	≥10-<45%	
7778-18-9	calcium sulphate, natural	<4.0%	
• Additional information: For the wording of the listed hazard phrases refer to section 16.			

4 First-aid measures

· Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms recieve medical treatment.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention. After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing:

Drink copious amounts of water and provide fresh air. Immediately call a doctor. Seek medical treatment.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

Printing date 04/20/2023

Reviewed on 04/20/2023

Trade name: Architectural FinishTM

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

No special measures required.

• *Methods and material for containment and cleaning up:* Use neutralizing agent.

Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

• **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

• Information about protection against explosions and fires: Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- Storage: cool and dry
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Printing date 04/20/2023

Reviewed on 04/20/2023

Trade name: Architectural Finish[™]

	(Contd. of page 3)
	rol parameters
-	ponents with limit values that require monitoring at the workplace:
	7-15-1 Cement, portland, chemicals
PEL	Long-term value: 50 mppcf or 15* 5** mg/m ³
DEI	*total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 1* mg/m ³
12,	<i>E</i> ; *as respirable fraction
1480	8-60-7 Quartz (SiO2)
PEL	Long-term value: 0.05* mg/m ³
	*resp. dust; 30mg/m3/%SiO2+2
REL	Long-term value: 0.05* mg/m ³
	*respirable dust; See Pocket Guide App. A
TLV	Long-term value: $0.025* \text{ mg/m}^3$
7770	*as respirable fraction
	-18-9 calcium sulphate, natural
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³
	*total dust **respirable fraction
TLV	Long-term value: 10* mg/m ³
	*as inhalable fraction
· Addi	tional information: The lists that were valid during the creation were used as basis.
	osure controls
	onal protective equipment: eral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
Imme	ediately remove all soiled and contaminated clothing.
	hands before breaks and at the end of work.
	protective clothing separately. d contact with the eyes and skin.
	thing equipment: Suitable respiratory protective device recommended.
	ection of hands:
ſ	
ulli-	Protective gloves
	glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Frial of gloves
The s mani	selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from ifacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can e calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Wear appropriate eye protection to prevent eye contact.

(Contd. on page 5)

US

Printing date 04/20/2023

Trade name: Architectural FinishTM

Reviewed on 04/20/2023

(Contd. of page 4)

9 Physical and chemical proper	rties
· Information on basic physical and	chemical properties
· General Information	
· Appearance:	
Form:	Solid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	>999 °C (>1,830.2 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not determined.
• Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
• Danger of explosion:	Product does not present an explosion hazard.
• Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not applicable.
· Density at 20 °C (68 °F):	2.925 g/cm ³ (24.40913 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Soluble.
· Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
Solids content:	100.0 %
• Other information	No further relevant information available.

10 Stability and reactivity

• *Reactivity* No decomposition if stored and applied as directed.

- · Chemical stability No decomposition if stored and applied as directed
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid Keep away from heat and sources of ignition.
- *Incompatible materials:* No further relevant information available.

(Contd. on page 6)

Printing date 04/20/2023

Reviewed on 04/20/2023

Trade name: Architectural FinishTM

• *Hazardous decomposition products:* No dangerous decomposition products known.

(Contd. of page 5)

11 Toxicological information

· Information on toxicological effects

- Acute toxicity:
- Primary irritant effect:
- on the skin: May cause skin irritation.
- on the eye:
- Strong caustic effect.
- Irritating effect.

• Sensitization: Sensitization possible through skin contact.

 \cdot Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

Carcinogenic.

· Carcinogenic categories

· IARC (Inter	national Agency for Research on Cancer)	
14808-60-7	Quartz (SiO2)	1
13463-67-7	titanium dioxide	2B
1309-37-1	diiron trioxide	3
· NTP (Natio	nal Toxicology Program)	
14808-60-7	Quartz (SiO2)	K
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the	ingredients is listed.	

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water
- Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 7)

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/20/2023

Reviewed on 04/20/2023

Trade name: Architectural FinishTM

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system. It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to Federal, State, and Local regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

Transport information	
UN-Number DOT, ADR, ADN, IMDG, IATA	Not Regulated
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Not Regulated
Transport hazard class(es)	
DOT, ADR, ADN, IMDG, IATA Class	Not Regulated
Packing group DOT, ADR, IMDG, IATA	Not Regulated
Environmental hazards: Marine pollutant:	No
Transport in bulk according to Annex II of MARPOL73/ and the IBC Code	/78 Not applicable.
Transport/Additional information:	
ADR U.S. Domestic Ground Shipments: U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:	Same as listed for Standard Shipments above. Same as listed for Standard Shipments above.
Emergency Response Guide (ERG) Number:	Not determine
UN "Model Regulation":	Not Regulated

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
 Sara
 Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

(Contd. on page 8)

Printing date 04/20/2023

Reviewed on 04/20/2023

Trade name: Architectural Finish[™]

	(Cont	d. of page 7)
1344-28-1 d	aluminium oxide	<0.4%
554-13-2 i	ithium carbonate	<0.1%
• TSCA (Toxi	c Substances Control Act):	
65997-15-1	Cement, portland, chemicals	ACTIVE
	z ()	ACTIVE
7778-18-9	calcium sulphate, natural	ACTIVE
1344-28-1	aluminium oxide	ACTIVE
9004-58-4	Ethylhydroxyethyl cellulose	ACTIVE
497-19-8	sodium carbonate	ACTIVE
13463-67-7	titanium dioxide	ACTIVE
1309-37-1	diiron trioxide	ACTIVE
554-13-2	lithium carbonate	ACTIVE
· Hazardous	Air Pollutants	
None of the	ingredients is listed.	
· Proposition		
	nown to the State of California (Prop. 65) to cause cancer:	
	Quartz (SiO2)	
13463-67-7	titanium dioxide	
· Chemicals k	nown to cause reproductive toxicity for females:	
None of the	ingredients is listed.	
• Chemicals known to cause reproductive toxicity for males:		
None of the	ingredients is listed.	
· Chemicals k	nown to cause developmental toxicity:	
554-13-2 lii	hium carbonate	
· Cancaragan	ity catagorias	

· Cancerogenity categories · EPA (Environmental Protection Agency)

None of the ingredients is listed. • TLV (Threshold Limit Value established by ACGIH) 14808-60-7 Quartz (SiO2) A2 1344-28-1 aluminium oxide A413463-67-7 titanium dioxide A41309-37-1 diiron trioxide A4· MAK (German Maximum Workplace Concentration) 14808-60-7 Quartz (SiO2) 1 1344-28-1 aluminium oxide 2 13463-67-7 titanium dioxide 3A · NIOSH-Ca (National Institute for Occupational Safety and Health) 14808-60-7 Quartz (SiO2) 13463-67-7 titanium dioxide · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).


(Contd. on page 9)

Printing date 04/20/2023

Reviewed on 04/20/2023

Trade name: Architectural FinishTM

(Contd. of page 8)



· Signal word Danger

Hazard-determining components of labeling: Cement, portland, chemicals Quartz (SiO2)
Hazard statements Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer.

May cause respiratory irritation.

· Precautionary statements

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

• Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- Date of preparation / last revision 04/20/2023 / 56

```
· Abbreviations and acronyms:
```

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

Printing date 04/20/2023

Reviewed on 04/20/2023

Trade name: Architectural Finish[™]

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Skin Corr. 1C: Skin corrosion/irritation – Category 1C Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Carc. 1A: Carcinogenicity – Category 1A STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 (Contd. of page 9)