Printing date 04/23/2025

Reviewed on 04/23/2025

# **1** Identification

- · Product identifier
- Trade name: <u>Turbo Grout LT12</u>
- · Article number: 309013
- Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Dayton® Superior 4226 Kansas Avenue Kansas City, KS 66106

Tel.: (866) 329-8724

*Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.* 

· Information department: Environmental, Health, and Safety department.

# 2 Hazard(s) identification

· Classification of the substance or mixture

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 1A H350 May cause cancer.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

· Label elements

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

• Hazard-determining components of labeling: Cement, portland, chemicals Quartz (SiO2) • Hazard statements

May cause an allergic skin reaction. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Causes admage to organs inrough protonged or rep

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

• Classification system:

· NFPA ratings (scale 0 - 4)



(Contd. on page 2)

(Contd. of page 1)

≥40-≤70%

≥40-≤70%

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/23/2025

Reviewed on 04/23/2025

#### Trade name: Turbo Grout LT12

· HMIS-ratings (scale 0 - 4)



• Other hazards

· Results of PBT and vPvB assessment

- *PBT:* Not applicable.
- · vPvB: Not applicable.

#### **3** Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

65997-15-1 Cement, portland, chemicals

14808-60-7 Quartz (SiO2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

# 4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms recieve medical treatment.

- After inhalation:
- Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

*Immediately rinse with water.* 

If skin irritation continues, consult a doctor.

• After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Seek medical treatment.

· Information for doctor:

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

# 5 Fire-fighting measures

• Extinguishing media

- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

US

*Printing date 04/23/2025* 

Reviewed on 04/23/2025

(Contd. of page 2)

Trade name: Turbo Grout LT12

• Advice for firefighters • Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

#### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

No special measures required.

- Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13.
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

#### · Handling:

· Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities

· Storage: cool and dry

- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Com	• Components with limit values that require monitoring at the workplace:			
65997-15-1 Cement, portland, chemicals				
PEL	Long-term value: 50 mppcf or 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction			
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction			
TLV	Long-term value: 1* mg/m³ E; *as respirable fraction			
	(Contd. on page 4)			

(Contd. of page 3)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/23/2025

Reviewed on 04/23/2025

#### Trade name: Turbo Grout LT12

14808-60-7 Quartz (SiO2)
--------------------------

PEL Long-term value: 0.05\* mg/m<sup>3</sup> \*resp. dust; 30mg/m3/%SiO2+2

REL Long-term value: 0.05\* mg/m<sup>3</sup> \*respirable dust; See Pocket Guide App. A TLV Long-term value: 0.025\* mg/m<sup>3</sup>

\*as respirable fraction

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • Eye protection: Wear appropriate eye protection to prevent eye contact.* 

# 9 Physical and chemical properties

<ul> <li>Information on basic physical and</li> <li>General Information</li> </ul>	cnemicai properties	
· Appearance:		
Form:	Solid	
Color:	According to product specification	
· Odor:	Characteristic	
· Odor threshold:	Not determined.	
· pH-value:	Not applicable.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not determined.	
• Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	

Printing date 04/23/2025

Reviewed on 04/23/2025

#### Trade name: Turbo Grout LT12

		(Contd. of page 4
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	Not applicable.	
Density at 20 °C (68 °F):	2.866 g/cm³ (23.91677 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not applicable.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
Water:	Insoluble.	
Partition coefficient (n-octanol/wa	iter): Not determined.	
Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
Solvent content:		
Solids content:	100.0 %	
• Other information	No further relevant information available.	

# **10 Stability and reactivity**

• *Reactivity* No decomposition if stored and applied as directed.

- · Chemical stability No decomposition if stored and applied as directed
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- *Conditions to avoid Keep away from heat and sources of ignition.*
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: May cause skin irritation.
- on the eye: No irritating effect known.
- Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

*The product shows the following dangers according to internally approved calculation methods for preparations: Irritant* 

Carcinogenic.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

14808-60-7 Quartz (SiO2)

#### · NTP (National Toxicology Program)

14808-60-7 Quartz (SiO2)

(Contd. on page 6)

K

<sup>-</sup> US

(Contd. of page 5)

### Safety Data Sheet acc. to OSHA HCS

Printing date 04/23/2025

Reviewed on 04/23/2025

Trade name: Turbo Grout LT12

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12 Ecological information**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

# **13 Disposal considerations**

#### · Waste treatment methods

· Recommendation:

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to Federal, State, and Local regulations.

UN-Number DOT, ADR, ADN, IMDG, IATA	Not Regulated	
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Not Regulated	
Transport hazard class(es)		
DOT, ADR, ADN, IMDG, IATA Class	Not Regulated	
Packing group DOT, ADR, IMDG, IATA	Not Regulated	
Environmental hazards: Marine pollutant:	No	
Transport in bulk according to Annex II of and the IBC Code	MARPOL73/78 Not applicable.	

Printing date 04/23/2025

Reviewed on 04/23/2025

Trade name: Turbo Grout LT12

(Contd. of page 6)

ACTIVE ACTIVE

Transport/Additional information:			
· ADR · U.S. Domestic Ground Shipments: · U.S. Domestic Ground Non-Bulk (119 gal or less per	Same as listed for Standard Shipments above.		
container) Shipments:	Same as listed for Standard Shipments above.		
• Emergency Response Guide (ERG) Number:	Not determine		
· UN "Model Regulation":	Not Regulated		

# **15 Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

65997-15-1 Cement, portland, chemicals

14808-60-7 Quartz (SiO2)

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

• Chemicals known to the State of California (Prop. 65) to cause cancer:

14808-60-7 Quartz (SiO2)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value established by ACGIH)

14808-60-7 Quartz (SiO2)

· MAK (German Maximum Workplace Concentration)

14808-60-7 Quartz (SiO2)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

14808-60-7 Quartz (SiO2)

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 8)

A2

1

Printing date 04/23/2025

Reviewed on 04/23/2025

Trade name: Turbo Grout LT12

(Contd. of page 7)



· Signal word Danger

Hazard-determining components of labeling: Cement, portland, chemicals Quartz (SiO2)
Hazard statements May cause an allergic skin reaction. May cause cancer. Causes damage to organs through prolonged or repeated exposure.
Precautionary statements Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection.

*IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.* 

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- · Date of preparation / last revision 04/23/2025 / 35

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

<sup>•</sup> Abbreviations and acronyms:

Printing date 04/23/2025

Trade name: Turbo Grout LT12

Skin Sens. 1: Skin sensitisation – Category 1 Carc. 1A: Carcinogenicity – Category 1A STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Reviewed on 04/23/2025

(Contd. of page 8)

US