Tel.: (866) 329-8724

Safety Data Sheet acc. to OSHA HCS

Printing date 04/19/2023 Reviewed on 04/19/2023

1 Identification

- · Product identifier
- · Trade name: Resin Cure with Dye J11WD
- · Article number: 68928
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dayton® Superior

4226 Kansas Avenue

Kansas City, KS 66106

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident

involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Hazard(s) identification

· Classification of the substance or mixture

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Aquatic Acute 2 H401 Toxic to aquatic life.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Solvent naphtha (petroleum), medium aliph.

Distilled Tall Oil Fatty Acids

Hazard statements

May cause an allergic skin reaction.

Causes damage to the central nervous system through prolonged or repeated exposure.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Avoid release to the environment.

Wear protective gloves.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 04/19/2023 Reviewed on 04/19/2023

Trade name: Resin Cure with Dye J11WD

(Contd. of page 1)

- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
68131-87-3	Petroleum Hydrocarbon Resin	≥2.5-<14%
64742-88-7	Solvent naphtha (petroleum), medium aliph.	>5-<7.5%
61790-12-3	Distilled Tall Oil Fatty Acids	≥1-<1.1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms recieve medical treatment.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Seek medical treatment.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.

(Contd. on page 3)

Printing date 04/19/2023 Reviewed on 04/19/2023

Trade name: Resin Cure with Dye J11WD

(Contd. of page 2)

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · **Storage:** cool and dry
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

(Contd. on page 4)

Printing date 04/19/2023 Reviewed on 04/19/2023

Trade name: Resin Cure with Dye J11WD

(Contd. of page 3)

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Relative density

· Evaporation rate

· Vapor density

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

9 Physical and chemical properties

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Wear appropriate eye protection to prevent eye contact.

Information on basic physical and chemical properties		
General Information		
Appearance:	Limit	
Form: Color:	Liquid Red	
Cotor: Odor:	neu Petroleum-like	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 100°C (212°F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	230 °C (446 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	1.1 Vol %	
Upper:	6 Vol %	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	0.98607 g/cm³ (8.22875 lbs/gal)	

Not determined.

Not determined.

Not determined.

(Contd. on page 5)

Printing date 04/19/2023 Reviewed on 04/19/2023

Trade name: Resin Cure with Dye J11WD

		(Contd. of page
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wo	iter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	5.5-7.6 %	
Water:	77.4 %	
Solids content:	20.0 %	
· Other information	No further relevant information available.	
· Volatile Organic Compounds:	Contains less than 100 g/L.	

10 Stability and reactivity

- · Reactivity No decomposition if stored and applied as directed.
- · Chemical stability No decomposition if stored and applied as directed
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Keep away from heat and sources of ignition.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
64742-88-	7 Solvent n	naphtha (petroleum), medium aliph.	
Oral	LD50	>6,500 mg/kg (rat)	
Dermal	LD50	>3,000 mg/kg (rab)	
Inhalative	LC50/4 h	>14 mg/l (rat)	

- · Primary irritant effect:
- · on the skin: May cause skin irritation.
- · on the eye: No irritating effect known.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (In	ternational Agency for Research on Cancer)	
128-37-0	Butylated hydroxytoluene	3
91-20-3	naphthalene	2B
111-42-2	2,2'-iminodiethanol	2B
	(Contd on a	

(Contd. on page 6)

Printing date 04/19/2023 Reviewed on 04/19/2023

Trade name: Resin Cure with Dye J11WD

(Contd. of page 5)

· NTP (National Toxicology Program)

91-20-3 naphthalene

R

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Water hazard class 1 (Self-assessment): slightly hazardous for water

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to Federal, State, and Local regulations.

Transport information		
UN-Number DOT, ADR, ADN, IMDG, IATA	Not Regulated	
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Not Regulated	
Transport hazard class(es)		
DOT, ADR, ADN, IMDG, IATA		
Class	Not Regulated	
Packing group		
DOT, ADR, IMDG, IATA	Not Regulated	

(Contd. on page 7)

Printing date 04/19/2023 Reviewed on 04/19/2023

Trade name: Resin Cure with Dye J11WD

		(Contd. of page
· Environmental hazards: · Marine pollutant:	No	
· Transport in bulk according to Annex II of MARPOL73.	/78	
and the IBC Code	Not applicable.	
· Transport/Additional information:		
· ADR		
· U.S. Domestic Ground Shipments:	Same as listed for Standard Shipments above.	
· U.S. Domestic Ground Non-Bulk (119 gal or less per		
container) Shipments:	Same as listed for Standard Shipments above.	
Emergency Response Guide (ERG) Number:	Not determine	
· UN "Model Regulation":	Not Regulated	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

91-20-3 n	aphthalene	<0.025%
111-42-2 2,	2'-iminodiethanol	<0.1%
· TSCA (Tox	ic Substances Control Act):	
68131-87-3	Petroleum Hydrocarbon Resin	ACTIVE
64742-88-7	Solvent naphtha (petroleum), medium aliph.	ACTIVE
61790-12-3	Distilled Tall Oil Fatty Acids	ACTIVE
25265-77-4	Trimethyl-1,3-pentanediol, monoisobutyrate	ACTIVE
141-43-5	monoethanolamine	ACTIVE
11138-66-2	Xanthan Gum	ACTIVE
128-37-0	Butylated hydroxytoluene	ACTIVE
91-20-3	naphthalene	ACTIVE
111-42-2	2,2'-iminodiethanol	ACTIVE
107-22-2	glyoxal	ACTIVE
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
· Hazardous	Air Pollutants	
91-20-3 n	anhthalene	

91-20-3 naphthalene

111-42-2 2,2'-iminodiethanol

Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:

91-20-3 naphthalene

111-42-2 2,2'-iminodiethanol

(Contd. on page 8)

Printing date 04/19/2023 Reviewed on 04/19/2023

Trade name: Resin Cure with Dye J11WD

(Contd. of page 7) · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. · Cancerogenity categories · EPA (Environmental Protection Agency) 91-20-3 naphthalene C, CBD · TLV (Threshold Limit Value established by ACGIH) 128-37-0 Butylated hydroxytoluene A491-20-3 naphthalene A4111-42-2 2,2'-iminodiethanol A3107-22-2 glyoxal A4· MAK (German Maximum Workplace Concentration) 128-37-0 Butylated hydroxytoluene 4 91-20-3 naphthalene 2 111-42-2 2,2'-iminodiethanol *3B* 3B 107-22-2 glyoxal · NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed.

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS07

GHS08

GHS09

- · Signal word Danger
- · Hazard-determining components of labeling:

Solvent naphtha (petroleum), medium aliph.

Distilled Tall Oil Fatty Acids

· Hazard statements

May cause an allergic skin reaction.

Causes damage to the central nervous system through prolonged or repeated exposure.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Avoid release to the environment.

Wear protective gloves.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Water hazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.

(Contd. on page 9)

Printing date 04/19/2023 Reviewed on 04/19/2023

Trade name: Resin Cure with Dye J11WD

(Contd. of page 8)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- Date of preparation / last revision 04/19/2023 / 146
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Sens. 1: Skin sensitisation – Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Čategory 2

US