Printing date 04/21/2023

Reviewed on 04/21/2023

1 Identification

- · Product identifier
- Trade name: <u>Acrylic Bonding Agent J40</u>
- · Article number: 69081
- Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Dayton® Superior 4226 Kansas Avenue Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Hazard(s) identification

 \cdot Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2B H320 Causes eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.


· Label elements

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Warning

· Hazard-determining components of labeling: 2,2',2"-(hexahydro-1,3,5-triazine-1,3,5-trivl)triethanol 1,2-benzisothiazol-3(2H)-one • Hazard statements Causes skin and eye irritation. May cause an allergic skin reaction. · Precautionary statements Avoid breathing dust/fume/gas/mist/vapors/spray Wear protective gloves. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 1



Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Acrylic Bonding Agent J40

(Contd. of page 1)

≥0.1-<0.4%

• HMIS-ratings (scale 0 - 4)



• Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description
- 7732-18-5 water, distilled, conductivity or of similar purity
- · Identification number(s)
- EC number: 231-791-2
- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.
- Dangerous components:
- 4719-04-4 2,2',2"-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol
- · Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

- In the event of persistent symptoms recieve medical treatment.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- *In case of unconsciousness place patient stably in side position for transportation.*

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- *After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.*
- · After swallowing: Seek medical treatment.

· Information for doctor:

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.

• Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 04/21/2023

Reviewed on 04/21/2023

(Contd. of page 2)

Trade name: Acrylic Bonding Agent J40

• Advice for firefighters • Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- · Environmental precautions:
- Dilute with plenty of water.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage: cool and dry
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Acrylic Bonding Agent J40

Avoid contact with the eyes and skin.

- Breathing equipment: Suitable respiratory protective device recommended.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection: Wear appropriate eye protection to prevent eye contact.

Information on basic physical and o	chemical properties	
General Information		
Appearance:		
Form:	Liquid	
Color:	White	
Odor:	Odorless	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	0 °C (32 °F)	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.03573 g/cm ³ (8.64317 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	and. Not determined	

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Acrylic Bonding Agent J40

	(Contd. of page 4)
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Water:	48.5 %
Solids content: • Other information	25.0 % No further relevant information available.
· Volatile Organic Compounds:	Contains less than 50 g/L.

10 Stability and reactivity

• *Reactivity* No decomposition if stored and applied as directed.

- · Chemical stability No decomposition if stored and applied as directed
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid Keep away from heat and sources of ignition.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: May cause skin irritation.
- on the eye:
- Strong irritant with the danger of severe eye injury.
- Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)
- None of the ingredients is listed.
- · NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

• Aquatic toxicity: No further relevant information available.

• *Persistence and degradability* No further relevant information available.

(Contd. on page 6)

US

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Acrylic Bonding Agent J40

(Contd. of page 5)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:
- Not hazardous for water.
- Water hazard class 1 (Self-assessment): slightly hazardous for water
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- Danger to drinking water if even extremely small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to Federal, State, and Local regulations.

Transport information		
UN-Number		
DOT, ADR, ADN, IMDG, IATA	Not Regulated	
UN proper shipping name		
DOT, ADR, ADN, IMDG, IATA	Not Regulated	
Transport hazard class(es)		
DOT, ADR, ADN, IMDG, IATA		
Class	Not Regulated	
Packing group		
DOT, ADR, IMDG, IATA	Not Regulated	
Environmental hazards:		
Marine pollutant:	No	
Transport in bulk according to Annex II of MARPOL73,	/78	
and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR		
U.S. Domestic Ground Shipments:	Same as listed for Standard Shipments above.	
U.S. Domestic Ground Non-Bulk (119 gal or less per		
container) Shipments:	Same as listed for Standard Shipments above.	
Emergency Response Guide (ERG) Number:	Not determine	

US

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Acrylic Bonding Agent J40

(Contd. of page 6)

ACTIVE

ACTIVE

ACTIVE

ACTIVE

· UN "Model Regulation":

Not Regulated

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

• Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

None of the ingredients is listed.

• TSCA (Toxic Substances Control Act):

4719-04-4 2,2',2"-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol

1310-73-2 sodium hydroxide

2634-33-5 1,2-benzisothiazol-3(2H)-one

7732-18-5 water, distilled, conductivity or of similar purity

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 8)

Printing date 04/21/2023

Reviewed on 04/21/2023

(Contd. of page 7)

Trade name: Acrylic Bonding Agent J40

· Hazard pictograms



· Signal word Warning

- *Hazard-determining components of labeling:* 2,2',2''-(hexahydro-1,3,5-triazine-1,3,5-triyl)triethanol 1,2-benzisothiazol-3(2H)-one
- · Hazard statements

Causes skin and eye irritation.

May cause an allergic skin reaction.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environmental, Health & Safety Department

- · Contact: Environmental, Health & Safety Manager
- · Date of preparation / last revision 04/21/2023 / 191

· Abbreviations and acronvms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B Skin Sens. 1: Skin sensitisation – Category 1