

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 04/16/2025

1 Identification

- **Product identifier**

- **Trade name:** Pro-Poxy 50 - Part A

- **Article number:** 140013A

- **Application of the substance / the mixture**

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Dayton® Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Muta. 2 H341 Suspected of causing genetic defects.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07 GHS08 GHS09

- **Signal word** Warning

- **Hazard-determining components of labeling:**

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane

2,3-epoxypropyl o-tolyl ether

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

- **Hazard statements**

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 04/16/2025

Trade name: Pro-Poxy 50 - Part A

(Contd. of page 1)

· **Classification system:**· **NFPA ratings (scale 0 - 4)**· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	0	Fire = 0
PHYSICAL HAZARD	0	Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

25085-99-8	Diglycidyl ether of bisphenol A homopolymer	≥50-<80%
17557-23-2	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	≥10-≤25%
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	≥1-<10%
2210-79-9	2,3-epoxypropyl o-tolyl ether	≥2.5-<5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**· **General information:**

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms receive medical treatment.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.· **After swallowing:** Seek medical treatment.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 04/16/2025

Trade name: Pro-Poxy 50 - Part A

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** cool and dry
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 04/16/2025

Trade name: Pro-Poxy 50 - Part A

(Contd. of page 3)

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:** Liquid**Color:** Clear· **Odor:** Slight· **Odor threshold:** Not determined.· **pH-value:** Not determined.· **Change in condition****Melting point/Melting range:** Undetermined.**Boiling point/Boiling range:** Undetermined.· **Flash point:** Not applicable.· **Flammability (solid, gaseous):** Not applicable.· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product does not present an explosion hazard.· **Explosion limits:****Lower:** Not determined.**Upper:** Not determined.· **Vapor pressure:** Not determined.· **Density:** Not determined.· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 04/16/2025

Trade name: Pro-Poxy 50 - Part A

(Contd. of page 4)

- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
- **Solids content:** 100,0 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

25085-99-8 Diglycidyl ether of bisphenol A homopolymer

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:**
 - Strong irritant with the danger of severe eye injury.
 - Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
 - The product shows the following dangers according to internally approved calculation methods for preparations:
 - Irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 04/16/2025

Trade name: Pro-Poxy 50 - Part A

(Contd. of page 5)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
 - Water hazard class 1 (Self-assessment): slightly hazardous for water
 - Water hazard class 2 (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
 - Also poisonous for fish and plankton in water bodies.
 - Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

- | | |
|----------------------------------|--|
| · UN-Number | |
| · DOT | Not Regulated |
| · ADR, IMDG, IATA | UN3082 |
| · UN proper shipping name | |
| · DOT | Not Regulated |
| · ADR | 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diglycidyl ether of bisphenol A homopolymer, formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol) |
| · IMDG | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diglycidyl ether of bisphenol A homopolymer, formaldehyde, oligomeric reaction products with 1-chloro-2,3- |

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 04/16/2025

Trade name: Pro-Poxy 50 - Part A

(Contd. of page 6)

· · IATA	epoxypropane and phenol), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diglycidyl ether of bisphenol A homopolymer, formaldehyde, oligomeric reaction products with 1-chloro-2,3- epoxypropane and phenol)
· Transport hazard class(es) · DOT · Class	Not Regulated
· ADR, IMDG, IATA  · Class · Label	9 Miscellaneous dangerous substances and articles 9
· Packing group · DOT · ADR, IMDG, IATA	Not Regulated III
· Environmental hazards: · Marine pollutant: · Special marking (ADR): · Special marking (IATA):	Product contains environmentally hazardous substances: 2,3- epoxypropyl o-tolyl ether Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
· Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category	Warning: Miscellaneous dangerous substances and articles 90 F-A,S-F A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Excepted quantities (EQ) · U.S. Domestic Ground Shipments: · U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments: · Emergency Response Guide (ERG) Number:	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml Same as listed for Standard Shipments above. DOT: Not regulated (Reclassified as per 49CFR 173.150). Not determine
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 04/16/2025

Trade name: Pro-Poxy 50 - Part A

(Contd. of page 7)

· **UN "Model Regulation":**

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIGLYCIDYL ETHER OF BISPHENOL A HOMOPOLYMER, FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

25085-99-8	Diglycidyl ether of bisphenol A homopolymer	ACTIVE
17557-23-2	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	ACTIVE
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	ACTIVE
9003-36-5	formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	ACTIVE
2210-79-9	2,3-epoxypropyl o-tolyl ether	ACTIVE

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

106-89-8 | epichlorohydrin

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Cancerogenity categories**· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **MAK (German Maximum Workplace Concentration)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 04/16/2025

Trade name: Pro-Poxy 50 - Part A

(Contd. of page 8)

Hazard pictograms



Signal word Warning

Hazard-determining components of labeling:

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane
2,3-epoxypropyl o-tolyl ether
oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Hazard statements

Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of causing genetic defects.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves/protective clothing/eye protection/face protection.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

- **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Environmental, Health & Safety Department

• **Contact:** Environmental, Health & Safety Manager

• **Date of preparation / last revision** 04/16/2025 / 17

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 04/16/2025

Trade name: Pro-Poxy 50 - Part A

(Contd. of page 9)

*REL: Recommended Exposure Limit**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A**Skin Sens. 1: Skin sensitisation – Category 1**Muta. 2: Germ cell mutagenicity – Category 2**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 09/08/2021

1 Identification

- **Product identifier**

- **Trade name:** Pro-Poxy 50 - Part B

- **Article number:** 140013B

- **Application of the substance / the mixture**

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Dayton® Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05 GHS09

- **Signal word** Danger

- **Hazard-determining components of labeling:**

2-methylpentane-1,5-diamine

- **Hazard statements**

Causes severe skin burns and eye damage.

Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 0

Reactivity = 0

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 09/08/2021

Trade name: Pro-Poxy 50 - Part B

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)

HEALTH	*3	Health = *3
FIRE	0	Fire = 0
PHYSICAL HAZARD	0	Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

61788-44-1	Styrenated phenol	≥25-≤50%
15520-10-2	2-methylpentane-1,5-diamine	≥10-≤20%
2579-20-6	1,3-Cyclohexanedimethanamine	<10.0%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms receive medical treatment.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Seek medical treatment.

· Information for doctor:

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

· **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 09/08/2021

Trade name: Pro-Poxy 50 - Part B

(Contd. of page 2)

- **Advice for firefighters**

- **Protective equipment:**

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- **Information about protection against explosions and fires:** No special measures required.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Keep receptacle tightly sealed.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 09/08/2021

Trade name: Pro-Poxy 50 - Part B

(Contd. of page 3)

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:****Form:** Liquid**Color:** Clear· **Odor:** Slight· **Odor threshold:** Not determined.· **pH-value:** Not determined.· **Change in condition****Melting point/Melting range:** Undetermined.**Boiling point/Boiling range:** Undetermined.· **Flash point:** Not applicable.· **Flammability (solid, gaseous):** Not applicable.· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product does not present an explosion hazard.· **Explosion limits:****Lower:** Not determined.**Upper:** Not determined.· **Vapor pressure:** Not determined.· **Density:** Not determined.· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with****Water:** Not miscible or difficult to mix.· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:****Dynamic:** Not determined.**Kinematic:** Not determined.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 09/08/2021

Trade name: Pro-Poxy 50 - Part B

(Contd. of page 4)

- | | |
|--------------------------------------|--|
| · Other information | No further relevant information available. |
| · Volatile Organic Compounds: | Contains less than 50 g/L. |

10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

15520-10-2 2-methylpentane-1,5-diamine

Oral LD50 1,690 mg/kg (rat)

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 09/08/2021

Trade name: Pro-Poxy 50 - Part B

(Contd. of page 5)

- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

- | | |
|---|---|
| · UN-Number | UN2735 |
| · DOT, ADR, IMDG, IATA | |
| · UN proper shipping name | |
| · DOT | Amines, liquid, corrosive, n.o.s. (2-methylpentane-1,5-diamine, 1,3-Cyclohexanedimethanamine) |
| · ADR | 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (2-methylpentane-1,5-diamine, 1,3-Cyclohexanedimethanamine), ENVIRONMENTALLY HAZARDOUS |
| · IMDG | AMINES, LIQUID, CORROSIVE, N.O.S. (2-methylpentane-1,5-diamine, 1,3-Cyclohexanedimethanamine), MARINE POLLUTANT |
| · IATA | AMINES, LIQUID, CORROSIVE, N.O.S. (2-methylpentane-1,5-diamine, 1,3-Cyclohexanedimethanamine) |
| · Transport hazard class(es) | |
| · DOT | |
|   | |
| · Class | 8 Corrosive substances |

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 09/08/2021

Trade name: Pro-Poxy 50 - Part B

(Contd. of page 6)

· Label	8
· ADR, IMDG	
 	
· Class	8 Corrosive substances
· Label	8
· IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances: 4-nonylphenol, branched
· Marine pollutant:	Yes (DOT) Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Alkalis
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Remarks:	Special marking with the symbol (fish and tree).
· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml Same as listed for Standard Shipments above.
· U.S. Domestic Ground Shipments:	
· U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:	DOT: Not regulated (Reclassified as per 49CFR 173.150).
· Emergency Response Guide (ERG) Number:	Not determine
· IMDG	
· Limited quantities (LQ)	1L

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 09/08/2021

Trade name: Pro-Poxy 50 - Part B

(Contd. of page 7)

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (2-METHYLPENTANE-1,5-DIAMINE, 1,3-CYCLOHEXANEDIMETHANAMINE), 8, II, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

61788-44-1	Styrenated phenol	ACTIVE
9046-10-0	Polyoxypropylenediamine	ACTIVE
15520-10-2	2-methylpentane-1,5-diamine	ACTIVE
2579-20-6	1,3-Cyclohexanedimethanamine	ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/16/2025

Reviewed on 09/08/2021

Trade name: Pro-Poxy 50 - Part B

(Contd. of page 8)

Hazard pictograms



GHS05 GHS09

Signal word Danger

Hazard-determining components of labeling:

2-methylpentane-1,5-diamine

Hazard statements

Causes severe skin burns and eye damage.

Toxic to aquatic life with long lasting effects.

Precautionary statements

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

Water hazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environmental, Health & Safety Department

Contact: Environmental, Health & Safety Manager

Date of preparation / last revision 04/16/2025 / 8

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2