Tel.: (866) 329-8724

# Safety Data Sheet acc. to OSHA HCS

Printing date 04/25/2023 Reviewed on 04/25/2023

### 1 Identification

- · Product identifier
- · Trade name: Sure Anchor<sup>TM</sup> I J51 Part A
- · Article number: 100908A
- · Application of the substance / the mixture
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Dayton® Superior

4226 Kansas Avenue

Kansas City, KS 66106

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

# 2 Hazard(s) identification

· Classification of the substance or mixture

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Muta. 2 H341 Suspected of causing genetic defects.

Carc. 2 H351 Suspected of causing cancer.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

2,3-epoxypropyl o-tolyl ether

titanium dioxide

#### · Hazard statements

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

Suspected of causing cancer.

Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

(Contd. of page 1)

# Safety Data Sheet acc. to OSHA HCS

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part A

· Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

# 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
25085-99-8	Diglycidyl ether of bisphenol A homopolymer	≥10-<90%	
2210-79-9	2,3-epoxypropyl o-tolyl ether	≥2.5-<4%	
471-34-1	calcium carbonate	<4.0%	
67762-90-7	Hydrophobic silica	<3.25%	
13463-67-7	titanium dioxide	≥0.1-<1.6%	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

*In the event of persistent symptoms recieve medical treatment.* 

· After inhalation:

Supply fresh air and to be sure call for a doctor.

*In case of unconsciousness place patient stably in side position for transportation.* 

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· After skin contact:

*Immediately wash with water and soap and rinse thoroughly.* 

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Seek immediate medical advice.

Seek medical treatment.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part A

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage: cool and dry
- · Requirements to be met by storerooms and receptacles: Store in a cool dry location.
- Information about storage in one common storage facility: Store away from incompatible materials.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

(Contd. on page 4)

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part A

(Contd. of page 3)

### 471-34-1 calcium carbonate

PEL Long-term value: 15\* 5\*\* mg/m³
\*total dust \*\*respirable fraction

REL Long-term value: 10\* 5\*\* mg/m³
\*total dust \*\*respirable fraction

TLV TLV withdrawn

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection: Wear appropriate eye protection to prevent eye contact.

### 9 Physical and chemical properties

· Information on basic physical and	chemical properties
· General Information	
· Appearance:	
Form:	Liquid
Color:	Clear
· Odor:	Mild
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· Flash point:	>93 °C (>199.4 °F)
· Flammability (solid, gaseous):	Not applicable.
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.

(Contd. on page 5)

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part A

		(Contd. of page
Upper:	Not determined.	
Vapor pressure:	Not determined.	
Density at 20 °C (68 °F):	1.2 g/cm³ (10.014 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	t <b>ter):</b> Not determined.	
Viscosity:		
Dynamic at 20 °C (68 °F):	1,000,000 mPas	
Kinematic:	Not determined.	
Solvent content:		
Solids content:	100.0 %	
Other information	No further relevant information available.	

### 10 Stability and reactivity

- · Reactivity No decomposition if stored and applied as directed.
- · Chemical stability No decomposition if stored and applied as directed
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with acids, alkalis and oxidizing agents.
- · Conditions to avoid Keep away from heat and sources of ignition.
- · *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

### 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

#### 25085-99-8 Diglycidyl ether of bisphenol A homopolymer

 Oral
 LD50
 5,000 mg/kg (rat)

 Dermal
 LD50
 20,000 mg/kg (rabbit)

- Primary irritant effect:
- on the skin: May cause skin irritation.
- · on the eye:

Strong irritant with the danger of severe eye injury.

*Irritating effect.* 

- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 6)

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part A

Carcinogenic categories

IARC (International Agency for Research on Cancer)

14807-96-6 Talc

13463-67-7 titanium dioxide

7631-86-9 silicon dioxide, chemically prepared

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to Federal, State, and Local regulations.

# 14 Transport information

- · UN-Number
- · DOT, ADR, ADN, IATA

· IMDG

Not Regulated UN3082

(Contd. on page 7)

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part A

	(Contd. of pag
· UN proper shipping name · DOT, ADR, ADN, IATA · IMDG	Not Regulated ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI N.O.S. (epoxy resin), MARINE POLLUTANT
Transport hazard class(es)	
DOT, ADR, ADN, IATA Class	Not Regulated
· IMDG	
Class	9 Miscellaneous dangerous substances and articles
· Label	9 Miscenaneous aangerous substances and articles 9
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards: Marine pollutant:	No Symbol (fish and tree)
· Special precautions for user · EMS Number: · Stowage Category	F-A,S-F A
Transport in bulk according to Annex II of MARPOL73, and the IBC Code	/7 <b>8</b> Not applicable.
Transport/Additional information:	
DOT Remarks:	Not Regulated for Transport.
· ADR · Remarks: · U.S. Domestic Ground Shipments: · U.S. Domestic Ground Non-Bulk (119 gal or less per	Not Regulated for Transport. Same as listed for Standard Shipments above.
container) Shipments:	Same as listed for Standard Shipments above.
Emergency Response Guide (ERG) Number:	Not determine
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	Not Regulated

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part A

(Contd. of page 7)

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- ·Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):					
25085-99-8	5085-99-8 Diglycidyl ether of bisphenol A homopolymer AC				
	2,3-epoxypropyl o-tolyl ether AC				
471-34-1	calcium carbonate	ACTIVE			
67762-90-7	Hydrophobic silica	ACTIVE			
14807-96-6		ACTIVE			
	titanium dioxide	ACTIVE			
1	silicon dioxide, chemically prepared	ACTIVE			
1	aluminium hydroxide	ACTIVE			
63148-62-9	Siloxanes and Silicones, di-Me	ACTIVE			

#### · Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to the State of California (Prop. 65) to cause cancer:

13463-67-7 titanium dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

TI V (Thras	hald I in	nit Valua	established	by ACCIH
ILV (Inres	.,,,,,,,,	nu vaiue	esiamismea	DV ACCIINI

14807-96-6	Talc	A4
13463-67-7	titanium dioxide	A4

#### · MAK (German Maximum Workplace Concentration)

14807-96-6 Talc	<i>3B</i>
13463-67-7 titanium dioxide	3A

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 titanium dioxide

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

(Contd. of page 8)

# Safety Data Sheet acc. to OSHA HCS

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part A

· Hazard pictograms





GHS07 GHS0

- · Signal word Warning
- · Hazard-determining components of labeling:

2,3-epoxypropyl o-tolyl ether

titanium dioxide

· Hazard statements

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

Suspected of causing cancer.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- · Date of preparation / last revision 04/25/2023 / 221
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 2: Germ cell mutagenicity – Category 2

Carc. 2: Carcinogenicity - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Tel.: (866) 329-8724

# Safety Data Sheet acc. to OSHA HCS

Printing date 04/25/2023 Reviewed on 04/25/2023

### 1 Identification

- · Product identifier
- · Trade name: Sure Anchor<sup>TM</sup> I J51 Part B
- · Article number: 100908B
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dayton® Superior

4226 Kansas Avenue

Kansas City, KS 66106 Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident

involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

# 2 Hazard(s) identification

#### · Classification of the substance or mixture

Acute Tox. 4 H332 Harmful if inhaled.

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eve Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child. Repr. 2

H402 Harmful to aquatic life. *Aquatic Acute 3* 

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05

GHS07

· Signal word Danger

#### · Hazard-determining components of labeling:

*m-phenylenebis*(*methylamine*)

cyclohex-1,2-ylenediamine

#### · Hazard statements

Harmful if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

Specific treatment (see on this label).

(Contd. on page 2)

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part B

(Contd. of page 1)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 1Reactivity = 2

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
471-34-1	calcium carbonate	<70.0%	
104-40-5	nonylphenol	<20.0%	
1477-55-0	m-phenylenebis(methylamine)	≥5-<15%	
14808-60-7	Quartz (SiO2)	≥0.1-<3.75%	
	Magnesite	<1.2%	
694-83-7	cyclohex-1,2-ylenediamine	≥0.1-<0.7%	
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic	≥0.1-≤0.3%	

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

- · Description of first aid measures
- · General information:

*Immediately remove any clothing soiled by the product.* 

*In the event of persistent symptoms recieve medical treatment.* 

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

*In case of unconsciousness place patient stably in side position for transportation.* 

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· After skin contact:

*Immediately wash with water and soap and rinse thoroughly.* 

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part B

(Contd. of page 2)

After swallowing:

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Seek medical treatment.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool dry location.
- Information about storage in one common storage facility: Store away from incompatible materials.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part B

(Contd. of page 3)

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 471-34-1 calcium carbonate

- PEL Long-term value: 15\* 5\*\* mg/m³
  \*total dust \*\*respirable fraction
- REL Long-term value: 10\* 5\*\* mg/m³ \*total dust \*\*respirable fraction
- TLV TLV withdrawn

#### 1477-55-0 m-phenylenebis(methylamine)

- REL Ceiling limit value: 0.1 mg/m<sup>3</sup>
  - Skin
- TLV Ceiling limit value: 0.1 mg/m³, 0.018 ppm

#### 14808-60-7 Quartz (SiO2)

- PEL Long-term value: 0.05\* mg/m<sup>3</sup> \*resp. dust; 30mg/m3/%SiO2+2
- REL Long-term value: 0.05\* mg/m<sup>3</sup>

\*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025\* mg/m³ \*as respirable fraction

### 546-93-0 Magnesite

- PEL Long-term value: 15\* 5\*\* mg/m³
  \*total dust \*\*respirable fraction
- REL Long-term value: 10\* 5\*\* mg/m³ \*total dust \*\*respirable fraction
- TLV TLV withdrawn
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

(Contd. of page 4)

# Safety Data Sheet acc. to OSHA HCS

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part B

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection: Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical proper	ties			
· Information on basic physical and c · General Information · Appearance:	chemical properties			
Form:	Liquid			
Color:	Grey			
· Odor:	Distinctive			
· Odor threshold:	Not determined.			
· pH-value:	Not determined.			
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Undetermined.			
· Flash point:	>94 °C (>201.2 °F)			
· Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:	370 °C (698 °F)			
· Decomposition temperature:	Not determined.			
· Auto igniting:	Product is not selfigniting.			
· Danger of explosion:	Product does not present an explosion hazard.			
· Explosion limits:				
Lower:	1.0 Vol %			
Upper:	0.0 Vol %			
· Vapor pressure:	Not determined.			
· Density at 20 °C (68 °F):	1.776 g/cm³ (14.82072 lbs/gal)			
Relative density	Not determined.			
· Vapor density	Not determined.			
· Evaporation rate	Not determined.			
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.			
· Partition coefficient (n-octanol/water): Not determined.				
· Viscosity:	,			
Dynamic:	Not determined.			
Kinematic:	Not determined.			
· Solvent content:				
Solids content:	100.0 %			

(Contd. on page 6)

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part B

(Contd. of page 5)

· Other information

No further relevant information available.

### 10 Stability and reactivity

- Reactivity No decomposition if stored and applied as directed.
- · Chemical stability No decomposition if stored and applied as directed
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with acids, alkalis and oxidizing agents.
- · Conditions to avoid Keep away from heat and sources of ignition.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

### 1477-55-0 m-phenylenebis(methylamine)

 Oral
 LD50
 1,040 mg/kg (rat)

 Inhalative
 LC50/4 h
 2.4 mg/l (rat)

- · Primary irritant effect:
- · on the skin: May cause skin irritation.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International	Agency j	or I	Kesearci	n on	Cancer)
-----------------------	----------	------	----------	------	---------

14808-60-7 Quartz (SiO2)

K

· NTP (National Toxicology Program)

14808-60-7 Quartz (SiO2)

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 7)

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part B

(Contd. of page 6)

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to Federal, State, and Local regulations.

1 / //	7		C	7.0
IAI	Vanc	nort II	ntorma	tion
TTT	נטעעט ע	$vv\iota\iota$	ujujuu	uvu

1 3	
· UN-Number · DOT, ADR, IMDG, IATA	UN1760
· UN proper shipping name · DOT	Corrosive liquids, n.o.s. (nonylphenol)
· ADR	1760 CORROSIVE LIQUID, N.O.S. (nonylphenol), ENVIRONMENTALLY HAZARDOUS
· IMDG	CORROSIVE LIQUID, N.O.S. (nonylphenol), MARINE POLLUTANT
· IATA	CORROSIVE LIQUID, N.O.S. (nonylphenol)

- · Transport hazard class(es)
- $\cdot DOT$



· Class 8 Corrosive substances

· Label

(Contd. on page 8)

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part B

	(Contd. of page
· ADR, IATA	
· Class · Label	8 Corrosive substances 8
· IMDG	
· Class · Label	8 Corrosive substances 8
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards: Marine pollutant:	Product contains environmentally hazardous substances nonylphenol Yes Symbol (fish and tree)
Special precautions for user Danger code (Kemler): EMS Number: Stowage Category Stowage Code	Warning: Corrosive substances 80 F-A,S-B A SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73, and the IBC Code	/7 <b>8</b> Not applicable.
Transport/Additional information:	
DOT Remarks:	Add "Marine Pollutant" to end of proper shipping name shipping in a bulk container (>119 gallons).
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
U.S. Domestic Ground Shipments: U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:	Same as listed for Standard Shipments above.  Same as listed for Standard Shipments above.
Emergency Response Guide (ERG) Number:	Not determine
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
	(Contd. on page

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part B

(Contd. of page 8)

· UN "Model Regulation":

UN 1760 CORROSIVE LIQUID, N.O.S. (NONYLPHENOL), 8, III, ENVIRONMENTALLY HAZARDOUS

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

104-40-5 no	onylphenol	<20.0%
· TSCA (Toxi	c Substances Control Act):	<u> </u>
471-34-1	calcium carbonate	ACTIVE
104-40-5	nonylphenol	ACTIVE
1477-55-0	m-phenylenebis(methylamine)	ACTIVE
14808-60-7	Quartz (SiO2)	ACTIVE
546-93-0	Magnesite	ACTIVE
694-83-7	cyclohex-1,2-ylenediamine	ACTIVE
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic	ACTIVE
12227-89-3	Ferric Oxide	ACTIVE
124-09-4	hexamethylenediamine	ACTIVE
156-87-6	3-aminopropan-1-ol	ACTIVE
110-60-1	tetramethylenediamine	ACTIVE
15520-10-2	2-methylpentane-1,5-diamine	ACTIVE

#### · Hazardous Air Pollutants

None of the ingredients is listed.

63148-62-9 Siloxanes and Silicones, di-Me

- · Proposition 65
- · Chemicals known to the State of California (Prop. 65) to cause cancer:

14808-60-7 Quartz (SiO2)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 10)

ACTIVE

Printing date 04/25/2023 Reviewed on 04/25/2023

Trade name: Sure Anchor<sup>TM</sup> I J51 - Part B

(Contd. of page 9)

#### • TLV (Threshold Limit Value established by ACGIH)

14808-60-7 Quartz (SiO2)

*A2* 

#### · MAK (German Maximum Workplace Concentration)

14808-60-7 Quartz (SiO2)

1

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

14808-60-7 Quartz (SiO2)

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05

S05 GHS07

· **Signal word** Danger

#### · Hazard-determining components of labeling:

m-phenylenebis(methylamine)

cyclohex-1,2-ylenediamine

#### · Hazard statements

Harmful if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- · Date of preparation / last revision 04/25/2023 / 286
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 11)

Printing date 04/25/2023 Reviewed on 04/25/2023

#### Trade name: Sure Anchor<sup>TM</sup> I J51 - Part B

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Dam. 1: Serious eye damage/eye irritation — Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Repr. 2: Reproductive toxicity – Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. of page 10)

US