

# ProAnchor Elite

**A CODE COMPLIANT anchoring adhesive approved for bulk dispensing systems!**

ProAnchor Elite is a two component, moisture tolerant, 100% solids, high modulus epoxy gel adhesive approved for use in cartridges and in bulk for anchoring in cracked and un-cracked concrete and internally threaded inserts in un-cracked concrete.

- Meets requirements of ACI 355.4 and ICC-ES AC308 per IAPMO ER-690
- High strength structural adhesive
- Ideal for anchoring dowels, bolts, reinforcing steel and threaded rod
- Fast-setting
- Suitable for dry, water saturated and water-filled holes
- Qualified for Seismic Design Categories A through F
- Made in the USA in accordance with CFR 49 section 50101

#### APPLICABLE STANDARDS

Meets AASHTO M235 & ASTM C881, IBC/IRC, FBC, LABC, LARC, DOT, and NSF 61. Acceptable for use in USDA inspected facilities.

#### VOC

Compliant with all Canadian and U.S. VOC regulations including Federal EPA, OTC, LADCO, SCAQMD & CARB.



**NEW! Anchor DesignPro Software**

*See back for details*


*Contact your Dayton Superior representative for more information or to place an order.*

# CHEMICAL SOLUTIONS



Contact your Dayton Superior representative for more details or to place an order.

	Dayton Superior® ProAnchor Elite	HILTI RE 500 V3	DeWALT® Pure110+	Simpson StrongTie SET-XP	Unitex® Pro-Poxy™ 500
Building Code Compliant (IBC/IRC)	✓	✓	✓	✓	✓
Made in the USA	✓	✗	✗	✓	✗
Cartridge & Bulk Evaluated/Approved	✓	✗	✗	✗	✗
Withstands Temperatures > 200 °F	✓	✗	✗	✗	✗
Core-Drilled Holes (SD)	✓	✓	✗	✗	✗
NSF / ANSI 61 & 372 Drinking Water & Lead Free	✓	✗	✗	✗	✗
Treaded Rod, Rebar & Internally Threaded Inserts	✓	✓	✗	✗	✗
No Hole Cleaning w/ Vacuum Drill Bits	✓	✓	✓	✓	✗
Tested For Use With Battery Dispensing Tools	✓	✓	✓	✓	✗
Full Cure @ 75 °F in 7 Hours or Less	✓	✓	✗	✗	✓
Uncracked Bond Strength (avg), 176+ Short Term Temp, No Sustained Load (psi)	<b>1,925</b>	<b>1,460</b>	<b>1,190</b>	<b>N/A*</b>	<b>725</b>
Cracked Bond Strength (avg), 176+ Short Term Temp, No Sustained Load (psi)	<b>1,130</b>	<b>855</b>	<b>880</b>	<b>N/A*</b>	<b>620</b>



**NEW! Anchor DesignPro Software**

Free download - get started at: [www.DaytonSuperior.com/designPro](http://www.DaytonSuperior.com/designPro)

\*Simpson SET-XP limited to a maximum short-term temperature of 150 °F and therefore is not applicable for this comparison to products which can be designed to higher temperatures. Hilti is a registered trademark of Hilti Aktiengesellschaft Corporation | Simpson, SET-XP is a registered trademarks of Simpson Strong-Tie Company, Inc. | Pure110+ & DeWalt are trademarks of Stanley Black & Decker



Building Strength™

DAYTONSUPERIOR.COM | 800-745-3700

