TOP-CAST® SS 100 Site Saver

- Protects surfaces from overspray and splatters
- Replaces costly plastic barriers
- Easy removal within 24 hours

TOP-CAST® EX 200 Wash-Off Extender

- Extends Top-Cast removal times
- Provides several hours of extension
- Contributes to a more consistent etch.

TOP-CAST® PR 300 Penetrating Protector

- · Penetrates, protects, and hardens
- Dustproofs with lasting moisture protection
- Extends life of substrate

TOP-CAST® CS 400 Cure and Seal

- Cures, seals, and dustproofs exposed aggregate
- Semi-gloss finish with stain protection
- UV stable and non-yellowing

TOP-CAST® HG 500 High Gloss Sealer

- Seals and protects with a high gloss finish
- Resists common chemicals, blushing and hazing
- Excellent weatherability and non-yellowing

Our Top-Cast Team is happy to answer any questions:

877-266-7732



- TOP-CAST® SS 100 Site Saver
- TOP-CAST® EX 200 Wash-Off Extender
- TOP-CAST® PR 300 Penetrating Protector
- TOP-CAST® CS 400 Cure and Seal
- TOP-CAST® HG 500 High Gloss Sealer

A BREAKTHROUGH, EASY TO USE

CONCRETE FINISHING SYSTEM

THAT LOWERS APPLICATION COST

FOR HIGHER MARGINS.

The **Top-Cast Decorative Finish System** is designed to make the Top-Cast application easier while providing various levels of protection and a range of glossy finishes.



When used together with Top-Cast
Surface Retarders, the Decorative Finish
System provides a complete package for beautifully designed, protected and sealed exposed aggregate surfaces.

WWW.DAYTONSUPERIOR.COM Technical Services: 877-266-7732



Copyright © 2025 Dayton Superior Corporation, All Rights Reserved WF 947900



TOP-CAST®

DECORATIVE CONCRETE FINISH SYSTEM





TOP-CAST®

ELEGANT AND BEAUTIFUL CONCRETE THAT ANYONE CAN ACHIEVE

TOP-CAST® by GCP Applied Technologies Inc.
Photos courtesy of Trademark Concrete Systems. Inc.

GET BETTER RESULTS. NO MISTAKES. IT'S SO EASY.

Adds profitable decorative opportunities with no special equipment or training.



TOP-CAST[®] **Concrete Surface Retarders**

CHOOSE YOUR FINISH

- Available in 12 different grades that create a range of finishes from micro-etch to fully exposed aggregate.
- Grade selection based on estimated aggregate exposure level.
- All grades are formulated separately to create distinctly different products.

| TOP-CAST FINISH TABLE | NO. CODE | ESTIMATED AGGREGATE EXPOSURE LEVEL | PACKAGE COLOR |
|-----------------------|----------|------------------------------------|---------------|
| MICRO ETCH | 01 | Light Acid Wash | White |
| | 03 | Acid Etch Finish | Violet |
| | 05 | Sandblast Finish | Light Blue |
| | 15 | Up to 1/4" (6.5mm) | Yellow |
| MEDIUM ETCH | 25 | 1/8" - 1/4" (3mm - 6.5mm) | Beige |
| | 50 | 1/8" - 3/8" (3mm - 9.5mm) | Canary Green |
| | 75 | 1/8" - 3/8" (3mm - 9.5mm) | Blue |
| | 100 | 3/8" - 1/2" (9.5mm - 13mm) | Gray |
| FULL-DEPTH ETCH | 125 | 3/8" - 5/8" (9.5mm - 16mm) | Pink |
| | 150 | 3/8" - 5/8" (9.5mm - 16 mm) | Green |
| | 200 | 5/8" - 1" (16mm - 25mm) | Salmon |
| | 250 | 1" - 1-1/2" (25mm - 38mm) | Orange |

Values listed are for 3500 psi mix. In some conditions with certain mixes it may be neccessary to rinse the retarded matrix the same day.

Always prepare mock up at the project to verify the appropriate grade for specific mix designs.

UNIFORM HIGH-QUALITY FINISH

- **COST-EFFECTIVE COVERAGE RATES**
- **OUNMATCHED RELIABILITY AND CONTROL**
- **OUTSTANDING TECHNICAL SUPPORT**

O ENVIRONMENTALLY FRIENDLY



Refer to the Technical Data Sheet, Top-Cast User Guide and SDS for full instructions and safe practices prior to use.

Visit: www.DaytonSuperior.com

