

TOP-CAST® SS 100 Site Saver

- Protects surfaces from overspray and splatters
- Replaces costly plastic barriers
- Easy removal within 24 hours

TOP-CAST® EX 200 Wash-Off Extender

- Extends Top-Cast removal times
- Provides several hours of extension
- Contributes to a more consistent etch

TOP-CAST® PR 300 Penetrating Protector

- Penetrates, protects, and hardens
- Dustproofs with lasting moisture protection
- Extends life of substrate

TOP-CAST® CS 400 Cure and Seal

- Cures, seals, and dustproofs exposed aggregate
- Semi-gloss finish with stain protection
- UV stable and non-yellowing

TOP-CAST® HG 500 High Gloss Sealer

- Seals and protects with a high gloss finish
- Resists common chemicals, blushing and hazing
- Excellent weatherability and non-yellowing

Our Top-Cast Team is happy to answer any questions:

877-266-7732



THE COMPLETE TOP-CAST® DECORATIVE FINISH SYSTEM

- TOP-CAST® SS 100 Site Saver
- TOP-CAST® EX 200 Wash-Off Extender
- TOP-CAST® PR 300 Penetrating Protector
- TOP-CAST® CS 400 Cure and Seal
- TOP-CAST® HG 500 High Gloss Sealer

A BREAKTHROUGH, EASY TO USE
CONCRETE FINISHING SYSTEM
THAT LOWERS APPLICATION COST
FOR HIGHER MARGINS.

The **Top-Cast Decorative Finish System** is designed to make the Top-Cast application easier while providing various levels of protection and a range of glossy finishes.



When used together with Top-Cast Surface Retarders, the Decorative Finish System provides a complete package for beautifully **designed, protected and sealed** exposed aggregate surfaces.

WWW.DAYTONSUPERIOR.COM
Technical Services: 877-266-7732



Copyright © 2020 Dayton Superior Corporation, All Rights Reserved.



**BUILDING
STRENGTH™**

TOP-CAST®

DECORATIVE
CONCRETE FINISH
SYSTEM



**DAYTON
SUPERIOR**

TOP-CAST®

**ELEGANT AND BEAUTIFUL
CONCRETE THAT ANYONE
CAN ACHIEVE**

TOP-CAST® by GCP Applied Technologies Inc.
Photos courtesy of Trademark Concrete Systems, Inc.

**GET BETTER RESULTS.
NO MISTAKES.
IT'S SO EASY.**

*Adds profitable decorative opportunities with
no special equipment or training.*

SPRAY

- Spray or roll after bleed water dissipates and concrete is thumbprint hard
- Pigmented to show coverage
- No plastic needed

RINSE

- Expose within 24 hours
- Rinse same day or pressure wash next day

PROTECT

- Various levels of stain protection
- Harden, dustproof and seal
- Extend life of exposed aggregate

SHOW




- Uniform finish every time
- Increases productivity with better results



TOP-CAST® Concrete Surface Retarders

CHOOSE YOUR FINISH

- Available in 12 different grades that create a range of finishes from micro-etch to fully exposed aggregate.
- Grade selection based on estimated etch depth and strength of mix.
- All grades are formulated separately to create distinctly different products.

TOP-CAST FINISH TABLE	NO. CODE	ESTIMATED ETCH DEPTH	PACKAGE COLOR
MICRO ETCH 	01	Light Acid Wash	White
	03	Acid Etch Finish	Violet
	05	Sandblast Finish	Light Blue
	15	Up to 1/4" (6.5mm)	Yellow
MEDIUM ETCH 	25	1/8" - 1/4" (3mm - 6.5mm)	Beige
	50	1/8" - 3/8" (3mm - 9.5mm)	Canary Green
	75	1/8" - 3/8" (3mm - 9.5mm)	Blue
	100	3/8" - 1/2" (9.5mm - 13mm)	Gray
FULL-DEPTH ETCH 	125	3/8" - 5/8" (9.5mm - 16mm)	Pink
	150	3/8" - 5/8" (9.5mm - 16 mm)	Green
	200	5/8" - 1" (16mm - 25mm)	Salmon
	250	1" - 1-1/2" (25mm - 38mm)	Orange

Values listed are for 3500 psi mix. In some conditions with certain mixes it may be necessary to rinse the retarded matrix the same day.

Always prepare mock up at the project to verify the appropriate grade for specific mix designs.

UNIFORM HIGH-QUALITY FINISH

UNMATCHED RELIABILITY AND CONTROL

ENVIRONMENTALLY FRIENDLY



COST-EFFECTIVE COVERAGE RATES
UP TO 3X BETTER THAN COMPETITORS

OUTSTANDING TECHNICAL SUPPORT

Refer to the Technical Data Sheet, Top-Cast User Guide and SDS for full instructions and safe practices prior to use.
Visit: www.DaytonSuperior.com