

Green = Compliance

Product	V.O.C. (g/L)	EPA	OTC	LADCO	SCAQMD	CARB	Maryland	Utah**	CO Reg 21	Canada	Shelf Life (months)
Accelerators		N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	
C-Set	0										12
Q-Set	0										12
Bond Breakers		600	350	350	350/100 ⁴	350	350	350	350	350	
Sure Lift® J6WB	<100										9
Sure Lift with Dye J6D	<750	¹									24
Sure Lift J6LVOC	<350										24
Maxi Tilt with Dye	<100										9
Cleaners and Strippers		N/R	N/R	N/R	Regulated	Regulated	N/R	N/R	50	N/R	
Citrus Cleaner J48	<800										24
Zero VOC J49 Cleaner	0										24
Green Bean Clean®	<600										24
Dissolve It	<150										24
Cure & Seals		700	350	350	100	350	350	350	350	350	
Cure & Seal 309 J18	<200										18
Cure & Seal 1315 J22WB	<350										12
Cure & Seal LV 25% J20UV	<700										24
Cure & Seal 25% J20LVOC	<350										24
Cure & Seal 25% J22UV	<700										24
Cure & Seal 30% J23UV	<700										24
Cure & Seal 30% J23LVOC	<350										24
Cure & Seal 309 EF	<100										18
Cure & Seal 1315 EF	<100										18
Curing Compounds		350	350	350	100 / 350 ²	350	350	350	350	350	
Clear Cure VOC J7WB	<100										18
City White Cure J8	<100										12
White Wax Cure J9A	<100										12
White Resin Cure J10W	<350				²						18
Clear Resin Cure J11W	<100										18
Resin Cure with Dye J11WD	<100										18
White Wax Cure CRD300	<100										12
Cure Hard J14	0										24
Epoxy Products		N/R	N/R	N/R	N/R	N/R	N/R	350	N/R	N/R	
Sure Anchor Epoxy J50	0										24
Sure Anchor I J51	0										18
All Weather Epoxy J51AW	0										24

SEE NOTES ON PAGE 3

Product	V.O.C. (g/L)	EPA	OTC	LADCO	SCAQMD	CARB	Maryland	Utah**	CO Reg 21	Canada	Shelf Life (months)
Pro-Poxy 50	0										24
Sure Seal LV/LM	0										24
Sure Bond J58	0										24
Slow Set Bonding Agent	0										24
Pro-Poxy 2500	0										24
Rebar Spray J62	556*										24
Epoxy Grout J55	0										24
Rapid Resin Repair	0										12
Poxy-Chock	0										24
Sure Fil J52	0										24
Pro-Poxy P606	0										24
ProAnchor Elite	0										24
ProAnchor WeatherMax	0										18
Evaporation Retardants		N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	
AquaFilm® J74RTU	0										12
Form Releases		450	250	250	100	250	250	250	250	250	
Clean Strip J1 EF	0										12
Clean Strip J1A	<250										24
Clean Strip J1A Winter Grade	<250										24
Clean Strip J100VOC	<100										24
Clean Strip Ultra J3	<250										24
Magic Kote®	<250										24
Clean Strip J2	<450										24
Clean Strip J2 Winter Grade	<450										24
Pure Pro Zero	0										24
Latex Bonding Agents/Adhesives		N/R	N/R	N/R	N/R	N/R	N/R	N/R	55	N/R	
Acrylic Bonding Agent J40	<50										18
PVA Bonding Agent J41	0										12
Level Primer J42	1										12
Level Primer J42RTU	0										12
Liquid Densifiers		N/R	N/R	N/R	N/R	N/R	100	N/R	350	N/R	
Densifier Concentrate J12	0										12
Densifier J13	0										12
Sure Hard Densifier J17	0										12

SEE NOTES ON PAGE 3

Product	V.O.C. (g/L)	EPA	OTC	LADCO	SCAQMD	CARB	Maryland	Utah**	CO Reg 21	Canada	Shelf Life (months)
Pentra-Hard Densifier	<50										36
Pentra-Hard Guard	<50										24
Pentra-Hard Finish	<50										24
Sealers		600	400	400	100	400	100	400	100	400	
Ultra Seal EF	<100										18
AggreGloss J25	<700	1									24
AggreGloss Satin J25S	<700	1									24
Anti Spall J33	<400										24
Tuf Seal J35	<800	1									24
Tuf Seal Satin J35S	<800	1									24
Tuf Seal J35LVOC	<100										24
Tuf Seal J35LVOC Satin	<100										24
AggreGloss J25LVOC	<100										24
AggreGloss J25LVOC Satin	<100										24
Surface Retarders		N/R	N/R	N/R	Regulated	N/R	780	780	780	N/R	
Top-Cast					3						24
Top-Cast SS 100	<100										24
Top-Cast EX 200	<100										18
Top-Cast PR 300	0										12
Top-Cast CS 400	<100										18
Top-Cast HG 500	<100										18
Water Repellants		600	400	400	350	400	350	350	350	400	
Weather Worker 10% J26WB	<100										12
Weather Worker 40% J29	<600										24
Weather Worker 100% J29A	<250										24

NOTES:

1. Manufacturer pays exceedance fee which allows use of product under EPA regulations.
 2. 350 g/L for Roadways and Bridges ONLY; for all other applications the VOC is 100 g/L.
 3. All grades of Top-Cast are compliant with all Canadian and U.S. VOC regulations for sealers including Federal EPA, OTC, LADCO, SCAQMD and CARB
 4. SCAQMD requires products to conform to lowest VOC for advertised use, so bond breakers fall under cures
- * Aerosol can products are also measured by MIR (maximum incremental activity) or VOC % by weight. J62 has an MIR of 1.22 and a V.O.C. 51.1% by weight
- ** Only seven Utah counties are under these regulations: Box Elder, Cache, Davis, Salt Lake, Tooele, Utah, and Weber

SCAQMD: In the State of California, all of Orange County, urban portions of Los Angeles, Riverside and San Bernardino Counties

CARB: State of California, other than those under the SCAQMD regulations

- OTC:** States of CT, DE, MA, ME, NH, NJ, NY, PA, RI, VT, No. VA, District of Columbia
- LADCO:** States of IL, IN, MI, OH, WI
- EPA:** All States not governed by the more restrictive aforementioned regulatory agencies
- Maryland:** Maryland VOC standards changed January 1, 2017
- Utah:** Only the following counties are under these regulations: Box Elder, Cache, Davis, Salt Lake, Tooele, Utah, and Weber
- Col Reg 21:** Colorado VOC standards changed May 1, 2020