

Green = Compliance

Product	V.O.C. (g/L)	EPA	OTC	LADCO	SCAQMD	CARB	Maryland	Utah**	CO Reg 21	Canada	Shelf Life (months)
Accelerators		N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	
C-Set	0										12
Q-Set	0										12
Bond Breakers		600	350	350	350/100 ⁴	350	350	350	350	350	
Sure Lift® J6WB	<100										9
Sure Lift with Dye J6D	<750	¹									24
Sure Lift J6LVOC	<350										24
Maxi Tilt with Dye	<100										9
Cleaners and Strippers		N/R	N/R	N/R	Regulated	Regulated	N/R	N/R	50	N/R	
Citrus Cleaner J48	<800										24
Zero VOC J49 Cleaner	0										24
Green Bean Clean®	<600										24
Dissolve It	<150										24
Cure & Seals		700	350	350	100	350	350	350	350	350	
Cure & Seal 309 J18	<200										18
Cure & Seal 1315 J22WB	<350										12
Cure & Seal LV 25% J20UV	<700										24
Cure & Seal 25% J20LVOC	<350										24
Cure & Seal 25% J22UV	<700										24
Cure & Seal 30% J23UV	<700										24
Cure & Seal 30% J23LVOC	<350										24
Cure & Seal 309 EF	<100										18
Cure & Seal 1315 EF	<100										18
Curing Compounds		350	350	350	100 / 350 ²	350	350	350	350	350	
Clear Cure VOC J7WB	<100										18
City White Cure J8	<100										12
White Wax Cure J9A	<100										12
White Resin Cure J10W	<350				²						18
Clear Resin Cure J11W	<100										18
Resin Cure with Dye J11WD	<100										18
White Wax Cure CRD300	<100										12
Cure Hard J14	0										24
Epoxy Products		N/R	N/R	N/R	N/R	N/R	N/R	350	N/R	N/R	
Sure Anchor Epoxy J50	0										24
Sure Anchor I J51	0										18
All Weather Epoxy J51AW	0										24

SEE NOTES ON PAGE 3

Product	V.O.C. (g/L)	EPA	OTC	LADCO	SCAQMD	CARB	Maryland	Utah**	CO Reg 21	Canada	Shelf Life (months)
Pro-Poxy 50	0										24
Sure Seal LV/LM	0										24
Sure Bond J58	0										24
Slow Set Bonding Agent	0										24
Pro-Poxy 2500	0										24
Rebar Spray J62	556*										24
Epoxy Grout J55	0										24
Rapid Resin Repair	0										12
Poxy-Chock	0										24
Sure Fil J52	0										24
Pro-Poxy P606	0										24
ProAnchor Elite	0										24
ProAnchor WeatherMax	0										18
Evaporation Retardants		N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	N/R	
AquaFilm® J74RTU	0										12
Form Releases		450	250	250	100	250	250	250	250	250	
Clean Strip J1 EF	0										12
Clean Strip J1A	<250										24
Clean Strip J1A Winter Grade	<250										24
Clean Strip J100VOC	<100										24
Clean Strip Ultra J3	<250										24
Magic Kote®	<250										24
Clean Strip J2	<450										24
Clean Strip J2 Winter Grade	<450										24
Pure Pro Zero	0										24
Latex Bonding Agents/Adhesives		N/R	N/R	N/R	N/R	N/R	N/R	N/R	55	N/R	
Acrylic Bonding Agent J40	<50										18
PVA Bonding Agent J41	0										12
Level Primer J42	1										12
Level Primer J42RTU	0										12
Liquid Densifiers		N/R	N/R	N/R	N/R	N/R	100	N/R	350	N/R	
Densifier Concentrate J12	0										12
Densifier J13	0										12
Sure Hard Densifier J17	0										12

SEE NOTES ON PAGE 3

Product	V.O.C. (g/L)	EPA	OTC	LADCO	SCAQMD	CARB	Maryland	Utah**	CO Reg 21	Canada	Shelf Life (months)
Pentra-Hard Densifier	<50										36
Pentra-Hard Guard	<50										24
Pentra-Hard Finish	<50										24
Polymer Floor Coatings		400	250	250	50	250	100	250	100	250	
Spec Cote WB (Clear)	<250										12
Spec Cote WB (w/Color)	<200										12
Spec Cote 100	0										12
Spec Cote 100 Clear	0										12
Spec Cote 100 CR	<100										12
Spec Cote Urethane	<400										12
Sealers		600	400	400	100	400	100	400	100	400	
Ultra Seal EF	<100										18
AggreGloss J25	<700	1									24
AggreGloss Satin J25S	<700	1									24
Anti Spall J33	<400										24
Tuf Seal J35	<800	1									24
Tuf Seal Satin J35S	<800	1									24
Tuf Seal J35LVOG	<100										24
Tuf Seal J35LVOG Satin	<100										24
AggreGloss J25LVOG	<100										24
AggreGloss J25LVOG Satin	<100										24
Surface Retarders		N/R	N/R	N/R	Regulated	N/R	780	780	780	N/R	
Top-Cast					3						24
Top-Cast SS 100	<100										24
Top-Cast EX 200	<100										18
Top-Cast PR 300	0										12
Top-Cast CS 400	<100										18
Top-Cast HG 500	<100										18
Water Repellants		600	400	400	350	400	350	350	350	400	
Weather Worker 10% J26WB	<100										12
Weather Worker 40% J29	<600										24
Weather Worker 100% J29A	<250										24

NOTES:

1. Manufacturer pays exceedance fee which allows use of product under EPA regulations.
2. 350 g/L for Roadways and Bridges ONLY; for all other applications the VOC is 100 g/L.

- 3.** All grades of Top-Cast are compliant with all Canadian and U.S. VOC regulations for sealers including Federal EPA, OTC, LADCO, SCAQMD and CARB
 - 4.** SCAQMD requires products to conform to lowest VOC for advertised use, so bond breakers fall under cures
- * Aerosol can products are also measured by MIR (maximum incremental activity) or VOC % by weight. J62 has an MIR of 1.22 and a V.O.C. 51.1% by weight
 - ** Only seven Utah counties are under these regulations: Box Elder, Cache, Davis, Salt Lake, Tooele, Utah, and Weber

SCAQMD: In the State of California, all of Orange County, urban portions of Los Angeles, Riverside and San Bernardino Counties

CARB: State of California, other than those under the SCAQMD regulations

OTC: States of CT, DE, MA, ME, NH, NJ, NY, PA, RI, VT, No. VA, District of Columbia

LADCO: States of IL, IN, MI, OH, WI

EPA: All States not governed by the more restrictive aforementioned regulatory agencies

Maryland: Maryland VOC standards changed January 1, 2017

Utah: Only the following counties are under these regulations: Box Elder, Cache, Davis, Salt Lake, Tooele, Utah, and Weber

Col Reg 21: Colorado VOC standards changed May 1, 2020