

## TECHNICAL DATA SHEET

### DESCRIPTION

Spacer wheels are designed to easily clip over rebar, providing proper cover spacing between the formwork and rebar.

### APPLICATION

Intended for drill shafts, caissons, precast, or other applications utilizing formwork.



### FEATURES

- Multiple cover ranges from 5/8" to 3" – concrete cover is defined as the distance from where the reinforcement sits in the hub of the wheel to outside of the wheel where it contacts the form
- Designed to fit a various range of mesh and rebar sizes
- Lightweight
- Locking wheel available in 3" size only

### BENEFITS

- Quick and easy installation
- Concrete gray color to match concrete

### APPROVALS / COMPLIANCE

- ACI 315-99
- CRSI requirements for Class 1 compliance

### ORDERING INFORMATION

#### INFRASTRUCTURE - SPACER WHEELS

| Product Code | Description              | Weight    |
|--------------|--------------------------|-----------|
| 1202-4002    | PP35 - 3/4" MESH         | 0.0059 LB |
| 1202-4003    | PP35 - 5/8" MESH         | 0.0059 LB |
| 1202-4000    | P35 - 1" MESH - #2       | 0.0176 LB |
| 1202-4010    | PP35 - 1" #3-#6          | 0.0242 LB |
| 1202-4001    | PP35 - 3/4" #1-#2        | 0.0077 LB |
| 1202-4011    | PP35 - 1" #3-#6 BULK     | 0.0242 LB |
| 1202-4015    | PP35 - 1-1/2" #1-#2      | 0.0264 LB |
| 1202-4025    | PP35 - 1-1/2" #3-#6      | 0.0374 LB |
| 1202-4030    | PP35 - 2" MESH           | 0.0400 LB |
| 1202-4040    | PP35 - 2" #3-#6          | 0.0617 LB |
| 1202-4045    | PP35 - 2-3/8" #4-#8      | 0.0463 LB |
| 1202-4050    | PP35 - 3" #3-#6          | 0.0749 LB |
| 1202-4055    | PP45 - 3" #4 -#6 LOCKING | 0.2621 LB |

### MANUFACTURER

Dayton Superior Corporation  
 1125 Byers Road  
 Miamisburg, OH 45342  
 Customer Service: 888-977-9600  
 Technical Services: 877-266-7732  
 Website: [www.daytonsuperior.com](http://www.daytonsuperior.com)

### WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.