

TECHNICAL DATA SHEET

DESCRIPTION

Shims are designed out of a high impact material and to be used to level concrete during erection

APPLICATION

Intended for precast and tilt-up applications



FEATURES

- Manufactured from high impact polystyrene
- 5000-6000 PSI bearing capacity
- Will not rust or stain

BENEFITS

- Using shims helps even out irregularities in foundation and other concrete structures
- Easy way to ensure aesthetically pleasing & structurally sound construction

INSTALLATION

1. Place shims as needed between foundation (or structural member) and the precast / tilt-up element

ORDERING INFORMATION

SHIMS

Product Code	Description	Weight
1202-4200	2" X 2" X 1/16"	0.007 LB
1202-4205	2" X 2" X 1/8"	0.014 LB
1202-4210	2" X 2" X 1/4"	0.028 LB
1202-4215	2" X 2" X 1/2"	0.055 LB
1202-4220	3" X 3" X 1/16"	0.011 LB
1202-4225	3" X 3" X 1/8"	0.035 LB
1202-4230	3" X 3" X 1/4"	0.062 LB
1202-4235	3" X 3" X 1/2"	0.115 LB
1202-4240	4" X 6" X 1/4"	0.212 LB
1202-4241	4" X 6" X 1/8"	0.108 LB
1202-4242	4" X 6" X 1/16"	0.055 LB

MANUFACTURER

Paragon Products
1516 East Mapleleaf Drive
Mount Pleasant, IA 52641
1-800-776-0385

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.