

TECHNICAL DATA SHEET

DESCRIPTION

Concrete Test Cylinders are used to test and monitor concrete strength in applications where minimum strength is required.

APPLICATION

For use in any application that uses concrete.



FEATURES

- Available sizes: 2"x4", 3"x6", 4"x8", 6"x12"
- All sizes have domed lids except for the 2"x4" cylinder
- Reinforced lip and bottom
- 6"x12" Cylinder and Lid SOLD SEPERATELY

BENEFITS

- Attached lid (on sizes up to 4"x8") makes for easy use on job site
- Notched lip for easy stripped

APPROVALS / COMPLIANCE

- Meets all ASTM and AASHTO standards
- Plastic specifications in reference to impact resistance (D256) and water absorption (D570) can be supplied upon request

ORDERING INFORMATION

ACCESSORIES - CONCRETE TEST CYLINDER W/ FLAT LID

Product Code	Description	Weight
1202-5000	2" X 4" GRAY	0.057 LB
1202-5020	4" X 8" GRAY	0.184 LB
1202-5025	4" X 8" GRAY	0.184 LB

ACCESSORIES - CONCRETE TEST CYLINDER W/ DOMED LID

Product Code	Description	Weight
1202-5005	3" X 6" GRAY	0.184 LB
1202-5010	4" X 8" GRAY	0.313 LB
1202-5012	4" X 8" YELLOW	0.313 LB
1202-5014	4" X 8" ORANGE	0.184 LB

ACCESSORIES - CONCRETE TEST CYLINDER & LID

Product Code	Description	Weight
1202-7000	6" X 12" YELLOW CONCRETE TEST CYLINDER ONLY	0.652 LB
1202-8000	6" X 12" GRAY TEST CYLINDER ONLY - PACKAGED 36 TO A CARTON	0.653 LB
1202-8850	6" X 12" GRAY TEST CYLINDER ONLY - PACKAGED 20 TO A CARTON	0.652 LB
1202-9500	6" DOMED GRAY TEST CYLINDER LID ONLY	0.060 LB
1202-9505	6" FLATGRAY TEST CYLINDER LID ONLY	0.055 LB

ACCESSORIES - CONCRETE TEST CYLINDER STRIPPING

TOOL

Product Code	Description	Weight
1202-9510	CONCRETE CYLINDER STRIPPING TOOL	1.25 LB

MANUFACTURER

Paragon Products
1516 East Mapleleaf Drive
Mount Pleasant, IA 52641
1-800-776-0385

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.