D382 Taper-Lock® Threaded Plug

Rebar Splicing

TECHNICAL DATA SHEET

DESCRIPTION


The D382 Taper-Lock® Threaded Plug fits Dayton Superior Taper-Lock® Couplers sizes #4 through #18.


APPLICATION

The plastic plugs are threaded to provide a positive, secure fit with the coupler. The threaded plugs protect the internal threads of the coupler from external factors such concrete and water. The plugs have a notch in the top surface for easy removal.

PRODUCT SPECIFICATION

- Rebar sizes #4 [13mm] through #18 [57mm]
- Made from a HDPE plastic material
- Dayton blue color





FEATURES

- D382 plastic plugs are threaded to provide a positive, secure fit with the coupler
- Used to protect the internal threads of the coupler from external factors such concrete and water
- Engineered to have a notch in the top surface for easy removal

TECHNICAL DATA

Bar Size	Product Code	Weight	'ØD' Dimension (in.)	Thickness (in.)
#4	139963	0.005	.750	.055
#5	139964	0.006	.850	.055
#6	139965	0.006	1.000	.055
#7	139966	0.008	1.150	.055
#8	139967	0.011	1.350	.055
#9	139968	0.017	1.550	.055
#10	139969	0.019	1.700	.055
#11	139970	0.022	1.800	.055
#14	139971	0.024	2.250	.055
#18	139972	0.039	3.050	.055

RELATED PRODUCTS

- D310 Taper-Lock® Standard Coupler
- D320 Taper-Lock® Transitional Coupler
- D330 Taper-Lock® Positional Coupler
- D340 Taper-Lock® Metal & Plastic Flange Couplers
- D360 Taper-Lock® Weldable Coupler

MANUFACTURER

Dayton Superior Corporation
1125 Byers Road
Miamisburg, OH 45342
Customer Service: 888-977-9600
Technical Services: 877-266-7732
Website: www.daytonsuperior.com

File Date: 1/17/2025

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.