

## TECHNICAL DATA SHEET

### DESCRIPTION

The Dayton Superior T45 Ground Release II Patch Cap is manufactured from ABS paintable plastic and provides a cosmetic alternative for patching insert holes.



6" T45 Ground Release used w/ P52, T41 & T49



2.5" T45 Ground Release used w/ T6A

### FEATURES

- Available in concrete gray color
- Available in 3/4" Nominal Size with 2.5" or 6" diameter tops to fit specific Anchors or Inserts.

### BENEFITS

- Easy to install by pushing it into the void or over anchor.
- Friction holds the cap in place
- The beveled flange assures a tight, flush fit
- No grouting is required.

### RELATED PRODUCTS

- T6A - Brace Anchor
- T41 - Ground Release Insert
- T49 - Gyro Tilt Plus® Face Lift Insert
- P52 - Swift Lift® Edge Lift Anchor

### ORDERING INFORMATION

#### GROUND RELEASE II™ PATCH CAPS

Product Code	Description	Weight
60888	3/4" (6" CAP) BRACE ANCHOR PATCH CAP FOR USE W/ P52, T41 AND T49	2.40 LB/BAG
60889	3/4" (2.5" CAP) BRACE ANCHOR PATCH CAP FOR USE W/ T6A	0.50 LB/BAG

### MANUFACTURER

Dayton Superior Corporation  
 1125 Byers Road  
 Miamisburg, OH 45342  
 Customer Service: 888-977-9600  
 Technical Services: 877-266-7732  
 Website: www.daytonsuperior.com

### WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.