

TECHNICAL DATA SHEET

DESCRIPTION

The SBP Slab Bolster with Plate is a continuous metal bar support used to maintain a consistent elevation of rebar in reinforced concrete. These use a metal plate as its base with evenly spaced legs connecting to a top wire. SBP Slab Bolster with Plate is manufactured in the USA.

APPLICATION

The SBP Slab Bolster with Plate is used to support lower slab steel on fill or other soft material. Also, continuous 5 ft long wire eliminates the need for a carrier bar or many individual supports.

PRODUCT SPECIFICATION

- The SBP Slab Bolster w/ Plate comes in heights of 1-1/2" to 3", in 1/2" Increments. Additional heights are available under special made to order in 1/4" increments. Please call for lead time, availability and pricing.
- Corrugations on top wire are spaced on 1" centers to serve as guides for placing reinforcing bars.
- Steel plate provides bearing surface on loosely compacted soil, rock base, sand base or carton forms.
- Available in plain, galvanized or epoxy-coated finish.



BENEFITS

- Continuous design reduces labor time placing rebar

HOW TO SPECIFY

Specific:
Rebar Supports shall be SB, SBU & SBP metal rebar supports manufactured by Dayton Superior Corporation

Generic:
The rebar supports shall meet building code requirements as required by

_____ (insert name here). The rebar supports shall be resistance welded, metal rebar supports manufactured from high quality steel in the USA.

APPROVALS / COMPLIANCE

- ACI 50-66
- ACI-315 & ACI-315R

RELATED PRODUCTS

- SB Slab Bolster
- SBU Slab Bolster Upper
- BB Beam Bolster
- BBU Beam Bolster Upper

HOW TO ORDER

- Specify: (1) Linear Feet Length - Quantity, (2) Name, (3) Height, (4) Special Coatings - Finish
Example: 2000, SBP Slab Bolster with Plate, 3", Plain

Additional sizes available. Please contact Dayton Superior.

ORDERING INFORMATION

SLAB BOLSTER WITH PLATE - PLAIN

Product Code	Description	Weight
70730	1-1/2" X 5'	0.270 LB / FT
70750	2" X 5'	0.300 LB / FT
70770	2-1/2" X 5'	0.300 LB / FT
70790	3" X 5'	0.550 LB / FT

MANUFACTURER

Dayton Superior Corporation
1125 Byers Road
Miamisburg, OH 45342
Customer Service: 888-977-9600
Technical Services: 877-266-7732
Website: www.daytonsuperior.com

TECHNICAL DATA SHEET

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.