


# **TECHNICAL DATA SHEET**

#### DESCRIPTION

Dayton Superior A2 Plastic Cones can be added to A3, A4 and A44 Snap Ties, and A46 and A48 Loop Ties.

## **APPLICATION**

The cones act as internal spreaders, reduce grout leakage and aid in the breakback operation.





## **FEATURES**

- A2 Plastic Cones are recommended when specifications require a nominal 1", 1-1/2", 2" or greater breakback.
- Breakback is approximately 3/16" less than the cone length.
- Plastic Cones are not intended to support loads applied by personal fail arrest systems and/or scaffold brackets.

## **TECHNICAL DATA**

DIAMETER	LENGTH
3/4"	1", 1-1/2"
1"	1", 1-1/2"
1-1/4"	1-1/2", 2"

# **RELATED PRODUCTS**

- A3 Snap Ties
- A4 Hex Head Snap Ties
- A44 Stainless Steel Snap Ties
- A46 Loop Ties
- A48 Gang Loop Ties

#### ORDERING INFORMATION

Product Code	Description	Weight
49112	1" DIA X 1"	0.009 LB
49108	3/4" DIA X 1"	0.010 LB
49150	3/4" DIA X 1-1/2"	0.010 LB
49118	1" DIA X 1-1/2"	0.020 LB
49160	1-1/4"DIA X 1-1/2"	0.020 LB
49172	1" DIA X 2"	0.020 LB

## **MANUFACTURER**

Dayton Superior Corporation 1125 Byers Road Miamisburg, OH 45342 Customer Service: 888-977-9600 Technical Services: 877-266-7732 Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in person dried than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.