


TECHNICAL DATA SHEET

DESCRIPTION

The Double Frame Anchor is made from threaded D/R Euro Bar, providing the ability to develop the full load of the bar when properly embedded.

APPLICATION

The Double Frame Anchor is designed for one-sided forming applications utilizing an embedded anchor.



FEATURES

- Easy to install and use
- Non-weldable

TECHNICAL DATA

NOTE: Minimum Concrete Strength is 25MPa

Diameter	A (mm)	L (mm)	L1 (mm)	L2 (mm)	Working Load on each end (kN)	Weight (kg)
15mm	230	550	360	340	90	1.87
20mm	300	600	380	320	160	3.94
26mm	350	840	550	360	280	8.69

RELATED PRODUCTS

- B12AD Euro Bar
- B12ASW Swivel Wing Nut
- B12AW Wing Nut
- B12AWN Cast Nut Washer

ORDERING INFORMATION

D/R THREAD BAR - DOUBLE LOOP ANCHOR

Product Code	Description	Weight
100054	15MM X 550MM	4.12 LB
100055	20MM X 600MM	8.69 LB

D/R THREAD BAR - EURO BARS

Product Code	Description	Weight
146350	15MM X 19'-1"	33.66 LB
146351	20MM X 19'-1"	33.66 LB

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.