





TECHNICAL DATA SHEET


DESCRIPTION

B12A D/R Thread Bar is a high strength, fast-acting, cold-rolled contour thread.

APPLICATION

B12A D/R Thread Bars are designed for securing and spacing clamp type forms.





FEATURES

- The B12A D/R Thread Bar's 2-1/2 threads per inch offers fast installation and stripping.
- D/R Thread Bar is available in 20'-0" standard lengths and can be cut to specific project requirements.
- Field cutting with Carborundum blades is easily accomplished without thread damage.
- Safe Working Load provides a factor of safety of approximately 2 to 1.

RELATED PRODUCTS

- B12AD Euro Bar
- D23 Water Resistant Washer
- B12A D/R Thread Bar Accessories

HOW TO ORDER

Specify: (1) quantity, (2) name, (3) length. Example: 500 pcs. B12A D/R Thread Bar, 20'-0" long.

ORDERING INFORMATION

D/R THREAD BAR - N/A

| Product Code | Description | Weight |
|--------------|--|---------|
| 121710 | 20MM X 20'-0"; SWL=32,000 LBS NON- WELDABLE | 1.60 LB |
| 121715 | 15MM X 20'-0"; SWL=20,000 LBS | 1.00 LB |

D/R THREAD BAR ACCESSORIES - N/A

| Product Code | Description | Weight |
|--------------|-----------------|---------|
| 100015 | 3/4" B12A EGALV | 4.30 LB |

MANUFACTURER

Dayton Superior Corporation 1125 Byers Road Miamisburg, OH 45342

Customer Service: 888-977-9600 Technical Services: 877-266-7732 Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.

Page 1 of 1 File Date: 2/26/2018