



TECHNICAL DATA SHEET

DESCRIPTION

B29 Loose Plastic Cones are manufactured from PC/ABS material.

APPLICATION

B29 Loose Plastic Cones are used with B1 and B2 Coil Ties.



FEATURES

- B29 Loose Plastic Cones are placed on the coil bolts after the coil bolts have been inserted through the form face but prior to threading the bolt into the coil tie.
- The large end of the cone provides sufficient bearing surface to prevent crushing of the plywood around the bolt hole.
- B29 plastic cones are removed from the concrete with a B15 Cone Removal Wrench and can be reused.
- Cones are to be used for spreader action only and are not designed for scaffold bracket or other accessory loads.

TECHNICAL DATA

B29 LOOSE PLASTIC CONE SELECTION CHART

Bolt Diameter	Setback (Cone Length) A	B	C
1/2"	1"	1-1/4"	1"
1/2"	1-1/2"	1-1/4"	1"
1/2"	2"	1-1/4"	1"
3/4"	1"	1-5/8"	1-7/16"
3/4"	1-1/2"	1-5/8"	1-7/16"
3/4"	2"	1-5/8"	1-7/16"
1"	2-1/2"	2-1/8"	1-3/4"
1-1/4"	2-1/2"	2-3/8"	2-1/8"

RELATED PRODUCTS

- B1 or B2 Coil Ties
- B15 Cone Removal Wrench

HOW TO ORDER

Specify: (1) quantity, (2) name, (3) bolt diameter, (4) setback.

Example: 2,000 pcs. B29 Loose Plastic Cone, 1/2", 2" setback.

Additional sizes are available made to order. Please call for lead time, availability and pricing.

ORDERING INFORMATION

PLASTIC CONES FOR COIL TIES LOOSE CONE PLASTIC

Product Code	Description	Weight
35121	1/2" X 1" SETBACK	0.03 LB
35125	3/4" X 1" SETBACK	0.05 LB
35128	1" X 2-1/2" SETBACK	0.20 LB

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com

TECHNICAL DATA SHEET

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.