

TECHNICAL DATA SHEET


DESCRIPTION

B39 Wing Nut is made of ductile iron.

APPLICATION

B39 can be used for any application requiring quick removal and application of a nut.





FEATURES

- Safe Working Loads are based on 1/2" setback from face of concrete.
- Safe Working Load provides a factor of safety of approximately 2 to 1.

TECHNICAL DATA

B39 Wing Nut Selection Chart						
Coil Rod Diameter	Safe Working Load Tension (lbs.)	A	в	с	D	
1/2"	9,000	5"	1-1/4"	2-3/8"	1-3/8"	
3/4"	18,000	5-7/8"	1-1/4"	2-1/2"	1-3/4"	
7/8"	18,000	6"	1-5/8"	2-3/4"	1-3/4"	
1"	38,000	6"	1-5/8"	3"	2"	
1-1/4"	52,000	5-5/8"	1-5/8"	2-3/4"	2-1/4"	
1-1/2"	80,000	6-3/4"	1-7/8"	2-3/4"	2-7/8"	

RELATED PRODUCTS

- D9 Taper Tie
- D30 She-Bolt

HOW TO ORDER

Specify: (1) quantity, (2) name, (3) diameter

ORDERING INFORMATION

Product Code	Description	Weight
30580	1/2"	0.65 LB
30581	3/4"	0.976 LB
30586	7/8"	1.1558 LB
30582	1"	1.09 LB
30583	1-1/4"	1.296 LB
30584	1-1/2"	2.8725 LB
143674	1-1/4"	1.296 LB

MANUFACTURER

Dayton Superior Corporation 1125 Byers Road Miamisburg, OH 45342 Customer Service: 888-977-9600 Technical Services: 877-266-7732 Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES) Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or at a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS COR A DAPTICUL AD RURDOSE OR OTHERWISE THE REMEDICE FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.