

B40 PLASTIC SETBACK PLUG

Medium/Heavy Forming


TECHNICAL DATA SHEET

DESCRIPTION

B40 Plastic Setback Plug is fabricated from high density polyethelene.

APPLICATION

B40 Plastic Setback Plugs seal the hole left when Screw-On Cones are removed from the concrete.



FEATURES

- Plugs are available for use with 1/2" diameter coil ties setback 1" or 1-1/2" from the concrete face.
- Plugs are stocked in light and dark grey to blend with the natural color of the concrete.
- Contrasting colors are available on special order.

RELATED PRODUCTS

- B3 Coil Tie
- B30 Screw-On Plastic Cones

HOW TO ORDER

Specify: (1) quantity, (2) name, (3) color. Example: 2,000 pcs. B40 Plastic Setback Plugs, light grey.

ORDERING INFORMATION

Product Code	Description	Weight
63421	1/2" X 1" SETBACK	0.0112 LB
63422	1/2" X 1-1/2" SETBACK	0.0112 LB
120160	3/4" X 1-3/4" SETBACK	0.026 LB

MANUFACTURER

Dayton Superior Corporation 1125 Byers Road Miamisburg, OH 45342 Customer Service: 888-977-9600 Technical Services: 877-266-7732 Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.