

TECHNICAL DATA SHEET

DESCRIPTION

Bar Chair support has a 4-point contact that positions reinforcing bar or light steel to proper cover height.

APPLICATION

To support wide spaced light steel in slab or deck construction.

PRODUCT SPECIFICATION

- Cover height 3/4" to 2", 1/4" increments
- Available in; Galvanized, Plastic tipped, Plastic Dipped, Epoxy and Plain



FEATURES

- Formed cradle to place reinforcing bar or wire mesh
- Foot designed to set on most forming surfaces
- 4-point support base for stability
- Light weight,

BENEFITS

- Easy to place

HOW TO SPECIFY

Bar Chair support shall be as manufactured by Dayton Superior Corporation.

APPROVALS / COMPLIANCE

- ACI ACI-SP66-04, ACI-315 and ACI-315R

RELATED PRODUCTS

- JC – Joist Chair
- BCP – Bar Chair with Plate
- SC – Speed Chair
- HC – Individual High Chair
- HCP – Individual High Chair with Plates

HOW TO ORDER

- Specify:
 1. Quantity,
 2. Name,
 3. Height,
 4. Finish,

ORDERING INFORMATION

PLAIN

Product Code	Description	Weight
75400	3/4"	0.055 LB
75410	1"	0.0605 LB
75420	1-1/4"	0.06 LB
75430	1-3/4"	0.08 LB
75440	1-3/4"	0.1 LB
75450	2"	0.11 LB

GALVANIZED

Product Code	Description	Weight
75401	3/4"	0.05 LB
75411	1"	0.06 LB
75421	1-1/4"	0.08 LB
75431	1-1/2"	0.08 LB
75441	1-3/4"	0.1 LB
75451	2"	0.11 LB

PLASTIC TIPPED

Product Code	Description	Weight
75406	3/4"	0.098 LB
75416	1"	0.1 LB
75426	1-1/4"	0.109 LB
75436	1-1/2"	0.111 LB
75446	1-3/4"	0.122 LB

PLASTIC DIPPED

Product Code	Description	Weight
75403	3/4"	0.07 LB
75413	1"	0.08 LB
75423	1-1/4"	0.09 LB
75433	1-1/2"	0.09 LB
75443	1-3/4"	0.1 LB
75453	2"	0.1 LB

TECHNICAL DATA SHEET

EPOXY COATED

Product Code	Description	Weight
75407	3/4"	0.057 LB
75417	1"	0.0725 LB
75427	1-1/4"	0.072 LB
75437	1-1/2"	0.08 LB
75447	1-3/4"	0.0825 LB
75457	2"	0.0935 LB

MANUFACTURER

Dayton Superior Corporation
1125 Byers Road
Miamisburg, OH 45342
Customer Service: 888-977-9600
Technical Services: 877-266-7732
Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.