

## TECHNICAL DATA SHEET

### DESCRIPTION

L shape wire with a welded 45° strut supports exterior overhang bracket while other end is threaded with a length of 1/2" coil thread to supports interior decking formwork.

### APPLICATION

Fixed hanger placed over steel beam or concrete girder and permits adjustment to grade after formwork is installed. Break back capability on horizontal leg of hanger. For concrete girders of box beams, legs formed at 15° to vertical are suggested. There is a 1" break back feature on horizontal leg of the fixed hanger

### PRODUCT SPECIFICATION

- 2 to 1 safety factor
- 4,500 lbs. per side safe working load
- Hanger must have equal load on both sides of beam
- Available; E-Galv. Epoxy and Plain




### FEATURES

- 45° to strut
- Vertical leg angle at 90° or 15°
- 1" break back

### HOW TO SPECIFY

Coil Rod Hanger shall be specified as manufactured by Dayton Superior Corporation.

### INSTALLATION



Optional for  
Concrete  
Beams

### RELATED PRODUCTS

- B11 Flat Washer
- B13 Coil Nut
- B42 Batter Washer
- C41 Coil Rod Hanger

### HOW TO ORDER

- Specify;
  - 1.Quantity
  - 2.Name
  - 3.Flange width
  - 4.Total drop
  - 5.Length of thread
  - 6.Bend angle

### MANUFACTURER

Dayton Superior Corporation  
1125 Byers Road  
Miamisburg, OH 45342  
Customer Service: 888-977-9600  
Technical Services: 877-266-7732  
Website: [www.daytonsuperior.com](http://www.daytonsuperior.com)

### WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.