

TECHNICAL DATA SHEET

DESCRIPTION

Pres-Steel Hook Half Hanger has a 45° end clip that accepts a 1/2" diameter coil bolt. End clip is welded at one end of wire with a short 90° bend at the other end. Welded to the 90° short bent end is a "J" hook steel plate.

APPLICATION

Pres-Steel Hook Half Hanger sits on top of steel beam where the hooked end engages to edge of the flange anchoring the hanger.

PRODUCT SPECIFICATION

- 2 to 1 safety factor
- 3,500 lbs. = safe working load
- 7,000 lbs. = ultimate strength
- Available; HDG, E-Galv. Epoxy and Plain



FEATURES

- 45° end clip
- "J" hook plate welded to one end

BENEFITS

- Easy to install

HOW TO SPECIFY

C63 Pres-Steel Hook Half Hanger shall be specified as manufactured by Dayton Superior Corporation.

RELATED PRODUCTS

- B12 Continuous Coil Threaded Rod
- B13 Coil Nut
- B42 Batter Washer
- C67 Tie Bar Beam Clip Pre-Stress Hanger
- C68 Pres-Steel Ty-Down Half Hanger

HOW TO ORDER

- Specify;
 - 1.Quantity
 - 2.Name
 - 3.Flange width
 - 4.Flange thickness
 - 5.Finish

MANUFACTURER

Dayton Superior Corporation
1125 Byers Road
Miamisburg, OH 45342
Customer Service: 888-977-9600
Technical Services: 877-266-7732
Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.