

TECHNICAL DATA SHEET

DESCRIPTION

Dayton Superior Combination Dobie, Series: CCD is used for supporting wire mesh or rebar to ensure proper placement during construction. It has a standard strength of 4,000 PSI. The CCD comes in multiple heights within a single unit. CRSI Class 1, D.O.T Approved.



FEATURES

- Load Capacity: Standard Strength is 4,000 PSI.
- Standards: CRSI Class 1, D.O.T Approved
- Usage: For Supporting Wire Mesh or Rebar to Ensure Proper Placement

Technical Data

STANDARD 4000 STRENGTH

SIZE	COVER
2" X 2" X 2-1/2"	1-1/2", 2", OR 2-1/2"
3" X 3" X 4"	2-1/2", 3", 3-1/2", OR 4"

APPROVALS / COMPLIANCE

- Meets all requirements and qualifies as a CRSI Class 1 Bar Support.
- On-Grade or Below Grade, D.O.T. Approved (in most states).

ORDERING INFORMATION

COMBINATION DOBIES - STANDARD

Product Code	Description	Weight
123718	2" X 2" X 2-1/2"	0.82 LB
123719	3" X 3" X 4"	2.85 LB

MANUFACTURER

Dayton Superior Corporation
1125 Byers Road
Miamisburg, OH 45342
Customer Service: 888-977-9600
Technical Services: 877-266-7732
Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.