


## TECHNICAL DATA SHEET

**DESCRIPTION**

Dowel Dobies are concrete cubes used to support wire mesh or rebar at proper cover height on grade.

**PRODUCT SPECIFICATION**

- Available cover heights: 1-1/2" to 4" in 1/2" increments


**FEATURES**

- Designed with multiple heights within a single unit
- Standard 4000 psi compressive strength.

**BENEFITS**

- Same expansion coefficient as concrete

**APPROVALS / COMPLIANCE**

- ACI-315-99
- On-Grade or Below-Grade, D.O.T. Approved (in most states)

**HOW TO ORDER**

- Specify (1) quantity, (2) name, (3) cover height

Example: 500, Dowel Dobies, 5" cover height

Additional sizes available through made to order. Please call for lead time, pricing and availability.

**ORDERING INFORMATION**
**DOWEL DOBIES - STANDARD**

Product Code	Description	Weight
123721	3" X 4" X 5"	4.799 LB

**MANUFACTURER**

Dayton Superior Corporation  
 1125 Byers Road  
 Miamisburg, OH 45342  
 Customer Service: 888-977-9600  
 Technical Services: 877-266-7732  
 Website: www.daytonsuperior.com

**WARRANTY (ACCESSORIES)**

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.