

## TECHNICAL DATA SHEET

### DESCRIPTION

Clean Strip Ultra J3 is a premium, low odor, ready-to-use, chemically reactive form release that is V.O.C. compliant in all regulatory regions. It is ideal for architectural and precast concrete and for general forming applications. Clean Strip Ultra J3 works to ensure clean, positive release of plywood, fiberglass, aluminum, steel and other concrete forming materials. Clean Strip Ultra J3 prolongs the life of plywood forms, and acts to reduce rusting of steel forms. Properly applied, Clean Strip Ultra J3 is non-staining, reduces the number of surface air voids (bugholes) and will not interfere with the adhesion of subsequent coatings.

### USE

Clean Strip Ultra J3 chemically releases hardened concrete from steel, aluminum, plywood, and composition forms. In conjunction with good concrete placement and forming technique, this quality product promotes easy stripping and minimizes form clean up. It is non-staining, and reduces the number of surface air voids (bugholes) on regular and superplasticized concrete.

### FEATURES

- Coverage up to 2,000 sq. ft./gal.
- Extended form life
- Reduced labor normally used to clean forms
- Minimizes concrete surface dusting
- Helps prevent rusting of steel forms
- Compatible with most form liners
- Low odor Clean Strip™ Ultra J3 is suitable for use on all forms except expanded polystyrene.

### VOC

Less than 100 g/L. Compliant with Canadian and U.S. VOC regulations for Concrete Form Release agents including Federal EPA, OTC, LADCO, SCAQMD & CARB.

### Estimating Guide

	Sq. Feet per gallons	Sq. Meters per Liters
Steel	2500	61.5
Aluminum	2500	31.5
Medium Density Plywood	1500-2000	36.9-49.2
High Density Plywood	2500	61.5
Rough Sawn Lumber 1st coat	1000	24.6
2nd coat	1500	36.9
Texture and absorption of forming material will dictate final coverage rate. Prior to coating plywood forms, apply one or two heavy brush coats to edges to ensure ease of form removal.		

### Packaging

PRODUCT CODE	PACKAGE	SIZE	
		Gallons	Liters
309133	Pail	5	18.9
309134	Drum	55	208.2
309135	Tote	275	1041

### STORAGE

Store in dry environment.  
Shelf life is three years from date of manufacture.

### Surface Preparation:

Surfaces to be treated should be clean and free of water, dust and dirt or residues that might transfer to the final concrete surface.

### Placement:

Apply during dry weather with low pressure spray, roller or brush. Apply uniformly in a thin but continuous film to assure proper coverage. For best results apply to forms before each use. Avoid applying too heavily. Wipe excessive material from forms prior to installing forms and concrete placement. Prior to coating plywood forms, apply one or two heavy brush coats to edges to ensure complete water-proofing protection.

### CLEAN UP

Sprayers and other equipment may be cleaned with Citrus Cleaner J48 or other solvent degreaser.

## TECHNICAL DATA SHEET

**LIMITATIONS****FOR PROFESSIONAL USE ONLY**

Not for use as a bond breaker or concrete release agent for tiltup concrete construction. Requires recoating after each use. Do not apply onto reinforcing steel. **DO NOT OVER APPLY.** Over-application could cause excessive surface dusting and/or transfer to concrete. When any material is to be applied over the newly formed concrete, follow the application instructions of the material, manufacturer.

**PRECAUTIONS****READ SDS PRIOR TO USING PRODUCT**

- May cause cancer.
- Wear protective clothing, gloves and eye protection (goggles, safety glasses and/or face shield)
- If swallowed, immediately call a poison center/doctor. Do not induce vomiting.
- Do not take internally
- In case of ingestion, seek medical help immediately
- May be fatal if swallowed and enters airways.
- If eye contact occurs, flush immediately with clean water and seek medical help as needed
- Dispose of waste material in accordance with federal, state and local requirements

**MANUFACTURER**

Dayton Superior Corporation  
1125 Byers Road  
Miamisburg, OH 45342  
Customer Service: 888-977-9600  
Technical Services: 877-266-7732  
Website: [www.daytonsuperior.com](http://www.daytonsuperior.com)

**WARRANTY**

Dayton Superior Corporation ("Dayton") warrants for 12 months from the date of manufacture or for the duration of the published product shelf life, whichever is less, that at the time of shipment by Dayton, the product is free of manufacturing defects and conforms to Dayton's product properties in force on the date of acceptance by Dayton of the order. Dayton shall only be liable under this warranty if the product has been applied, used, and stored in accordance with Dayton's instructions, especially surface preparation and installation, in force on the date of acceptance by Dayton of the order. The purchaser must examine the product when received and promptly notify Dayton in writing of any non-conformity before the product is used and no later than 30 days after such non-conformity is first discovered. If Dayton, in its sole discretion, determines that the product breached the above warranty, it will, in its sole discretion, replace the non-conforming product, refund the purchase price or issue a credit in the amount of the purchase price. This is the sole and exclusive remedy for breach of this warranty. Only a Dayton officer is authorized to modify this warranty. The information in this data sheet supersedes all other sales information received by the customer during the sales process. **THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM, TRADE OR OTHERWISE.**

Dayton shall not be liable in contract or in tort (including, without limitation, negligence, strict liability or otherwise) for loss of sales, revenues or profits; cost of capital or funds; business interruption or cost of downtime, loss of use, damage to or loss of use of other property (real or personal); failure to realize expected savings; frustration of economic or business expectations; claims by third parties (other than for bodily injury), or economic losses of any kind; or for any special, incidental, indirect, consequential, punitive or exemplary damages arising in any way out of the performance of, or failure to perform, its obligations under any contract for sale of product, even if Dayton could foresee or has been advised of the possibility of such damages. The Parties expressly agree that these limitations on damages are allocations of risk constituting, in part, the consideration for this contract, and also that such limitations shall survive the determination of any court of competent jurisdiction that any remedy provided in these terms or available at law fails of its essential purpose.