

## TECHNICAL DATA SHEET

### DESCRIPTION

Plain style Dobie rebar supports offer multiple sizes for various cover requirements and are used for spacing the reinforcement and setting cover height above grade or formwork. Suited for footing and foundation reinforcement work where heavy concentrations of rebar occur.

### APPLICATION

Supports rebar mats and wire mesh to provide proper concrete cover of rebar. Used primarily in horizontal rebar applications.

### PRODUCT SPECIFICATION

- Manufactured using standard 4000 psi concrete.



### FEATURES

- Available in cover heights from 1" to 18"
- Suited for on-grade reinforcement

### TECHNICAL DATA

CPD Standard and Heavy Duty Dobies

Product Size	Cover
2" X 2" X 1"	1"
2" X 2" X 1-1/2"	1-1/2"
2" X 2" X 2"	2"
3" X 3" X 2"	2" OR 3"
3" X 3" X 3"	3"

### APPROVALS / COMPLIANCE

- CRSI Class 1 Bar Support
- DOT Approved (in most states)

### RELATED PRODUCTS

- CWD Wire Dobies
- CCD Combination Dobies
- CDD Dowel Dobies

### HOW TO ORDER

- Additional sizes available through made to order. Please call for lead time, pricing and availability.

### ORDERING INFORMATION

#### PLAIN DOBIES - STANDARD

Product Code	Description	Weight
123711	2" X 2" X 1-1/2"	0.509 LB
123713	2" X 2" X 2"	0.701 LB
123714	3" X 3" X 2"	1.586 LB
123715	3" X 3" X 3"	2.108 LB

#### PLAIN DOBIES - HEAVY DUTY

Product Code	Description	Weight
220371	3" X 3" X 2"	1.610 LB
220376	3" X 3" X 3"	2.280 LB

### MANUFACTURER

Dayton Superior Corporation  
1125 Byers Road  
Miamisburg, OH 45342  
Customer Service: 888-977-9600  
Technical Services: 877-266-7732  
Website: [www.daytonsuperior.com](http://www.daytonsuperior.com)

**TECHNICAL DATA SHEET****WARRANTY (ACCESSORIES)**

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.