

**TECHNICAL DATA SHEET** 

# DESCRIPTION


Dayton Superior Combination Dobie, Series: CWD is used for supporting wire mesh or rebar to ensure proper placement during construction. It has a standard strength of 4,000 PSI. The CWD comes in mulple heights within a single unit. CRSI Class 1, D.O.T Approved.

## APPLICATION

Supports rebar mats and wire mesh to provide proper concrete cover of rebar that is used primarily in horizontal rebar applications.

## **PRODUCT SPECIFICATION**

■ Manufactured using standard 4000 psi



## **FEATURES**

- Available in cover heights from 3/4" to 5"
- Suited for On-Grade, Below-Grade, Metal Decks, Side-Form Spacers, and Pools

### **APPROVALS / COMPLIANCE**

- Meets all requirements and qualifies as a CRSI Class 1 Bar Support.
- On-Grade or Below Grade, D.O.T. Approved (in most states).

## **RELATED PRODUCTS**

- CCD Combination Dobies
- CDD Dowel Dobies
- CPD Plain Dobies

## HOW TO ORDER

Additional sizes available through made to order. Please call for lead time, pricing and availability.

## **ORDERING INFORMATION**

#### WIRE DOBIES - STANDARD

Product Code	Description	Weight
123701	2" X 2" X 1"	0.326 LB
123702	2" X 2" X 1-1/2"	0.536 LB
123704	2" X 2" X 2"	0.734 LB
123707	3" X 3" X 3"	2.193 LB

### MANUFACTURER

Dayton Superior Corporation 1125 Byers Road Miamisburg, OH 45342 Customer Service: 888-977-9600 Technical Services: 877-266-7732 Website: www.daytonsuperior.com

### WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.

