TECHNICAL DATA SHEET



## DESCRIPTION
DeGrease is an industrial-strength, versatile, concentrated cleaner for cleaning a multitude of hard surfaces. Cleans oil, grease, dirt and grime from asphalt, concrete, metal and painted walls. DeGrease has less than 0.5% VOC's, is safe to use, is environmentally friendly and is ideal for any cleaning job.

## USE
General surface cleaning, asphalt and concrete. DeGrease will remove wax, form release, and lubricants. Used full strength, DeGrease will remove grease and oil build up from equipment, floors, and concrete surfaces.

## FEATURES
- Low Odor
- 100% Biodegradable
- Won't Harm Sealants
- Removes grease, oil and form release

## PROPERTIES
Flash Point: None

pH Level: 12.18 pH of 1/10 wt/wt solution in soft water.

Odor: Low odor

**Note:**
Surfaces wet with DeGrease may be slippery. Dispose of waste material in accordance with federal, state and local requirements

## VOC
Contains 0.5 g/L. Compliant with all Canadian and U.S. VOC regulations for Concrete Form Release agents including Federal EPA, OTC, LADCO, SCAQMD & CARB.

## Packaging

| PRODUCT CODE | PACKAGE | SIZE | |
|---|---|---|---|
| | | Gallons | Liters |
| 145689 | Jug | 1 | 3.8 |
| 145690 | Pail | 5 | 18.9 |

## STORAGE
Store between 36°F (2°c) and 100°F (38°C). Shelf life Is 24 months from date of manufacture in original unopened containers.

## APPLICATION
Concentrated Formula Mixing Directions
Concrete / Floors: Add 4 ounces of DeGrease per gallon of water. Apply freely to the floor or hard surface with a mop or sponge. Pick-up and rinse with clean water.

Light / Medium Soils: Add 4 ounces of DeGrease per gallon of water. Apply to surface and allow to penetrate. A light scrubbing action will increase cleaning effectiveness. Rinse thoroughly with clean water.

Heavy Soils: Mix one part DeGrease to one part water for tough to remove soils. Apply to surface and allow to penetrate until soils have been loosened. Scrubbing action will increase cleaning effectiveness. Repeat if necessary. Rinse thoroughly with clean water.

Floor Machine Application: Mix one part DeGrease to one part water. Apply freely to surface. Let sit 5-10 minutes before agitating surface with floor machine. Pick-up and rinse with clean water.

## LIMITATIONS
Keep containers tightly sealed when not in use
Protect from freezing

## PRECAUTIONS

## READ SDS PRIOR TO USING PRODUCT
- KEEP OUT OF THE REACH OF CHILDREN.
- Do not take internally.
- Avoid prolonged contact with skin.
- Avoid ingestion of material.
- If swallowed, do not induce vomiting – call physician.
- Avoid contact with eyes.
- Protective clothing is recommended.
- Protective goggles are recommended
- If splashed in eyes, wash immediately with clean water and call physician if irritation persists.
- Contact areas should be thoroughly washed with soap and water.
- Additional precautions, safety information and first aid treatments are contained in the Material Safety Data Sheet.

Sec

## MANUFACTURER

Dayton Superior Corporation
1125 Byers Road
Miamisburg, OH 45342
Customer Service: 888-977-9600
Technical Services: 877-266-7732
Website: www.daytonsuperior.com

## WARRANTY

Dayton Superior Corporation ("Dayton") warrants for 12 months from the date of manufacture or for the duration of the published product shelf life, whichever is less, that at the time of shipment by Dayton, the product is free of manufacturing defects and conforms to Dayton's product properties in force on the date of acceptance by Dayton of the order. Dayton shall only be liable under this warranty if the product has been applied, used, and stored in accordance with Dayton's instructions, especially surface preparation and installation, in force on the date of acceptance by Dayton of the order. The purchaser must examine the product when received and promptly notify Dayton in writing of any non-conformity before the product is used and no later than 30 days after such non-conformity is first discovered. If Dayton, in its sole discretion, determines that the product breached the above warranty, it will, in its sole discretion, replace the non-conforming product, refund the purchase price or issue a credit in the amount of the purchase price. This is the sole and exclusive remedy for breach of this warranty. Only a Dayton officer is authorized to modify this warranty. The information in this data sheet supersedes all other sales information received by the customer during the sales process. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM, TRADE OR OTHERWISE.

Dayton shall not be liable in contract or in tort (including, without limitation, negligence, strict liability or otherwise) for loss of sales, revenues or profits; cost of capital or funds; business interruption or cost of downtime, loss of use, damage to or loss of use of other property (real or personal); failure to realize expected savings; frustration of economic or business expectations; claims by third parties (other than for bodily injury), or economic losses of any kind; or for any special, incidental, indirect, consequential, punitive or exemplary damages arising in any way out of the performance of, or failure to perform, its obligations under any contract for sale of product, even if Dayton could foresee or has been advised of the possibility of such damages. The Parties expressly agree that these limitations on damages are allocations of risk constituting, in part, the consideration for this contract, and also that such limitations shall survive the determination of any court of competent jurisdiction that any remedy provided in these terms or available at law fails of its essential purpose.

Sec