

TECHNICAL DATA SHEET

DESCRIPTION

A chemically active liquid formulated to remove concrete build up from concrete forms, tools, mixers, hardware, shoring, ready-mix truck, aluminum form and post tension rods. Dissolve It helps avoid the damaging effects of sandblasting, chipping or hammering concrete from equipment.

USE

Removes hardened concrete from concrete handling or finishing equipment such as: screeds, trowels, concrete forms, anchors, hardware, mixers or ready-mix truck. Dissolve It will also remove masonry mortar from equipment, mixers, etc.

FEATURES

- Prevents damage to equipment caused by physical removal such as sandblasting or hammering
- Ready-to-use; no mixing or dilution
- Low odor
- Dissolves concrete and mortar on tools, equipment, and forms
- Etches concrete floors

VOC

Contains less than 150 g/L.

Packaging

PRODUCT CODE	PACKAGE	SIZE	
		Gallons	Liter
145539	Drum	55	208.2
145538	Pail	5	18.9
145537	Jug (4 per case)	1	3.8

STORAGE

Dissolve It should be stored in tightly sealed original factory containers. Store in a horizontal position to prevent moisture accumulation on the drum head. Do not allow to freeze. Shelf life in unopened containers is 24 months from date of manufacture.

APPLICATION

Brush or spray apply ready-to-use Dissolve It at approximately 75 sq. ft./gal.(1.8 m2/L), to the hardened concrete surface or mortar to be removed. (If possible, immersion is the best application method). A light foaming action will occur when applied. Allow to soak and agitate.

After the cement paste has softened remove with a scraper or power washer.

The reaction between Dissolve It and concrete (cement paste) will cause a fizzing. When the fizzing stops, Dissolve It is neutralized (pH 7) or all the material has been dissolved. Once Dissolve It is neutralized or inert, dispose in accord with local city, county, or state ordinances.

Heavy build-up on tools may require repeated applications to remove the concrete down to clean metal. When working on vertical surfaces, several applications may be required to loosen hardened material due to run down.

CLEAN UP

Use soap and water to clean equipment.

FOR PROFESSIONAL USE ONLY

Dissolve It may slightly etch clean metal. Avoid excess exposure to clean metal surfaces. Perform an exposure test on magnesium tools to insure compatibility.

PRECAUTIONS

READ SDS PRIOR TO USING PRODUCT

- Avoid hazards by following all precautions found in the Safety Data Sheet (SDS), product labels and technical literature.
- Please read this information prior to using the product.

MANUFACTURER

Dayton Superior Corporation
1125 Byers Road
Miamisburg, OH 45342
Customer Service: 888-977-9600
Technical Services: 877-266-7732
Website: www.daytonsuperior.com

WARRANTY

Dayton Superior Corporation ("Dayton") warrants for 12 months from the date of manufacture or for the duration of the published product shelf life, whichever is less, that at the time of shipment by Dayton, the product is free of manufacturing defects and conforms to Dayton's product properties in force on the date of acceptance by Dayton of the order. Dayton shall only be liable under this warranty if the product has been applied, used, and stored in accordance with Dayton's instructions, especially surface preparation and installation, in force on the date of acceptance by Dayton of the order. The purchaser must examine the product when received and promptly notify Dayton in writing of any non-conformity before the product is used and no later than 30 days after such non-conformity is first discovered. If Dayton, in its sole discretion, determines that the product breached the above warranty, it will, in its sole discretion, replace the non-conforming product, refund the purchase price or issue a credit in the amount of the purchase price. This is the sole and exclusive remedy for breach of this warranty. Only a Dayton officer is authorized to modify this warranty. The information in this data sheet supersedes all other sales information received by the customer during the sales process. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM, TRADE OR OTHERWISE.



TECHNICAL DATA SHEET

Dayton shall not be liable in contract or in tort (including, without limitation, negligence, strict liability or otherwise) for loss of sales, revenues or profits; cost of capital or funds; business interruption or cost of downtime, loss of use, damage to or loss of use of other property (real or personal); failure to realize expected savings; frustration of economic or business expectations; claims by third parties (other than for bodily injury), or economic losses of any kind; or for any special, incidental, indirect, consequential, punitive or exemplary damages arising in any way out of the performance of, or failure to perform, its obligations under any contract for sale of product, even if Dayton could foresee or has been advised of the possibility of such damages. The Parties expressly agree that these limitations on damages are allocations of risk constituting, in part, the consideration for this contract, and also that such limitations shall survive the determination of any court of competent jurisdiction that any remedy provided in these terms or available at law fails of its essential purpose.

Sec