

TECHNICAL DATA SHEET

DESCRIPTION

The Dayton Superior F42W Loop Ferrule Insert is fabricated by welding a loop strut to a closed-end ferrule and is well suited for structural connections and the suspension of equipment, piping, etc. The F42W is the F42, but includes mounting washers.

FEATURES

- Available in Plain, Electro Galvanized and Type 304 Stainless Steel Finishes.
- Safe Working Load provides a factor of safety of approximately 3 to 1 in 3,000 psi normal weight concrete.
- Safe Working Loads are based on 1/2" setback from face of concrete.
- Minimum spacing between inserts is twice the minimum corner distance.
- Includes mounting washers

TECHNICAL DATA

F42 Loop Ferrule Insert Selection Chart							
Bolt Diameter & Threads per Inch	Min Edge Distance	Min Corner Distance	SWL Tension	SWL Shear	Max Bolt Engagement	A	B
1/4" - 20 NC	5"	5"	650 lbs.	650 lbs.	3/4"	2-3/4"	0.243"
3/8" - 16 NC	5"	5"	2,000 lbs.	1,260 lbs.	3/4"	2-3/4"	0.243"
	10"	15"	2,000 lbs.	2,000 lbs.			
1/2" - 13 NC	5"	5"	2,000 lbs.	1,280 lbs.	1"	2-3/4"	0.243"
	7"	10"	2,000 lbs.	2,000 lbs.			
5/8" - 11 NC	5"	7"	2,000 lbs.	1,990 lbs.	1-1/8"	3-1/2"	0.258"
	5"	7"	2,000 lbs.	2,000 lbs.			
3/4" - 10 NC	5"	7"	2,200 lbs.	1,990 lbs.	1-1/8"	3-1/2"	0.258"
	8"	8"	2,200 lbs.	2,200 lbs.			
7/8" - 9 NC	8"	8"	5,300 lbs.	4,060 lbs.	1-1/8"	6"	0.375"
	10"	15"	5,300 lbs.	5,300 lbs.			
1" - 8 NC	8"	8"	5,300 lbs.	4,060 lbs.	1-1/8"	6"	0.375"
	10"	15"	5,300 lbs.	5,300 lbs.			

Safe Working Load provides a factor of safety of approximately 3 to 1 in 3,000 psi normal weight concrete. Safe Working Loads are based on 1/2" setback from face of concrete.

ORDERING INFORMATION

LOOP FERRULE INSERT W/ MOUNTING WASHER - N/A

Product Code	Description	Weight
49703	1/2" PLAIN 13NC	0.21 LB
49705	5/8" PLAIN 11NC	0.34 LB
49707	3/4" PLAIN 10NC	0.38 LB
100184	7/8" HOT DIPPED GALV. 9NC	0.48 LB

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.